

APC SRT192RMBP UPS akumuliatorius 192 V

Gamintojas: **APC** · Modelis: **SRT192RMBP** · EAN: **731304301776** · Prekės kodas: **551268**



2 307,91 €

Kaina su PVM

Be PVM: **1 907,36 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

✓ Juoda

✓ 1 vnt

✓ 192 V



Aprašymas

Extend runtime

By connecting one or more APC Smart-UPS On-Line SRT external battery packs to the corresponding APC Smart-UPS On-Line SRT, you can easily increase the number of minutes that the APC UPS can independently supply emergency power. A runtime of several hours is even possible.

Extend lifespan

The SRT192RMBP contains two (APCRBC140) internal battery cartridges and these can be easily, safely and independently replaced by the user. This without having to disconnect the SRT192RMBP or switch off the corresponding APC SRT UPS and/or connected equipment. This way you can easily and cheaply extend the lifespan of the external APC battery pack and your equipment always remains online.

Easy to use

You can easily connect an APC Smart-UPS On-Line SRT external battery pack to the UPS or to another SRT192RMBP using the included connector. Thanks to the included 4-post rail kit, you can easily mount it in a rack.

Warranty extension

The factory warranty of the SRT192RMBP is 2 years and can be upgraded to 5 years with the APC service pack (WBEXTWAR3YR-SP-04).

This product is part of the Smart-UPS battery systems, providing extended runtime to SRT mission critical applications. This extendable-run battery pack provides extended runtime during prolonged power outages. Embedded monitoring at the cell, module, and cabinet level provides data of battery runtime and health. It is a lead-acid battery with a 2-year warranty. Its dimensions are 683mm (depth) x 432mm (height) x 130mm (width) and weighs 91.0kg. Ideal for Smart-UPS on-line mission critical applications. It conforms to OSHPD.

Techninė specifikacija

Savybės	
Baterijos įtampa	192 V
Baterijų skaičius	1 vnt
Produkto spalva	Juoda
Sertifikatai	
Atitikties sertifikatai	RoHS
Svoris ir matmenys	
Svoris	91 kg
Plotis	432 mm
Aukštis	130 mm
Ilgis	682 mm
Pakuotės duomenys	
Pakuotės plotis	600 mm
Pakuotės aukštis	420 mm
Pakuotės gylis	1000 mm
Paketo svoris	105,5 kg
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-15 - 45 °C
Darbo santykinės drėgmės diapazonas	0 - 95%
Sandėliavimo santykinis drėgmės diapazonas	0 - 95%
Darbinis aukštis	0 - 3000 m
Ne darbinis aukštis	0 - 15000 m
Logistikos duomenys	
Darniosios sistemos (DS) kodas	85044095

Bendrasis anglies pėdsakas (kg of CO2e) 483,08

Matmenys ir svoris

Matmenys (I × P × A) 100,00cm × 60,00cm × 45,00cm

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 RUEIL MALMAISON, FR

se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt