Switch MIKROTIK Type L3 CRS354-48G-4S+2Q+RM

Gamintojas: **MIKROTIK** · Modelis: **CRS354-48G-4S+2Q+RM** · EAN: **4752224002266** · Prekės kodas: **552193**



543,90 €

Kaina su PVM

Be PVM: **449,50 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt






Aprašymas

Best price and best performance on the market – this 48 port switch will rock any setup, including 40 Gbps devices!

If you are looking for a single switch that will put your network setup ahead of the curve without costing a fortune, look no further. The new CRS354-48G-4S+2Q+RM is an effective and adaptable rackmount solution for managing networks in demanding and busy environments. With this product we aim to set a new price-performance bar – get more features while spending way less!

This powerful switch has 48 x 1G RJ45 ports and 4 x 10G SFP+ ports. There are also 2 x 40G QSFP+ ports for extremely fast fiber connections or linking with other 40 Gbps devices. The total non-blocking throughput is 168 Gbps, switching capacity is 336 Gbps and the forwarding rate reaches 235 Mpps.
Summary: Mikrotik CRS354-48G-4S+2Q+RM. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 48, Console port: RJ-45. Full duplex. Switching capacity: 336 Gbit/s. Power connector: AC-in jack. Rack mounting | Vendor Homepage: https://mikrotik.com/product/crs354_48g_4splus2qplusrm#fndtn-specifications | Switch layer: L2 | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 48 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Console port: RJ-45 | Power connector: AC-in jack | QSFP+ module slots quantity: 2 | SFP+ module slots quantity: 4 | 10G support: Yes | Full duplex: Yes | Forwarding rate: 235 | Switching capacity: 336 | International Protection (IP) code: IPX0 | Product colour: Grey | Rack mounting: Yes | Built-in processor: Yes | Flash memory: 16 | Internal memory: 64 | Processor frequency: 650 | AC input voltage: 100 - 240 | Power consumption (max): 60 | Operating temperature (T-T): -20 - 60 | Depth: 297 | Height: 44 | Width: 443 | Cables included: AC | Rack mount kit: Yes | Certification: CE/RED, EAC, RoHS | Harmonized System (HS) code: 85176990 | Model: MIKROTIK CRS354-48G-4S+2Q+RM | Units per Pallet: 12 | Units per Shipping Box: 3 | Unit Calculated Volume: 0.0234 | Unit Calculated Weight: 5.47

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	58,00cm × 9,00cm × 37,00cm
Svoris	5,12kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903