

Dahua Technology DH-CS4226-24ET-240 tinklo komutatorius Valdomas L2 Gigabit Ethernet (10/100/1000) Maitinimas per Eternetą (PoE) Juoda

Gamintojas: **DAHUA** · Modelis: **CS4226-24ET-240** · EAN: **6923172571267** · Prekės kodas: **552320**



158,90 €

Kaina su PVM

Be PVM: **131,32 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Valdomas L2 Web pagrįstas valdymas
- ✓ Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 26
- ✓ Adreso lentelės dydis: 8000 įrašai Perjungimo pajėgumas: 8,8 Gbit/s
- ✓ Stovo montavimas
- ✓ AC Pridėtas maitinimo šaltinis Maitinimas per Eternetą (PoE)



Aprašymas

Highly intuitive, the Smart Managed Switch can manage local networks. With the DoLink Care platform, it can also perform cloud management. The switch performs operation and maintenance using topology visualization on front-end, transmission and back-end storage devices that are in the security system and IT system. With its full metal design, the switch has great heat dissipation and can operate in temperatures ranging -10°C to 55°C. It offers EMC and has protection against overvoltage, overcurrent, static electricity, lightning strikes, pulses and other types of interference. For the PoE series Smart

Managed Switch, power is supplied up to 250 meters away. The orange port supplies up to 60 W and the red port provides up to 90 W. Also, link aggregation and STP are available on select models to ensure the network remains stable. The switch can be used in small and medium-sized businesses such as supermarkets, offices, restaurants, cafés and

hotels.

Cloud Management

Devices can be managed through the DoLynk Care app and performs real-time monitoring of the network. The app also displays the status of devices, triggers alarms for errors in real time and sends notifications.

Network Topology Management

Supports the LLDP protocol and is able to generate and display the network topology, so that you can quickly identify issues, and perform operation and maintenance remotely on devices that are in the topology.

BT 90W (Red Port)

The red ports support IEEE802.3af, IEEE802.3at, IEEE802.3bt and HiPoE standards, with a maximum output power consumption of 90W per port. Suitable for powering high-power devices.

Long Distance PoE

The transmission distance of a PoE port can be up to 250 m, meeting the requirement of wired transmission (bandwidth reduced to 10 Mbps).

PoE Watchdog

Adopts the innovative PoE Watchdog. PoE Watchdog can be switched on by dialing/turning on the WEB page switch. It enables the switch to automatically detect port status and restart the failed ports to recover connection in case of IPC connection exception. This enables intelligent operation and maintenance management in its true sense and effectively reduces manual maintenance costs.

Loop Protection

When a loop is detected, the loop alarm will be triggered and the elimination mechanism will activate to prevent broadcast storms from occurring.

Techninė specifikacija

Valdymo funkcijos	
Perjungimo tipas	Valdomas
Perjungimo sluoksnis	L2
Web pagrįstas valdymas	Taip
Ryšys	
Pagrindinių perjungimo RJ-45 ethernet prievadų skaičius	26
Pagrindinių perjungimo RJ-45 ethernet prievadų tipas	Gigabit Ethernet (10/100/1000)
Įdiegtų SFP modulių kiekis	0
Įdiegtų SFP+ modulių kiekis	0
Gigabit Ethernet (varinis) portų kiekis	24
SFP modulio angų kiekis	2

Tinklas

Tinklo standartai	IEEE 802.3, IEEE 802.3ad, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G parama	Ne
VLAN palaikymas	Taip
VLANs skaičius	32

Duomenų perdavimas

Adreso lentelės dydis	8000 įrašai
Perjungimo pajėgumas	8,8 Gbit/s
Persiuntimo dažnis	6,55 Mpps
Jumbo Frames palaikymas	Taip
„Jumbo“ kadrai	15000
Paketo buferio atmintis	4 MB

Saugumas

DHCP funkcijos	DHCP client
----------------	-------------

Konstrukcija

Stovo montavimas	Taip
Produkto spalva	Juoda
Korpuso medžiaga	Metalas
Atstatymo mygtukas	Taip

Veikimo charakteristikos

Vidutinis laikas tarp trikčių (MTBF)	562,765 h
--------------------------------------	-----------

Energijos valdymas

Maitinimo šaltinis	AC
Pridėtas maitinimo šaltinis	Taip
Galios suvartojimas (maks.)	265 W

„Power over Ethernet“ (PoE)

Maitinimas per Eternetą (PoE)	Taip
Maitinimo per Eternetą (PoE) galia prievadui	30 W
Bendrosios galios per Eternetą (PoE) charakteriskos	240 W

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	-10 - 55 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C
Darbo santykinės drėgmės diapazonas	5 - 95%
Sandėliavimo santykinis drėgmės diapazonas	5 - 95%

Svoris ir matmenys

Plotis	220 mm
Ilgis	440 mm
Aukštis	44 mm
Svoris	2,47 kg

Pakuotės duomenys

Pakuotės plotis	342 mm
Pakuotės gylis	540 mm
Pakuotės aukštis	90 mm
Paketo svoris	3,12 kg

Matmenys ir svoris

Matmenys (I × P × A)	54,00cm × 34,00cm × 9,00cm
----------------------	----------------------------

Dokumentai ir vaizdo įrašai

[› Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Zhejiang Dahua Technology Co., Ltd

Bin'an Road, Binjiang District No.1187 & 1199,
310053 Hangzhou, CN
dahuasecurity.com

ATSAKINGAS ASMUO ES

Dahua Technology GmbH

Niederkasseler Lohweg 185, 40547 Düsseldorf,
DE
dahuasecurity.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt