



Access Point TP-LINK Omada 1x2.5GbE EAP660HD



Modelis: EAP660HD

Gamintojas: TP-LINK

EAN: 6935364089719

Prekės kodas: 552360

260.98€

Ultra-High Performing
AX3600 Enterprise Wireless for
High-Density Environments

High-Density Connectivity with 4× Increased Capacity
OFDMA* and Uplink & Downlink MU-MIMO** increase network capacity by up to 4× versus Wi-Fi 5 (802.11ac) in high-density environments to connect more devices simultaneously†. Leverage multi-user capabilities and upgrade your business like never before.

Blazing Fast Speed with 8 Spatial Streams

The Omada Wi-Fi 6 Access Point features the latest 802.11ax technologies like 1024 QAM and Long OFDM Symbol, which allows the EAP to boost overall speeds up to 3550 Mbps (2402 Mbps on a 5

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

GHz band and 1148 Mbps on a 2.4 GHz band)†. With 8 spatial streams, multi-user throughput is incredibly increased to drive more applications.

Omada SDN—Smarter Cloud Solution for Business Networking

Omada Software Defined Networking (SDN) platform integrates network devices including access points, switches and gateways, guaranteeing powerful business network with higher efficiency, higher security, and higher reliability.

Optimized Wired Performance with 2.5 GE PoE+ Port

Armed with a 2.5 Gigabit Ethernet Port, the EAP660 HD delivers exceptional multi-gigabit performance to support the insatiable demand for better and faster Wi-Fi. Compatibility with standard 802.3at PoE+ is ideal for flexible deployment.

Seamless Roaming

802.11k/v roaming switches clients automatically to the AP with the optimal signal with a seamless transition when moving.△ This allows sensitive applications like VoIP and video conferences to go uninterrupted.

Boost Network Efficiency in All Aspects

With Rich Advanced Features

Band Steering

Automatically moves dual band devices onto the wider 5GHz band for faster connections.

Load Balance

ensures large numbers of users have smooth network experiences in high-density business networks

Airtime Fairness

Increases average network throughput in heavily congested environments

- Ultra-Fast Wi-Fi 6 Speeds: Simultaneous 1148 Mbps on 2.4 GHz and 2402 Mbps on 5 GHz totals 3550 Mbps Wi-Fi speeds.†
- High-Density Connectivity: 4× increased capacity to connect more devices simultaneously.‡

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Integrated into Omada SDN: Zero-Touch Provisioning (ZTP), Centralized Cloud Management, and Intelligent Monitoring
- Centralized Management: Cloud access and Omada app for ultra convenience and easy management
- 2.5G Port: A 2.5 Gbps Ethernet port boosts total internet throughput
- Seamless Roaming: Even video streams and voice calls are unaffected as users move between locations.△
- PoE+ Support: Supports Power over Ethernet (802.3at) for convenient deployment and installation
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi/Voucher, etc.) and abundant wireless security technologies

Summary: TP-Link Omada AX3600 Wireless Dual Band Multi-Gigabit Ceiling Mount Access Point. 2.4 GHz, 5 GHz, Maximum data transfer rate: 2402 Mbit/s. Security algorithms: WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3-Enterprise, WPA3-PSK. Ethernet LAN data rates: 25000 Mbit/s. Power over Ethernet (PoE). Product colour: White | Vendor Homepage: <https://www.tp-link.com/uk/business-networking/ceiling-mount-ap/eap660-hd/> | 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: No | Airtime Fairness (ATF): Yes | Automatic channel scanning: Yes | Automatic channel selection: Yes | Ethernet LAN data rates: 25000 | Frequency band: 2.4 - 5 | Maximum data transfer rate: 2402 | Maximum data transfer rate (2.4 GHz): 1148 | Maximum data transfer rate (5 GHz): 2402 | MIMO: Yes | MIMO type: Multi User MIMO | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11ax/IEEE 802.11b/IEEE 802.11g/IEEE 802.11n | Quality of Service (QoS) support: Yes | Rate limiting: Yes | VLAN support: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Wi-Fi roaming: Yes | Wireless isolation: Yes | MAC address filtering: Yes | Remote Authentication Dial-In User Service (RADIUS): Yes | Security algorithms: WPA2-Enterprise/WPA2-PSK/WPA3-Enterprise/WPA3-PSK/WPA-Enterprise/WPA-PSK | Service Set Identifier (SSID) features: Multiple SSIDs | Syslog: Yes | Web-based management: Yes | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 1 | Output current: 2 | Output voltage: 12 | Power over Ethernet (PoE): Yes | Placement: Ceiling | Product colour: White | Antenna type: Internal | Depth: 243 | Height: 64 | Width: 243 | Mounting kit: Yes | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Harmonized System (HS) code: 85176990 | Series: Omada | Model name: EAP660 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.007442 | Unit Calculated Weight: 1.57