

Switch MIKROTIK 8x10Base-T 100Base-TX 1000Base-T 2xSFP+ CSS610-8P-2S+IN

Gamintojas: **MIKROTIK** · Modelis: **CSS610-8P-2S+IN** · EAN: **4752224007216** · Prekės kodas: **552498**



210,90 €

Kaina su PVM

Be PVM: **174,30 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

CSS610-8P-2S+IN is one of the most well-rounded switches on the market. It is a perfect fit for the most diverse setups: from home networks and small offices to hotels, call centers and so on. The unique combination of size, features, and price offers unbelievable scalability potential.

There are two SFP+ ports for 10 Gigabit fiber connectivity and eight Gigabit Ethernet ports with 802.3af/at PoE-out.

This switch is all about nice and easy setups. The compact form-factor means easier shipping and handling, while the lightweight SwOS means easier configuration. You can even configure this switch from your web browser! It gives you all the core functionality of a managed switch, and even more: you can manage port-to-port forwarding, broadcast storm control, apply MAC filters, configure VLANs, mirror traffic, apply bandwidth limitations, and even adjust some MAC and IP header fields.

But the real blessing is the combination of SFP+ and PoE-out Ethernet ports. With this setup, you can do all kinds of things on a tight budget. CSS610 has an impressive total PoE-out budget of 140 W, so you can use even in the most intense scenarios – like hotels, conference halls, or call centers! Use the PoE-out ports to connect the IP-phones while the SFP+ ports connect your primary server to the ISP. Or power a bunch of network cameras and instantly upload the footage to the cloud. And manage a cluster of wireless access points at the same time. Also, scalability is no longer a problem. With our pricing, you can afford a switch on every floor!

Like every toolbox needs screwdrivers and pliers, every network can use a solid PoE switch.

Summary: Mikrotik CSS610-8P-2S+IN. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8, Installed SFP+ modules quantity: 2. Switching capacity: 56 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 48 - 57 V. Power over Ethernet (PoE). Rack mounting | Vendor Homepage: https://mikrotik.com/product/css610_8p_2s_in#fndtn-downloads | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Installed SFP+ modules quantity: 2 | Networking standards: IEEE 802.3af/IEEE 802.3at | 10G support: Yes | Broadcast storm control: Yes | VLAN support: Yes | Switching capacity: 56 | MAC address filtering: Yes | Rack mounting: Yes | Product colour: White | Reset button: Yes | LED indicators: Yes | International Protection (IP) code: IP20 | Operating system installed: SwitchOS Lite | Processor model: Marvell 88E6193X | Flash memory: 0.064 | Fanless: Yes | Mean time between failures (MTBF): 200000 | Power source: AC/DC | Power supply included: Yes | AC input voltage: 100 - 240 | AC input frequency: 50 - 60 | DC input voltage: 48 - 57 | Input current: 2.2 | Power consumption (max): 162 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Power over Ethernet (PoE) ports quantity: 8 | Total Power over Ethernet (PoE) budget: 140 | Storage temperature (T-T): -40 - 70 | Width: 272 | Depth: 216 | Height: 50 | Cables included: AC | Rack mount kit: Yes | Sustainability compliance: Yes | Compliance certificates: CE/RoHS | Certification: EAC | Unit Calculated Weight: 2.2 | Product Net Weight: 0.7 | Unit Calculated Volume: 0.00741 | Units per Shipping Box: 5 | Unit Width: 6.5 | Units per Pallet: 0 | Shipping Box Height: 28 | Unit Depth: 38 | Unit Height: 25 | Name: NET SWITCH 8PORT 1000M 2SFP+/CSS610-8P-2S+IN MIKROTIK | Model: CSS610-8P-2S+IN

Techninė specifikacija

Matmenys ir svoris	
Matmenys (l × p × A)	38,00cm × 7,00cm × 25,00cm