



**Case LIAN LI
ATX/micro
ATX/Mini-
ITX/EATX
Black/Transparent
Midi Tower PC
Lian Li Lancool
III RGB Black
(G99.LAN3RX.00)
G99.LAN3RX.00**

Modelis: G99.LAN3RX.00

Gamintojas: LIAN LI

EAN: 4718466011794

Prekės kodas: 552608

163.99€

Kopnyc Lian Li Lancool III RGB Black (G99.LAN3RX.00)

LANCOOL III, the premium mid-tower chassis, offers better thermal performance than LANCOOL II by

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

including 4 pre-installed 140mm PWM fans, and featuring fine mesh panels designed to ensure ample airflow is delivered to the high-end components while the system runs at peak performance.

Comes equipped with 3x 140mm ARGB PWM fans that have similar performance as the LANCOOL III RGB 140mm back PWM Fan.

EXTREME AIRFLOW CRAFTMANSHIP

A fine mesh design has been implemented at the front, top, and both bottom side panels of the LANCOOL III.

HINGED PANELS ALL AROUND

The hinged tempered glass side panels offer an unobstructed view of the interior configuration, while the bottom shroud panels provide quick access to the PSU and storage drives.

The two removable 4mm tempered glass panels located on each side of the case can be opened by pulling the front aluminum handle.

The mesh panels located on both sides of the PSU shroud area can be removed for cleaning when the front panel is unattached.

FLEXIBLE CONFIGURATION

With ample interior room, the LANCOOL III can offer different cooling and usage scenarios

AIR Cooling

With high airflow stock fans, and air tower clearance up to 185mm, the LANCOOL III is ideal for an air-cooling build.

AIO Cooling

With ample front intake, the LANCOOL III can provide strong performance for an AIO cooling build. The top fan bracket can support up to 3 x 120mm/140mm fans and offers enough thickness clearance for an AIO with a 420 radiator/fan combo.

Custom Water Cooling

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

With the ability to support 3 × 360mm radiators simultaneously, the LANCOOL III can offer custom water-cooling enthusiasts, lots of imagination.

SPACIOUS COOLING SUPPORT

The LANCOOL III is optimized for water-cooling and high-end thermal solutions. A maximum of 10 × 120mm fans or a large 420mm radiator can be mounted in the main chamber.

Multi-way Front Fan/Radiator Bracket

The multi-way front fan bracket offers 4 different ways to mount a radiator or fans to cater to different cooling needs, and features a new latch/handle mechanism to easily secure it in place without the need of the locking thumbscrews.

Removable Top Fan Bracket

The removable top fan bracket with offset fan mounting points allows for a thicker fan and radiator combo to be installed at the top of the LANCOOL III by providing enough clearance from the ram.

Modular PSU Shroud Bracket - Fan/ Pump/ SSD

The adjustable modular PSU shroud bracket can accommodate 1 x 360mm radiator, 3 x 120mm fans, 3 x 2.5" SSDs, or a pump/reservoir combos.

Side Multi-Purpose Mounting Slots

Mounting slots beside the motherboard are provided at 105mm apart (standard 120mm fan mounting points) to allow the installation of a distro plate or a reservoir/pump bracket.

EXTENSIVE STORAGE CAPACITY

Multiple storage drive mounting locations are supported for up to 12 x 2.5" SSDs or 4 x 3.5" HDDs and 8 x 2.5" SSDs.

COMPREHENSIVE CABLE MANAGEMENT

As the second chamber located on the right side is visible, great consideration has been given to cable management. The LANCOOL III features an upgraded solution to ensure neat cable routing with toolless magnetic cable cover doors, and a well-organized layout for hubs and cables.

Sliding Cable Routing Cover

By slightly loosening the two back thumb screws, the cable cover can be adjusted to fit different sizes of motherboards.

REVERSIBLE FRONT I/O

Optimized for PC locate on a desk, the front I/O can be relocated to the bottom of the chassis.

FRIENDLY PSU INSTALLATION

The removable PSU mounting bracket allows for PSU installation outside of the chassis, to then slide it in through from the rear.

ANTI-SAG BRACKET FOR PERFECTLY HORIZONTAL GPU

A GPU anti-sag bracket is included for a seamless display of the hardware through the side tempered glass panels.

- Mid-tower modular chassis for all kinds of configurations
- Equipped with 4 × 140 PWM fans (ARGB or non-RGB)
- Featured airflow optimized mesh structure and hinged side panels
- Supports up to 420 radiator or 3 x 360 radiators and a maximum of 10 fans
- Offers 12 storage drives mounting locations
- Upgraded cable management solution for a clean build

Summary: Lian Li Lancool III . Form factor: Midi Tower, Type: PC, Product colour: Black, Transparent. Front fans installed: 3x 140 mm, Front fans diameters supported: 120,140 mm, Rear fans installed: 1x 140 mm. Supported HDD sizes: 2.5,3.5", SSD form factor: 2.5". Width: 238 mm, Depth: 526 mm, Height: 523 mm | Vendor Homepage: <https://lian-li.com/product/lancool-iii/> | Anti-dust filter: Yes | Cable management: Yes | Form factor: Midi Tower | Illumination: Yes | Illumination colour: Multi | Illumination location: Case fans | Material: Aluminium/SGCC/Tempered glass | Maximum CPU cooler height: 187 | Maximum graphics card length: 435 | Maximum PSU length: 220 | Number of 2.5" bays: 8 | Number of 3.5" bays: 4 | Number of expansion slots: 8 | On/off button: Yes | Product colour: Black/Transparent | Reset button: Yes | Side window: Yes | Supported motherboard form factors: ATX/EATX/micro ATX/Mini-ITX | Type: PC | Power supply included: No | Audio input: Yes | Audio output: Yes | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity: 1 | Fan speed: 200 - 1800 | Front fans diameters supported: 120/140 | Front fans

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

installed: 3x 140 mm | Front radiator sizes supported: 360/420 | Maximum air pressure: 2.3 |
Maximum airflow: 83.5 | Number of front fans supported (max): 3 | Number of rear fans supported
(max): 1 | Number of top fans supported (max): 3 | Rear fans diameters supported: 120/140 | Rear
fans installed: 1x 140 mm | Top fans diameters supported: 120/140 | Top radiator sizes supported:
360/420 | HDD/SSD combo cage: Yes | SSD form factor: 2.5" | Supported HDD sizes: 2.5/3.5 | Depth:
526 | Height: 523 | Width: 238 | Model name: Lian Li Lancool III RGB Black (G99.LAN3RX.00) | Case
product features: Transparent panel | Model: LANCOOL 3R-X BLACK | Units per Shipping Box: 1 | Unit
Calculated Volume: 0.1206 | Unit Calculated Weight: 16.9