



**Switch
MIKROTIK
CSS326-24G-
2S+RM Switch
type Managed
Rack mounting
Yes Form factor
1U 24xRJ-45
ports RJ-45
Ports Type
Gigabit Ethernet
(10/100/1000)
2xSFP+ module
slots quantity
10G support Yes
Power over
Ethernet (PoE)
Yes CSS326-
24G-2S+RM**

Modelis: CSS326-24G-2S+RM

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Gamintojas: MIKROTIK

EAN: 4752224002334

Prekės kodas: 552680

148.00€

SwOS powered 24 port Gigabit Ethernet switch with two SFP+ ports, wire speed connectivity with several new switching features.

The device is powered by a Marvell DX switch chip. The device is running an operating system designed specifically for MikroTik switch products - SwOS. SwOS is configurable from your web browser. It gives you all the basic functionality for a managed switch, plus more: allows to manage port-to-port forwarding, apply MAC filter, configure VLANs, mirror traffic, apply bandwidth limitation and even adjust some MAC and IP header fields. SFP cage supports both 1.25 Gb SFP and 10 Gb SFP+ modules.

Summary: Mikrotik CSS326-24G-2S+RM. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Networking standards: IEEE 802.1Q. Power connector: DC-in jack. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: <https://mikrotik.com/product/CSS326-24G-2SplusRM> | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power connector: DC-in jack | SFP+ module slots quantity: 2 | 10G support: Yes | Broadcast storm control: Yes | Networking standards: IEEE 802.1Q | Number of VLANs: 4000 | Port mirroring: Yes | Spanning tree protocol: Yes | VLAN support: Yes | Access Control List (ACL): Yes | MAC address filtering: Yes | Security algorithms: SNMP | Form factor: 1U | Product colour: White | Rack mounting: Yes | Reset button: Yes | Built-in processor: Yes | Flash memory: 2 | Internal memory: 2 | Number of power supply units: 1 | Power consumption (typical): 19 | Power source: DC/PoE | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Power over Ethernet (PoE) voltage range: 10 - 30 | Operating temperature (T-T): -40 - 70 | Depth: 144 | Height: 44 | Width: 440 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Manual: Yes | AC adapter included: Yes | Mounting brackets included: Yes | Harmonized System (HS)
code: 85176990 | Model name: CSS326-24G-2S+RM | Units per Shipping Box: 10 | Unit Calculated
Volume: 0.00957 | Unit Calculated Weight: 1.86