

Dahua Technology DH-CS4010-8GT-110 network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: **DAHUA** · Modelis: **DH-CS4010-8GT-110** · EAN: **6923172571151** · Prekės kodas: **552718**



89,90 €

Kaina su PVM

Be PVM: **74,30 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Meets the requirements of IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab standards
- ✓ Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards
- ✓ Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE
- ✓ A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof



Aprašymas

- Meets the requirements of IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab standards
- Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards
- Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE
- A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof

Summary: Dahua Technology DH-CS4010-8GT-110. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 10. MAC address table: 8000 entries, Switching capacity: 20 Gbit/s.

Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x. DC input voltage: 54 V. Power over Ethernet (PoE) | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Transmission/Cloud-Managed-Switches/CS4010-8GT-110>

110 | Switch type: Managed | Switch layer: L2 | Quality of Service (QoS) support: Yes | Cloud-managed: Yes | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 10 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 10 | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3bt/IEEE 802.3u/IEEE 802.3x | 10G support: No | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | Spanning tree protocol: Yes | VLAN support: Yes | Virtual LAN features: Port-based VLAN | Number of VLANs: 32 | Switching capacity: 20 | Forwarding rate: 4.17 | MAC address table: 8000 | Jumbo frames support: Yes | Jumbo frames: 15000 | Packet buffer memory: 0.5 | DHCP features: DHCP client | Rack mounting: No | Product colour: Black | Housing material: Metal | Reset button: Yes | LED indicators: Yes | Power source: DC/PoE | Power supply included: Yes | Redundant power supply (RPS) support: Yes | DC input voltage: 54 | Input current: 2.22 | Power consumption (max): 110 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 8 | Operating temperature (T-T): -10 - 55 | Storage temperature (T-T): -40 - 70 | Operating relative humidity (H-H): 5 - 95 | Storage relative humidity (H-H): 5 - 95 | Width: 190 | Depth: 106 | Height: 30 | Weight: 550 | Package width: 256 | Package depth: 244 | Package height: 87 | Package weight: 1300 | Sustainability compliance: Yes | Compliance certificates: CE | Unit Calculated Weight: 1.28 | Product Net Weight: 0.55 | Unit Calculated Volume: 0.005623 | Units per Shipping Box: 1 | Unit Width: 24.5 | Shipping Box Height: 9 | Unit Depth: 25.5 | Unit Height: 9 | Name: NET SWITCH 10P 1000M 8POE/CS4010-8GT-110 DAHUA | Model name: CS4010-8GT-110

Techninė specifikacija

Specifications	
Sandėlio grupė	Switches [+133][-162]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	10
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	10
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Flow control support	Yes
Spanning tree protocol	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
VLAN support	Yes
Virtual LAN features	Port-based VLAN

Number of VLANs	32
Data transmission	
MAC address table	8000 entries
Switching capacity	20 Gbit/s
Forwarding rate	4.17 Mpps
Jumbo frames support	Yes
Jumbo frames	15000
Packet buffer memory	0.5 MB
Security	
DHCP features	DHCP client
Design	
Rack mounting	No
Product colour	Black
Housing material	Metal
Reset button	Yes
LED indicators	Yes
Power	
Power source	DC/PoE
Power supply included	Yes
Redundant power supply (RPS) support	Yes
DC input voltage	54 V
Input current	2.22 A
Power consumption (max)	110 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	8
Operational conditions	
Operating temperature (T-T)	-10 - 55 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	190 mm
Depth	106 mm

Height	30 mm
--------	-------

Weight	550 g
--------	-------

Packaging data

Package width	256 mm
---------------	--------

Package depth	244 mm
---------------	--------

Package height	87 mm
----------------	-------

Package weight	1.3 kg
----------------	--------

Certificates

Compliance certificates	CE
-------------------------	----

Sustainability

Sustainability compliance	Yes
---------------------------	-----

Matmenys ir svoris

Matmenys (I × P × A)	26,00cm × 25,00cm × 9,00cm
----------------------	----------------------------