



**Access Point TP-
LINK Omada
2976 Mbps IEEE
802.11a/b/g IEEE
802.11n IEEE
802.11ac IEEE
802.11ax 1xRJ45
EAP650**

Modelis: EAP650

Gamintojas: TP-LINK

EAN: 4897098683545

Prekės kodas: 552842

113.99€

**The New Slimline Business WiFi 6
AX3000 Ceiling Mount WiFi 6 Access Point**

AX3000 WiFi 6 Speed

2402 Mbps on 5 GHz +

574 Mbps on 2.4 GHz†

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

High-Efficiency WiFi 6

More connected devices can enjoy faster speeds

Centralized Cloud Management

Manage the whole network locally or from the cloud

160 MHz Channel

Double the data at peak transmission times on a single stream with HE160+

Auto Channel Selection and Power Adjustment*

Optimize overall performance by reducing WiFi interference

Omada Mesh Technology

More flexible and convenient wireless deployment

Seamless Roaming

Uninterrupted streaming when moving between APs

Ultra-Slim Design

Φ160 mm × 33.6 mm elegant design brings more agility

PoE+ Powered

Supports both DC (adapter included) and 802.3at PoE+ for flexible installations

Seamless Integration into Omada SDN

The Omada Software Defined Networking (SDN) platform integrates network devices, including access points, switches, and routers. It provides 100% centralized cloud management and creates a highly scalable network controlled from a single interface.

Auto Channel Selection and Power Adjustment

to Optimize Overall Performance

Provides powerful wireless performance while significantly reducing WiFi interference by automatically adjusting the channel settings and transmission power levels of neighboring APs in the

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

same network.

Easy Deployment & Higher Performance by Omada Mesh

Easy Pairing, Less Wiring

With Mesh technology, Omada EAPs save you from extra wires by wirelessly extending your WiFi signal further and more flexibly to hard-to-wire areas.

Optimized Network Performance

Intelligent self-organization optimizes the best path between EAPs while self-healing ensures you stay online even when one AP is disrupted.

Always Stay Smooth with Fast Roaming

Ensures customers to enjoy uninterrupted streaming when moving around by switching clients automatically to the access points with the optimal signal.

Ultra-Slim Design Brings More Agility

Exceptional performance with compact design ensures simple WiFi installation while saving space. The elegant appearance makes EAP650 perfectly blend into any modern office, hotel, classroom, or café.

- Ultra-Fast WiFi 6 Speeds: Simultaneous 574 Mbps on 2.4 GHz and 2402 Mbps on 5 GHz totals 2976 Mbps WiFi speeds.
- High-Efficiency WiFi 6: More connected devices can enjoy faster speeds.
- Centralized Cloud Management: Omada SDN integration manages the whole network locally or from the cloud via web UI or Omada app.
- 160 MHz Channel: Double the data at peak transmission times on a single stream with HE160.
- Seamless Roaming: Video streams and voice calls are unaffected as users move between locations.
- Omada Mesh: Enables wireless connectivity between access points for extended range and flexible deployment.
- PoE+ Powered: Supports both 802.3at PoE+ and DC (adapter included) power supply for flexible installations.
- Ultra-Slim Design: $\Phi 160$ mm $\times$ 33.6 mm elegant design brings more agility.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Summary: TP-Link Omada AX3000 Ceiling Mount WiFi 6 Access Point. 2.4 GHz, 5 GHz, Maximum data transfer rate: 2976 Mbit/s. Security algorithms: SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3-Enterprise,.... Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White | Vendor Homepage: <https://www.tp-link.com/us/business-networking/omada-sdn-access-point/eap650/> | 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: No | Maximum data transfer rate: 2976 | Maximum data transfer rate (2.4 GHz): 574 | Maximum data transfer rate (5 GHz): 2402 | Ethernet LAN data rates: 10/100/1000 | Frequency band: 2.4 - 5 | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11ax/IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.1x/IEEE 802.3at | Cabling technology: 10/100/1000Base-T(X) | Number of users: 250 | Automatic channel scanning: Yes | Automatic channel selection: Yes | MIMO: Yes | MIMO type: Multi User MIMO | Spread spectrum method: OFDMA | Fit AP mode features: Mesh networking | VLAN support: Yes | Rate limiting: Yes | Flow control support: Yes | Band steering: Yes | Airtime Fairness (ATF): Yes | Quality of Service (QoS) support: Yes | BeamForming: Yes | Transmitting power (CE): 20 dBm(2.4 GHz, EIRP) 23 dBm(5 GHz, Band1 & Band2, EIRP) 30 dBm(5 GHz, Band3, EIRP) | Transmitting power (FCC): 25 dBm (2.4 GHz) 25 dBm (5 GHz) | Security algorithms: SNMP/SNMPv2/SNMPv3/SSH/WPA2-Enterprise/WPA2-PSK/WPA3-Enterprise/WPA3-PSK/WPA-Enterprise/WPA-PSK | MAC address filtering: Yes | Access Control List (ACL): Yes | Web-based management: Yes | Syslog: Yes | Firmware upgradeable: Yes | Ethernet LAN (RJ-45) ports: 1 | DC-in jack: Yes | Power over Ethernet (PoE): Yes | DC voltage range: 12 | Placement: Ceiling,Wall | Product colour: White | Reset button: Yes | LED indicators: Yes | Antenna type: Internal | Certification: CE, FCC, RoHS | Width: 160 | Depth: 160 | Height: 33.6 | Package type: Box | Quantity per pack: 1 | Mounting kit: Yes | Quick start guide: Yes | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage temperature (T-T): -40 - 70 | Storage relative humidity (H-H): 5 - 90 | Unit Calculated Weight: 0.856 | Product Net Weight: 0.5 | Unit Calculated Volume: 0.004198 | Units per Shipping Box: 16 | Units per Pallet: 0 | Shipping Box Height: 28 | Name: WRL ACCESS POINT 3000MBPS/OMADA EAP650 TP-LINK | Series: Omada | Model name: EAP650