



WRL ACCESS POINT 2.4GHZ/RB912R- 2ND- LTM&EC200A MIKROTIK



Modelis: RB912R-2ND-LTM&EC200A-EU

Gamintojas: MIKROTIK

EAN: 4752224009296

Prekės kodas: 552999

91.98€

Tiny, affordable weatherproof access point with a built-in LTE modem and GPS. Add extensive networking and tracking options to your vehicle without breaking the bank! This is a 2024 refresh with added B28 band support.

LtAP Mini LTE kit is a compact and rugged wireless access point designed to keep your vehicle connected wherever you go. Whether you're riding through the Great Outdoors or navigating busy urban streets, this tiny device ensures you're always online and ready to upload location data.

LtAP mini has a special extra-durable enclosure with a wall mounting kit, two SIM slots to alternate between cellular providers, and integrated GPS support, making this a perfect device for tracking

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

moving vehicles like cars, buses or trains.

There's an Ethernet port for your wired devices and a classic 2.4 GHz wireless radio. The RS232 serial port gives you console access for debugging.

The power options are as flexible as they get. You have the classic DC jack, 802.3af/at PoE-in, and a microUSB option. We have even seen users powering the LtAP mini with a portable power bank throughout the day!

The new LTE card offers a better price and the support of the most popular LTE bands, including the B28 band! It is connected to two internal antennas with u.FL connectors, so you can unplug the connectors and add your own external LTE antenna for even better coverage.

We have provided a simple tracking application example in the RouterOS documentation - to help you start tracking your vehicle's location in real-time. You will need to connect an external GPS antenna, we recommend using the ACGPSA antenna with IP67 water resistance rating.

Summary: Mikrotik LtAP mini LTE kit (2024). 2.4 GHz, Maximum data transfer rate: 300 Mbit/s. Power over Ethernet (PoE), Power consumption (max): 8 W | Vendor Homepage:

https://mikrotik.com/product/ltap_mini_lte_kit_2024 | 2.4 GHz: Yes | 5 GHz: No | 6 GHz: No |

Maximum data transfer rate: 300 | Maximum data transfer rate (2.4 GHz): 300 | DC-in jack: Yes | RS-232 interface: Yes | USB 2.0 ports quantity: 1 | USB connector type: Micro-USB | DC voltage range: 8 - 30 | Power consumption (max): 8 | Power over Ethernet (PoE): Yes | International Protection (IP) code: IP54 | Built-in processor: Yes | Flash memory: 16 | Internal memory: 64 | Processor frequency: 650 | Certification: CE, E-MARK, EAC, ROHS | Model: RB912R-2ND-LTM&EC200A-EU | Model name: LtAP mini LTE kit (2024) | Units per Pallet: 0 | Units per Shipping Box: 20 | Unit Calculated Volume: 0.001569 | Unit Calculated Weight: 0.455