

Dahua Technology DH-CS4006-4GT-60 network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: **DAHUA** · Modelis: **DH-CS4006-4GT-60** · EAN: **6923172571144** · Prekės kodas: **553084**



47,90 €

Kaina su PVM

Be PVM: **39,59 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Meets the requirements of IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab standards
- ✓ Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE power supply standards
- ✓ Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE
- ✓ A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof



Aprašymas

Highly intuitive, the Smart Managed Switch can manage local networks. With the DoLink Care platform, it can also perform cloud management. The switch performs operation and maintenance using topology visualization on front-end, transmission and back-end storage devices that are in the security system and IT system. With its full metal design, the switch has great heat dissipation and can operate in temperatures ranging -10°C to 55°C. It offers EMC and has protection against overvoltage, overcurrent, static electricity, lightning strikes, pulses and other types of interference. For the PoE series Smart Managed Switch, power is supplied up to 250 meters away. The orange port supplies up to 60 W and the red port provides up to 90 W. Also, link aggregation and STP are available on select models to ensure the network remains stable. The switch can be used in small and medium-sized businesses such as supermarkets, offices, restaurants, cafés and hotels.

Techninė specifikacija

Specifications	
Sandėlio grupė	Switches [+133][-162]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	6
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	6
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Full duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Spanning tree protocol	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
VLAN support	Yes
Virtual LAN features	Port-based VLAN
Number of VLANs	32
Data transmission	
MAC address table	8000 entries
Switching capacity	12 Gbit/s
Forwarding rate	8.93 Mpps
Jumbo frames support	Yes
Jumbo frames	15000
Security	
DHCP features	DHCP client

Design

Product colour	Black
Housing material	Metal
Reset button	Yes
LED indicators	Yes
Wall mountable	Yes

Power

Power source	DC
DC input voltage	53 V
Input current	1.226 A
Power consumption (max)	65 W

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	4

Operational conditions

Operating temperature (T-T)	-10 - 55 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%

Weight & dimensions

Width	130 mm
Depth	90 mm
Height	26 mm
Weight	290 g

Packaging data

Package width	265 mm
Package depth	238 mm
Package height	76 mm
Package weight	940 g

Matmenys ir svoris

Matmenys (I × P × A)	12,00cm × 20,00cm × 9,00cm
----------------------	----------------------------