

UPS TECNOWARE 840 Watts 1200 VA Wave form type Modified sinewave LineInteractive Phase 1 phase FGCERAPL1202SCH

Gamintojas: **TECNOWARE** · Modelis: **FGCERAPL1202SCH** · EAN: **8026475175786** · Prekės kodas: **553222**



85,90 €

Kaina su PVM

Be PVM: **70,99 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

- Complete protection against blackout and power surges (overvoltages and undervoltages)
- Recommended for Personal Computers, DVR / NVR and video surveillance systems, ADSL / fiber modem, switch / router, cash registers
- Not suitable with power supplies with Active PFC circuit (Server, PC game, video game console, workstation, Mac computer), lamps and electric motors
- AVR Automatic Voltage Regulator electronic circuit
- n 2 Italy / Schuko output sockets and n 1 schuko input cable
- outputs socket protected against blackout
- outputs socket protected against overvoltages
- multifunction LED and on-off button
- USB port for UPS control / monitoring and ignition programming / shutdown via Tecnomanager software
- UPS management software TecnoManager compatible with Windows, Mac OS X, Linux etc

Summary: Tecnoware FGCERAPL1202SCH. UPS topology: Standby (Offline), Output power capacity: 1.2 kVA, Output power: 840 W. AC outlet types: Type F, AC outlets quantity: 2 AC outlet(s), USB port type: Micro-USB B. Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 10 min, Typical backup time at half load: 40 min. Form factor: Compact, Product colour: Black, International Protection (IP) code: IP20. Width: 101 mm, Depth: 279 mm, Height: 142 mm | Vendor Homepage: <https://www.tecnoware.com/en-US/Dettaglio/Articolo/55> | UPS topology: Standby (Offline) | Output power capacity: 1.2 | Output power: 840 | Input operation voltage (min): 230 | Input operation voltage (max): 230 | Input frequency: 50/60 | Output operation voltage (min): 230 | Output frequency: 50/60 | Number of input phases: 1 | Number of output phases: 1 | Power

factor: 0.7 | Noise level: 40 | AC outlet types: Type F | AC outlets quantity: 2 | USB port: Yes | USB port type: Micro-USB B | Battery technology: Sealed Lead Acid (VRLA) | Typical backup time at full load: 10 | Typical backup time at half load: 40 | Form factor: Compact | Product colour: Black | International Protection (IP) code: IP20 | Operating temperature (T-T): 20 - 25 | Width: 101 | Depth: 279 | Height: 142 | Weight: 4500 | Package width: 180 | Package depth: 340 | Package height: 220 | Unit Calculated Weight: 4.69 | Product Net Weight: 4.5 | Unit Calculated Volume: 0.01229 | Units per Shipping Box: 4 | Unit Width: 18.5 | Units per Pallet: 0 | Shipping Box Height: 24.5 | Unit Depth: 34 | Unit Height: 22 | Name: UPS/AVR ERA PLUS 1200VA/FGCERAPL1202SCH TECNOWARE

Techninė specifikacija

Specifications	
Sandėlio grupė	UPS For Workstations [+12] [-82]
Matmenys ir svoris	
Matmenys (I x P x A)	34,00cm x 19,00cm x 22,00cm