

# Dahua Technology S3016-16GT network switch Unmanaged L2 Gigabit Ethernet (10/100/1000) Desktop/Wall-Mounting Black

Gamintojas: **DAHUA** · Modelis: **S3016-16GT** · EAN: **6939554932632** · Prekės kodas: **553254**



## 51,90 €

Kaina su PVM

Be PVM: **42,89 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ > 16 × RJ-45 10/100/1000 ports.
- ✓ > The all-gigabit ports transmit data without lag.
- ✓ > Features aggregation mode which aggregates uplink ports.
- ✓ > Features isolation mode which isolates all the ports from each other.
- ✓ > With its solid full metal design, the device has great heat dissipation and no fan.
- ✓ > Supports rack mount, wall mount and desktop mount.



## Aprašymas

- > 16 × RJ-45 10/100/1000 ports.
- > The all-gigabit ports transmit data without lag.
- > Features aggregation mode which aggregates uplink ports.
- > Features isolation mode which isolates all the ports from each other.
- > With its solid full metal design, the device has great heat dissipation and no fan.
- > Supports rack mount, wall mount and desktop mount.

Summary: Dahua Technology S3016-16GT. Switch type: Unmanaged, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. MAC address table: 16000 entries, Switching capacity: 32 Gbit/s. Networking

standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. Rack mounting, Form factor: Desktop/Wall-Mounting | Vendor Homepage: <https://transmission.dahuasecurity.com/fr/product-list/Business/Switches/AccessSwitch/S3016-16GT> | Switch type: Unmanaged | Switch layer: L2 | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3u | 10G support: No | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Switching capacity: 32 | Forwarding rate: 23.8 | MAC address table: 16000 | Jumbo frames support: Yes | Jumbo frames: 12000 | Packet buffer memory: 8.4 | Rack mounting: Yes | Form factor: Desktop/Wall-Mounting | Product colour: Black | Housing material: Metal | LED indicators: Yes | Power source: DC | Power supply included: Yes | AC input voltage: 100 - 240 | AC input frequency: 50/60 | Input current: 0.4 | Power consumption (typical): 7.8 | Power over Ethernet (PoE): No | Operating temperature (T-T): 0 - 40 | Operating relative humidity (H-H): 10 - 90 | Width: 294 | Depth: 119 | Height: 44 | Weight: 740 | Package width: 353 | Package depth: 215 | Package height: 75 | Package weight: 1297 | Unit Calculated Weight: 1.4 | Product Net Weight: 0.74 | Unit Calculated Volume: 0.005724 | Units per Shipping Box: 1 | Unit Width: 21.5 | Shipping Box Height: 7.5 | Unit Depth: 35.5 | Unit Height: 7.5 | Name: NET SWITCH 16PORT 10/100/1G/S3016-16GT DAHUA | Model name: S3016-16GT

Techninė specifikacija

| Specifications                                |                                       |
|-----------------------------------------------|---------------------------------------|
| Sandėlio grupė                                | Switches [+133][-162]                 |
| Management features                           |                                       |
| Switch type                                   | Unmanaged                             |
| Switch layer                                  | L2                                    |
| Ports & interfaces                            |                                       |
| Basic switching RJ-45 Ethernet ports quantity | 16                                    |
| Basic switching RJ-45 Ethernet ports type     | Gigabit Ethernet (10/100/1000)        |
| Installed SFP modules quantity                | 0                                     |
| Installed SFP+ modules quantity               | 0                                     |
| Network                                       |                                       |
| Networking standards                          | IEEE 802.3, IEEE 802.3ab, IEEE 802.3u |
| 10G support                                   | No                                    |
| Copper ethernet cabling technology            | 10BASE-T, 100BASE-TX, 1000BASE-T      |
| Data transmission                             |                                       |
| MAC address table                             | 16000 entries                         |
| Switching capacity                            | 32 Gbit/s                             |
| Forwarding rate                               | 23.8 Mpps                             |
| Jumbo frames support                          | Yes                                   |
| Jumbo frames                                  | 12000                                 |
| Packet buffer memory                          | 8.4 MB                                |
| Design                                        |                                       |
| Rack mounting                                 | Yes                                   |
| Form factor                                   | Desktop/Wall-Mounting                 |

|                                   |                            |
|-----------------------------------|----------------------------|
| Product colour                    | Black                      |
| Housing material                  | Metal                      |
| LED indicators                    | Yes                        |
| <b>Power</b>                      |                            |
| Power source                      | DC                         |
| Power supply included             | Yes                        |
| AC input voltage                  | 100 - 240 V                |
| AC input frequency                | 50/60 Hz                   |
| Input current                     | 0.4 A                      |
| Power consumption (typical)       | 7.8 W                      |
| <b>Power over Ethernet (PoE)</b>  |                            |
| Power over Ethernet (PoE)         | No                         |
| <b>Operational conditions</b>     |                            |
| Operating temperature (T-T)       | 0 - 40 °C                  |
| Operating relative humidity (H-H) | 10 - 90%                   |
| <b>Weight &amp; dimensions</b>    |                            |
| Width                             | 294 mm                     |
| Depth                             | 119 mm                     |
| Height                            | 44 mm                      |
| Weight                            | 740 g                      |
| <b>Packaging data</b>             |                            |
| Package width                     | 353 mm                     |
| Package depth                     | 215 mm                     |
| Package height                    | 75 mm                      |
| Package weight                    | 1.3 kg                     |
| <b>Matmenys ir svoris</b>         |                            |
| Matmenys (I × P × A)              | 36,00cm × 22,00cm × 8,00cm |