Axagon HMC-6M2 knyginių kompiuterių dokas / jungčių replikatorius Vielinis USB 3.2 Gen 1 (3.1 Gen 1) Type-C Aliuminis

Gamintojas: **AXAGON** · Modelis: **HMC-6M2** · EAN: **8595247905796** · Prekės kodas: **553444**



45,90 €

Kaina su PVM

Be PVM: **37,93 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vielinis
- ✓ Priimančioji sąsaja: USB 3.2 Gen 1 (3.1 Gen 1) Type-C
- ✓ „USB Power Delivery“
- ✓ Ethernet LAN jungtis 10,100,1000 Mbit/ai Wake-on-LAN pasirengimas
- ✓ Pilnai abipusis (duplex) Jumbo Frames palaikymas
- ✓ „Plug and Play“ funkcija











Aprašymas

Multiport USB-C 3.2 Gen 1 hub AXAGON HMC-6M2 COMBO 6in1 expands your laptop, computer or phone with four ports and external box for M.2 disk.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

You can easily and quickly connect up to two USB devices, Gigabit Ethernet network, HDMI display and SATA M.2 SSD disk to your computer at the same time via the double-sided USB-C connector. You also get the possibility to supply laptop using Power Delivery technology at the same time. The USB-C hub will provide you with a simple and compact 6in1 docking station for notebook like MacBook Pro.

The USB hub offers two USB outputs with standard USB-A connectors. The hub can also handle permanent connection of two external drives simultaneously. Transfer rate up to 5Gb/s thanks to the fast USB 3.2 Gen 1 interface.

USB-C connector is dedicated to power up a laptop or mobile phone using Power Delivery 3.0 technology by power up to 100W. Connect the USB-C Power Delivery charger to the hub and connect the hub to the laptop. This saves one USB-C port. The condition is a laptop with Power Delivery charging support from the USB-C port and a suitable PD charger.

HDMI output provides high quality image up to 4K/30Hz Ultra HD resolution and supports multi-channel audio transmission. DisplayPort Alternate Mode (DP Alt Mode) enabled USB-C port or Thunderbolt 3 port is necessary for the proper function of video output.

Gigabit network card extends your computer by a fast network connection, adds the missing RJ-45 network connector or another network card. LAN adapter is compatible with 10/100/1000 Mbit/s speeds and also offers a wide range of functions for example IPv4/IPv6, crossover detection and auto-correction, Wake-on-LAN, VLAN support or advanced Power Management features.

You can connect a SATA M.2 SSD drive thanks to the built-in slot on the back. The multiport hub thus becomes an external drive. M.2 cards can be single-sided or double-sided up to a size of 22x80 mm. The external M.2 box has no capacity limitations for SSDs and supports modern functions such as TRIM.

Elegant aluminum body ensures mechanical resistance and quality cooling. The finely structured surface with no fingerprint remains will also please you. Port replicator is an ideal accessory for laptops without USB-A connectors, network card and video output. Fixed 18 cm long USB-C cable.

You can use your current USB peripherals without having to purchase new ones. Thanks to the Plug and Play and Hot Plug functions, the connection of the hub is very simple without complicated installation. It is also possible to easily connect and disconnect peripherals while the computer is running. The hub does not afraid of connection to phones with a USB-C connector - for example, you can connect a flash drive, keyboard, mouse, display, TV or projector to the phone.

Input:
• 1x USB 3.2 Gen 1 / SuperSpeed USB port, USB-C male connector.
• Backward compatible with USB 3.1 Gen 1 / USB 3.0 and USB 2.0.
• Compatible with Thunderbolt 3.
• Connecting USB type C male connector on a fixed 18 cm long cable.

USB outputs:
• 2x SuperSpeed USB port, USB-A female connector.
• 1x USB type C Power Delivery port (only for charging), USB-C female connector.
• Supports transmission rates 5.000 / 480 / 12 / 1.5 Mb/s (SuperSpeed / High / Full / Low speed).
• The total bandwidth / transmission rate is determined by the USB 3.2 Gen 1 interface used (theor. 5 Gbit/s).
• USB-C hub handle the permanent connection of two external drives.

HDMI output:
• HDMI.
• HDMI A (F) female connector.
• Maximum supported resolution 4K / 4096 x 2160 at 30 Hz.
• DisplayPort Alternate Mode (DP Alt Mode) enabled USB-C port or Thunderbolt 3 port is necessary for the proper function of video output. Correct OS is also necessary. The video output function will not be available without these requirements.
• HPD (Hot-Plug-Detect) support.
• TMDS (Transition Minimized Differential Signalling) support.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

• HDCP 1.4 and 2.3 (High-bandwidth Digital Content Protection) support.
• Up to 8-channel LPCM audio, compressed audio (AC-3, DTC) and HBR audio format support.
• Sample rate up to 192 kHz and 24 bit audio support – depends on source and target device i.e. notebook/phone and TV/display/AV receiver.

RJ-45 output:
• Gigabit Ethernet interface with RJ-45 connector for UTP or STP cable connection.
• Supported transmission rates for the Ethernet interface 10/100/1000 Mb/s.
• Supported IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T specifications.
• 10/100/1000 Mbit/s auto-detection.
• Supports IPv4/IPv6 packet Checksum Offload Engine (COE) to reduce processor load, including IPv4 IP/TCP/UDP/ICMP/ IGMP & IPv6 TCP/UDP/ICMPv6 checksum control and generation.
• Supports TCP Large Send Offload V1 and V2.
• Supports IEEE 802.1P Layer 2 priority encoding & decoding.
• Supports IEEE 802.1Q VLAN tagging.
• Supports IEEE 802.3az EEE (Energy Efficient Ethernet) - reduce power consumption at rest.
• Supports Jumbo frame.
• Supports full-duplex transmissions with IEEE 802.3x flow control and half-duplex transmissions with back-pressure flow control.
• Supports Auto MDI/MDIX - crossover detection and auto-correction eliminats the need for crossover cables.
• Supports hardware Cyclic Redundancy Check (CRC) to detect transmission errors.
• Supports Pair Swap/Polarity/Skew Correction.

Supports Wake-on-LAN feature in different modes:
• Supports sleep mode and remote Wake Up via Magic Packet, Microsoft Wakeup Frame, Microsoft Wake Packet Detection, ECMA-393 proxZzzy® for sleeping hosts, RealWoW! and also Link Change Wake-up.

Advanced Power Management features:
• The adapter supports advanced power management and supports advanced power saving e.g. when the Ethernet cable disconnection. Supported power management technologies are e.g. Advanced Configuration Power management Interface (ACPI), Link Power Management (LPM) or IEEE 802.3az EEE (Energy Efficient Ethernet) and more.

Power Delivery input:
• Power Delivery 3.0 support – device power supply from the PD wall charger via USB-C hub.
• Maximum power supply power via PD USB-C hub output 100W - 20V/5A.
• Notebook or phone with Power Delivery charging support from the USB-C port and a suitable PD charger is necessary.

SATA M.2 slot:
• SATA M.2 SSD disks.
• Designed for B+M-key or B-key SATA (AHCI) M.2 SSDs without maximum capacity limitation.
• NGFF 75-pin B-key slot for SATA M.2 drives.
• Supports M.2 drives with a size of 2230, 2242, 2260, 2280 mm.
• Support of both one-sided and double-sided M.2 SSDs.
• Compliant with Serial ATA 3.2 specification (SATA/600), bit rates of up to 6 Gb/s (600 MB/s).
• Compliant with USB Mass Storage Class specification.
• Supports UASP (USB Attached SCSI) for faster data transmission in Windows 8 and later.
• Support of TRIM functionality to limit gradual degradation of the SSD performance over time.
• SSD boot support in external box.

Other features:
• Possibility to connect your device while running thanks to the Hot Plug support.
• Full Plug and Play support.
• Standby mode support.

• Power via USB bus - USB bus power or from PD wall charger.
• Heavy-duty aluminium body for better hub cooling. Higher surface hub temperature is not a problem - the heat generated by the hub and M.2 disk operation is better dissipated and transferred to the surroundings.
• Two indication LED – white LED indicates computer USB port connection (steady light), blue LED indicates data transfer in M.2 slot (blinking).
• High quality shielded cable ensures fast communication speed and minimal unwanted interference.
• Dimensions 123 x 51 x 14 mm.
• Weight 72 g (incl. cable).
• USB cable length 18 cm.

Supported operating systems:
• Microsoft Windows 10, Mac OS, Linux, Android and Chrome OS.
Compatibility depends on used OS and support from device manufacturer.
• Note 1: Drivers are included with supported operating systems and are installed automatically. No other drivers need to be installed.
• Note 2: DisplayPort Alternate Mode (DP Alt Mode) is only supported in updated OS and also depends on support from device (notebook, phone) manufacturer.

Package contains:
• USB-C hub with fixed 18 cm long cable,
• mounting material,
• printed installation manual in CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / TR / BG / CN / ARA,
• packed in a cardboard box with a hanging hole.

Techninė specifikacija

Ryšys	
Ryšio technologija	Vielinis
Priimančioji sąsaja	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	2
HDMI portų kiekis	1
Mikrofonas, line-in jack	Ne
USB 3.2 (3.1 1 kart.) C tipo prievadų skaičius	1
„USB Power Delivery“	Taip
USB maitinimo šaltinio peržiūra	3.0
USB maitinimo tiekimas iki	100 W
Jungtinis ausinių / mikrofono prievadas	Ne
HDCP	Taip
HDCP versija	1.4/2.3
„USB Type C DisplayPort Alternate Mode“	Taip
DC įėjimo lizdas	Ne
Tinklas	
Ethernet LAN jungtis	Taip
Ethernet LAN (RJ-45) portų kiekis	1

Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Wake-on-LAN pasirengimas	Taip
Tinklo standartai	IEEE 802.1Q, IEEE 802.1p
Jumbo Frames palaikymas	Taip
Pilnai abipusis (duplex)	Taip

Veikimo charakteristikos

Produkto spalva	Aliuminis
Integruotas kortelių skaitytuvas	Ne
Palaikomų saugojimo tvarkyklių skaičius	1
Palaikomi saugojimo kaupiklių tipai	SSD
Palaikomi saugojimo kaupiklio dydžiai	M.2
Integruotas SSD diskas	Ne
SSD Drive sąsajos	M.2, SATA, SATA II, SATA III
NVMe	Ne
Suderinami SSD dydžiai	M.2
SSD korpusas	Taip
Duomenų perdavimo sparta	5 Gbit/s
HD tipas	4K Ultra HD
Maksimali skaitmeninė raiška	4096 x 2160 pikseliai
Maksimalus atnaujinimo dažnis	120 Hz
Hot-Plug palaikymas	Taip
Lizdo sąsajos	HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C
LED indikatoriai	Taip
„Plug and Play“ funkcija	Taip
Įkrovimo funkcija	Taip
UASP palaikymas	Taip
Korpuso medžiaga	Aliuminis
Kilmės šalis	Kinija
Modelio suderinamumas	Universalus
Sertifikavimas	CE, RoHS

Garsas

Įmontuoti garsiakalbiai	Ne
Įmontuotas mikrofonas	Ne

Aušinimas

Įmontuotas ventiliatorius	Ne

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Energijos valdymas	
Maitinimo šaltinio tipas	USB
Maitinimo jungtis	C tipo USB
Maitinimo tipas	USB
Išėjimo įtampa	20 V
Išėjimo srovė	5 A
USB kabelio ilgis	0,18 m
Belaidis įkrovimas	Ne
Programinė įranga	
Palaikomos „Windows“ operacinės sistemos	Taip
Palaikomos MAC operacinės sistemos	Taip
Palaikoma operacinė sistema „Linux“	Taip
Palaikomos serverio valdymo sistemos	Taip
Palaikomos mobiliosios operacinės sistemos	Taip
Kitos palaikomos operacinės sistemos	Android, ChromeOS
Svoris ir matmenys	
Plotis	51 mm
Ilgis	14 mm
Aukštis	123 mm
Svoris	72 g
Pakuotės duomenys	
Kiekis pakuotėje	1 vnt
Pakuotės plotis	97 mm
Pakuotės gylis	20 mm
Pakuotės aukštis	220 mm
Paketo svoris	116 g
Pakuotės turinys	
Pridėti kabeliai	C tipo USB
Instrukcija	Taip
Techninė informacija	
Garantinis laikotarpis	3 metai
Atitikties sertifikatai	RoHS, CE
Kitos savybės	
Kabelio ilgis	0,18 m

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Kabelio tipas	Round cable
Perkrovos apsauga	Taip
Matmenys ir svoris	
Matmenys (I × P × A)	2,00cm × 10,00cm × 22,00cm

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.