

# Lindy USB 3.2 Type C Hub and Gigabit Ethernet Converter

Gamintojas: **LINDY** · Modelis: **43249** · EAN: **4002888432498** · Prekės kodas: **553568**



## 39,91 €

Kaina su PVM

Be PVM: **32,98 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Connects a USB 3.2 Type C computer to a Gigabit Ethernet network
- ✓ Provides three USB 3.2 / 3.1 Gen 1 / 3.0 Type A ports
- ✓ Supports 10/100/1000BASE-T, full and half duplex mode
- ✓ USB 3.2 / 3.1 Gen 1 / 3.0 SuperSpeed data transfer rates up to 5Gbps
- ✓ 2 year warranty



## Aprašymas

The Lindy USB 3.2 Hub and Gigabit Ethernet Converter allows users to conveniently connect a ultrabook, netbook or tablet to a Gigabit Ethernet network via a Type C USB port and also provides three additional USB 3.2 / 3.1 Gen 1 / 3.0 Type A ports.

This converter is ideal for ultrabooks or tablets which do not feature wired network connectivity and may only offer a limited number of USB ports.

With its small size and lightweight design this USB 3.2 Hub and Gigabit Ethernet Converter is easy and convenient to carry, and because it is powered by the USB Bus no power adapter is required. It is backwards compatible with Thunderbolt 3 ports to cover a wide range of devices including MacBooks.

Information about USB 3.0, 3.1 and 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host

interface.USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps. USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Techninė specifikacija

| Specifications                                  |                                         |
|-------------------------------------------------|-----------------------------------------|
| Sandėlio grupė                                  | USB Hubs [+68][-73]                     |
| Ports & interfaces                              |                                         |
| Ports quantity                                  | 4                                       |
| Host interface                                  | USB 3.2 Gen 1 (3.1 Gen 1) Type-C        |
| Hub interfaces                                  | RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 3                                       |
| Ethernet LAN (RJ-45) ports                      | 1                                       |
| Features                                        |                                         |
| Data transfer rate                              | 5000 Mbit/s                             |
| Product colour                                  | Black                                   |
| Housing material                                | Plastic                                 |
| Cable length                                    | 0.26 m                                  |
| Certification                                   | CE, FCC, RoHS, REACH                    |
| Power                                           |                                         |
| Power source type                               | USB                                     |
| USB powered                                     | Yes                                     |
| Weight & dimensions                             |                                         |
| Width                                           | 30 mm                                   |
| Depth                                           | 110 mm                                  |
| Height                                          | 20 mm                                   |
| Packaging content                               |                                         |
| Manual                                          | Yes                                     |
| Operational conditions                          |                                         |
| Operating temperature (T-T)                     | 0 - 50 °C                               |
| Storage temperature (T-T)                       | -10 - 75 °C                             |
| Operating relative humidity (H-H)               | 0 - 85%                                 |
| Logistics data                                  |                                         |
| Harmonized System (HS) code                     | 84719000                                |
| Matmenys ir svoris                              |                                         |

Matmenys (I × P × A)

14,00cm × 10,00cm × 3,00cm