

Lindy USB 3.0 Hub and Gigabit Ethernet Converter

Gamintojas: **LINDY** · Modelis: **43176** · EAN: **4002888431767** · Prekės kodas: **553892**



37,90 €

Kaina su PVM

Be PVM: **31,32 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connects a USB 3.0 Type A computer to a Gigabit Ethernet network
- ✓ Provides three USB 3.1 Gen 1 / 3.0 Type A ports
- ✓ Supports 10/100/1000BASE-T, full and half duplex mode
- ✓ USB 3.1 Gen 1 / 3.0 SuperSpeed data transfer rates up to 5Gbps
- ✓ 2 year warranty



Aprašymas

The Lindy USB 3.0 Hub and Gigabit Ethernet Converter allows users to conveniently connect a notebook or ultrabook to a Gigabit Ethernet network via a Type A USB port and also provides three additional USB 3.1 Gen 1 / 3.0 Type A ports.

This converter is ideal for notebooks which do not feature wired network connectivity and may only offer a limited number of USB ports.

With its small size and lightweight design this USB 3.0 Hub and Gigabit Ethernet Converter is easy and convenient to carry, and because it is powered by the USB Bus no power adapter is required.

Information about USB 3.0, 3.1 and 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface. USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps. USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Techninė specifikacija

Ports & interfaces	
Ports quantity	4
Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
Hub interfaces	RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
Ethernet LAN (RJ-45) ports	1
Features	
Data transfer rate	5000 Mbit/s
Product colour	Black
Housing material	Plastic
Cable length	0.29 m
Certification	CE, UKCA, FCC, RoHS, REACH
Network	
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u
Power	
Power supply type	USB
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Weight & dimensions	
Width	40 mm
Depth	110 mm
Height	20 mm
Weight	60 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	175 mm
Package depth	129 mm
Package height	30 mm
Package weight	100 g

Package type	Blister
Packaging content	
Manual	Yes
Operational conditions	
Minimum operating temperature	0 °C
Maximum operating temperature	70 °C
Operating temperature (T-T)	0 - 70 °C
Operating temperature (T-T)	0 - 158 °F
Storage temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Logistics data	
Harmonized System (HS) code	84719000
Other features	
Chipset	AX88179 (LAN), VL813 (Hub)
Matmenys ir svoris	
Matmenys (I × P × A)	16,00cm × 16,00cm × 2,00cm