



# I/O HUB USB3.2 3PORT GLAN/0.2M HMA-GL3A AXAGON

Modelis: HMA-GL3A

Gamintojas: AXAGON

EAN: 8595247905598

Prekės kodas: 554015

## 21.99€

Slim metal USB 3.2 Gen 1 (USB 3.0) multi-port hub AXAGON HMA-GL3A connects up to three USB devices to laptop or computer and also adds Gigabit network card which connects your computer to high speed network.

The metal hub body is made of aluminum and provides perfect mechanical protection for frequent carrying. Elegant finely structured body surface against fingerprint. Permanently fixed 20 cm long USB cable is ideal for users of mobile devices.

This compact multiport hub also handles the permanent connection of several external drives. Thanks to the fast USB 3.2 Gen 1 interface is transfer speed up to 5Gb/s.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

The Gigabit network adapter expands the computer with a fast and stable network connection, adds the missing RJ-45 network connector or adds another network card. The LAN adapter is compatible with 10/100/1000 Mbit/s speed and also offers a wide range of features, such as IPv4/IPv6 checksum to reduce CPU load by checksums, the crossover detection and auto-correction, support for various modes of the Wake-on-LAN feature, the work with virtual LAN (VLAN) and advanced Power Management features. In modern operating systems from Windows 8.1 above, the adapter allows easy automatic installation without the need for an Internet connection.

The port replicator is the ideal accessory for ultrabooks with a small number of USB-A ports and without network card. The hub does not even frighten to connect with phones using the appropriate OTG or USB-A > USB-C adapter. You can connect a flash drive, keyboard and mouse to your phone or tablet. Some phones and tablets with the Android operating system, such as the Samsung S9+, can be connected to the Internet with a network Ethernet cable with suitable adapter\* thanks to this hub.

#### Input:

- 1x USB 3.2 Gen 1 / SuperSpeed USB port, USB-A male connector.
- Backward compatible with USB 3.1 Gen 1 / USB 3.0 / USB 2.0 and USB 1.1.
- Connecting USB type A male connector on a fixed 20 cm long cable.

#### USB Outputs:

- 3x SuperSpeed USB port, USB-A female connectors.
- Support transfer rates 5.000 / 480 / 12 / 1.5 Mb/s (SuperSpeed / High / Full / Low speed).
- The total bandwidth / transfer rate of the box is given by the USB 3.2 Gen 1 interface (theoretically up to 5 Gbit/s).
- USB hub handle the permanent connection of several external drives.

#### RJ-45 Output:

- Gigabit Ethernet interface with RJ-45 connector for UTP or STP cable connection.
- Supported transmission rates for the Ethernet interface 10/100/1000 Mb/s.
- Supported IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T specifications.
- 10/100/1000 Mbit/s auto-detection.
- Supports IPv4/IPv6 packet Checksum Offload Engine (COE) to reduce processor load, including IPv4

IP/TCP/UDP/ICMP/ IGMP & IPv6 TCP/UDP/ICMPv6 checksum control and generation.

- Supports TCP Large Send Offload V1 and V2.
- Supports IEEE 802.1P Layer 2 priority encoding & decoding.
- Supports IEEE 802.1Q VLAN tagging.
- Supports IEEE 802.3az EEE (Energy Efficient Ethernet) - reduce power consumption at rest.
- Supports Jumbo frame.
- Supports full-duplex transmissions with IEEE 802.3x flow control and half-duplex transmissions with back-pressure flow control.
- Supports Auto MDI/MDIX - crossover detection and auto-correction eliminates the need for crossover cables.
- Supports hardware Cyclic Redundancy Check (CRC) to detect transmission errors.
- Supports Pair Swap/Polarity/Skew Correction.

Wake-on-LAN feature support in different modes:

- Supports sleep mode and remote Wake Up via Magic Packet, Microsoft Wakeup Frame, Microsoft Wake Packet Detection and Link Change Wake-up.
- Supports ECMA-393 proxZzy® standard for sleeping hosts to manage the network connection of sleeping guests using proxy servers.
- RealWoW! technology support allows remote wake up over the Internet.

Advanced Power Management features:

The adapter supports advanced power management to reduce losses during standby or light traffic on the network. It further supports advanced power saving when the Ethernet cable has been disconnected.

- Supports Advanced Configuration Power Management Interface (ACPI).
- Supports Power Management offload (ARP & NS).
- Supports Microsoft Always On Always Connected (AOAC).
- Supports Intel Converged Platform Power Management (CPPM).
- Supports Link Power Management (LPM).
- Supports Operating System-directed Power Management (OSPM).
- Supports IEEE 802.3az EEE (Energy Efficient Ethernet).

Other features:

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

- Possibility to connect your device while running thanks to the Hot Plug support.
- Full Plug and Play support.
- Sleep mode support.
- The high quality shielded cable ensures high communication speed and minimal undesirable interference.
- Power supply via USB bus (USB bus power).
- Dimensions 90 x 23 x 13 mm.
- Weight 38 g (incl. cable).
- USB cable length 20 cm.

#### Supported OS:

- MS Windows XP / Vista / 7 / 8 / 8.1 / 10 and later, Windows Server 2003 / 2008 / 2012 / 2016 and later (supported are all 32 and 64-bit versions of Windows OSs), MacOS X 10.4.x and later, Linux with kernel 2.6.x and later, Android most versions (WARNING - check with the Android device manufacturer if the Ethernet connection is supported).

#### Package contains:

- SuperSpeed USB multi port hub with fixed 20 cm long USB cable,
- printed installation manual in CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / TR / BG / CN / ARA,
- packed in a cardboard box with a hanging hole.

\* We recommend OTG reduction (adapter) for devices with a micro USB connector, for devices with USB-C connector we recommend USB-C > USB-A reduction, for example AXAGON RUCM-AFA.

Summary: Axagon HMA-GL3A Multiport-Hub USB 3.0 Typ A Gbit-LAN 3x USB-A microSD. Connectivity technology: Wired, Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-A. Ethernet LAN data rates: 10,100,1000 Mbit/s, Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Product colour: Black, Data transfer rate: 5 Gbit/s, Hub interfaces: RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A. Power source type: USB, Power connector: USB Type-A, Power supply type: USB. Width: 90 mm, Depth: 23 mm, Height: 13 mm | Vendor Homepage: <https://www.axagon.eu/en/produkty/hma-gl3a> | Combo headphone/mic port: No | Connectivity technology: Wired | DC-in jack: No | Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-A | Microphone in: No | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 3 | USB Power Delivery (USB PD): No | Auto

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shoppro.lt](http://www.shoppro.lt) | [info@shoppro.lt](mailto:info@shoppro.lt) | +370 693 39903

MDI/MDI-X: Yes | Ethernet LAN: Yes | Ethernet LAN (RJ-45) ports: 1 | Ethernet LAN data rates: 10/100/1000 | Full duplex: Yes | Jumbo frames support: Yes | Networking standards: IEEE 802.1p/IEEE 802.1Q/IEEE 802.3/IEEE 802.3ab/IEEE 802.3az/IEEE 802.3u/IEEE 802.3x | VLAN tagging: Yes | Wake-on-LAN ready: Yes | Brand compatibility: Universal | Card reader integrated: No | Certification: CE, RoHS | Country of origin: China | Data transfer rate: 5 | Hot-Plug support: Yes | Hub interfaces: RJ-45/USB 3.2 Gen 1 (3.1 Gen 1) Type-A | LED indicators: Yes | Plug and Play: Yes | Product colour: Black | Built-in microphone: No | Built-in speaker(s): No | Built-in fan: No | Power connector: USB Type-A | Power source type: USB | Power supply type: USB | USB cable length: 0.2 | Wireless charging: No | Linux operating systems supported: Yes | Mac operating systems supported: Yes | Mobile operating systems supported: Yes | Other operating systems supported: Yes | Server operating systems supported: Yes | Windows operating systems supported: Yes | Depth: 23 | Height: 13 | Weight: 38 | Width: 90 | Package depth: 100 | Package height: 28 | Package weight: 75 | Package width: 203 | Quantity per pack: 1 | Cables included: USB | Manual: Yes | Compliance certificates: RoHS | Warranty period: 2 | Cable length: 0.2 | Model: HMA-GL3A | Units per Shipping Box: 1 | Unit Calculated Volume: 0.0006 | Unit Calculated Weight: 0.09