# Axagon HMA-GL3A Multiport-Hub USB 3.0 Typ A Gbit-LAN 3x USB-A microSD Vielinis USB 3.2 Gen 1 (3.1 Gen 1) Type-A Juoda

Gamintojas: **AXAGON** · Modelis: **HMA-GL3A** · EAN: **8595247905598** · Prekės kodas: **554015**




**22,91 €**

Kaina su PVM

Be PVM: **18,93 €**

**Sandėlyje**

**Prekė internetu**
Nuskenuokite kodą arba apsilankykite www.shopro.lt

## Pagrindinės savybės

- ✓ Vielinis
- ✓ Priimančioji sąsaja: USB 3.2 Gen 1 (3.1 Gen 1) Type-A
- ✓ Ethernet LAN jungtis 10,100,1000 Mbit/ai Wake-on-LAN pasirengimas
- ✓ Auto MDI/MDI-X Pilnai abipusis (duplex) Jumbo Frames palaikymas
- ✓ „Plug and Play“ funkcija








## Aprašymas

Slim metal USB 3.2 Gen 1 (USB 3.0) multi-port hub AXAGON HMA-GL3A connects up to three USB devices to laptop or computer and also adds Gigabit network card which connects your computer to high speed network.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

The metal hub body is made of aluminum and provides perfect mechanical protection for frequent carrying. Elegant finely structured body surface against fingerprint. Permanently fixed 20 cm long USB cable is ideal for users of mobile devices.

This compact multiport hub also handles the permanent connection of several external drives. Thanks to the fast USB 3.2 Gen 1 interface is transfer speed up to 5Gb/s.

The Gigabit network adapter expands the computer with a fast and stable network connection, adds the missing RJ-45 network connector or adds another network card. The LAN adapter is compatible with 10/100/1000 Mbit/s speed and also offers a wide range of features, such as IPv4/IPv6 checksum to reduce CPU load by checksums, the crossover detection and auto-correction, support for various modes of the Wake-on-LAN feature, the work with virtual LAN (VLAN) and advanced Power Management features. In modern operating systems from Windows 8.1 above, the adapter allows easy automatic installation without the need for an Internet connection.

The port replicator is the ideal accessory for ultrabooks with a small number of USB-A ports and without network card. The hub does not even frighten to connect with phones using the appropriate OTG or USB-A > USB-C adapter. You can connect a flash drive, keyboard and mouse to your phone or tablet. Some phones and tablets with the Android operating system, such as the Samsung S9+, can be connected to the Internet with a network Ethernet cable with suitable adapter* thanks to this hub.

Input:
• 1x USB 3.2 Gen 1 / SuperSpeed USB port, USB-A male connector.
• Backward compatible with USB 3.1 Gen 1 / USB 3.0 / USB 2.0 and USB 1.1.
• Connecting USB type A male connector on a fixed 20 cm long cable.

USB Outputs:
• 3x SuperSpeed USB port, USB-A female connectors.
• Support transfer rates 5.000 / 480 / 12 / 1.5 Mb/s (SuperSpeed / High / Full / Low speed).
• The total bandwidth / transfer rate of the box is given by the USB 3.2 Gen 1 interface (theoretically up to 5 Gbit/s).
• USB hub handle the permanent connection of several external drives.

RJ-45 Output:
• Gigabit Ethernet interface with RJ-45 connector for UTP or STP cable connection.
• Supported transmission rates for the Ethernet interface 10/100/1000 Mb/s.
• Supported IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T specifications.
• 10/100/1000 Mbit/s auto-detection.
• Supports IPv4/IPv6 packet Checksum Offload Engine (COE) to reduce processor load, including IPv4 IP/TCP/UDP/ICMP/ IGMP & IPv6 TCP/UDP/ICMPv6 checksum control and generation.
• Supports TCP Large Send Offload V1 and V2.
• Supports IEEE 802.1P Layer 2 priority encoding & decoding.
• Supports IEEE 802.1Q VLAN tagging.
• Supports IEEE 802.3az EEE (Energy Efficient Ethernet) - reduce power consumption at rest.
• Supports Jumbo frame.
• Supports full-duplex transmissions with IEEE 802.3x flow control and half-duplex transmissions with back-pressure flow control.
• Supports Auto MDI/MDIX - crossover detection and auto-correction eliminates the need for crossover cables.
• Supports hardware Cyclic Redundancy Check (CRC) to detect transmission errors.
• Supports Pair Swap/Polarity/Skew Correction.

Wake-on-LAN feature support in different modes:
• Supports sleep mode and remote Wake Up via Magic Packet, Microsoft Wakeup Frame, Microsoft Wake Packet Detection and Link Change Wake-up.
• Supports ECMA-393 proxZzzy® standard for sleeping hosts to manage the network connection of sleeping guests using proxy servers.
• RealWoW! technology support allows remote wake up over the Internet.

Advanced Power Management features:
The adapter supports advanced power management to reduce losses during standby or light traffic on the network. It further supports advanced power saving when the Ethernet cable has been disconnected.
• Supports Advanced Configuration Power Management Interface (ACPI).
• Supports Power Management offload (ARP & NS).
• Supports Microsoft Always On Always Connected (AOAC).
• Supports Intel Converged Platform Power Management (CPPM).
• Supports Link Power Management (LPM).
• Supports Operating System-directed Power Management (OSPM).
• Supports IEEE 802.3az EEE (Energy Efficient Ethernet).

Other features:
• Possibility to connect your device while running thanks to the Hot Plug support.
• Full Plug and Play support.
• Sleep mode support.
• The high quality shielded cable ensures high communication speed and minimal undesirable interference.
• Power supply via USB bus (USB bus power).
• Dimensions 90 x 23 x 13 mm.
• Weight 38 g (incl. cable).
• USB cable length 20 cm.

Supported OS:
• MS Windows XP / Vista / 7 / 8 / 8.1 / 10 and later, Windows Server 2003 / 2008 / 2012 / 2016 and later (supported are all 32 and 64-bit versions of Windows OSs), MacOS X 10.4.x and later, Linux with kernel 2.6.x and later, Android most versions (WARNING - check with the Android device manufacturer if the Ethernet connection is supported).

Package contains:
• SuperSpeed USB multi port hub with fixed 20 cm long USB cable,
• printed installation manual in CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / TR / BG / CN / ARA,
• packed in a cardboard box with a hanging hole.

* We recommend OTG reduction (adapter) for devices with a micro USB connector, for devices with USB-C connector we recommend USB-C > USB-A reduction, for example AXAGON RUCM-AFA.

## Techninė specifikacija

| | |
|---|---|
| **Ryšys** | |
| Ryšio technologija | Vielinis |
| Priimančioji sąsaja | USB 3.2 Gen 1 (3.1 Gen 1) Type-A |
| USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius | 3 |
| Mikrofonas, line-in jack | Ne |
| „USB Power Delivery“ | Ne |
| Jungtinis ausinių / mikrofono prievadas | Ne |
| DC įėjimo lizdas | Ne |
| **Tinklas** | |
| Ethernet LAN jungtis | Taip |

| | |
|---|---|
| Ethernet LAN (RJ-45) portų kiekis | 1 |
| Eterneto LAN duomenų perdavimo norma | 10,100,1000 Mbit/ai |
| Wake-on-LAN pasirengimas | Taip |
| Tinklo standartai | IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x |
| Jumbo Frames palaikymas | Taip |
| Auto MDI/MDI-X | Taip |
| Pilnai abipusis (duplex) | Taip |
| VLAN tinklo žymėjimas | Taip |
| **Veikimo charakteristikos** | |
| Produkto spalva | Juoda |
| Integruotas kortelių skaitytuvas | Ne |
| Duomenų perdavimo sparta | 5 Gbit/s |
| Hot-Plug palaikymas | Taip |
| Lizdo sąsajos | RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A |
| LED indikatoriai | Taip |
| „Plug and Play“ funkcija | Taip |
| Kilmės šalis | Kinija |
| Modelio suderinamumas | Universalus |
| Sertifikavimas | CE, RoHS |
| **Garsas** | |
| Įmontuoti garsiakalbiai | Ne |
| Įmontuotas mikrofonas | Ne |
| **Aušinimas** | |
| Įmontuotas ventiliatorius | Ne |
| **Energijos valdymas** | |
| Maitinimo šaltinio tipas | USB |
| Maitinimo jungtis | USB A tipo |
| Maitinimo tipas | USB |
| USB kabelio ilgis | 0,2 m |
| Belaidis įkrovimas | Ne |
| **Programinė įranga** | |
| Palaikomos „Windows“ operacinės sistemos | Taip |
| Palaikomos MAC operacinės sistemos | Taip |
| Palaikoma operacinė sistema „Linux“ | Taip |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

| | |
|---|---|
| Palaikomos serverio valdymo sistemos | Taip |
| Palaikomos mobiliosios operacinės sistemos | Taip |
| Kitos palaikomos operacinės sistemos | Taip |
| **Svoris ir matmenys** | |
| Plotis | 90 mm |
| Ilgis | 23 mm |
| Aukštis | 13 mm |
| Svoris | 38 g |
| **Pakuotės duomenys** | |
| Kiekis pakuotėje | 1 vnt |
| Pakuotės plotis | 203 mm |
| Pakuotės gylis | 100 mm |
| Pakuotės aukštis | 28 mm |
| Paketo svoris | 75 g |
| **Pakuotės turinys** | |
| Pridėti kabeliai | USB |
| Instrukcija | Taip |
| **Techninė informacija** | |
| Garantinis laikotarpis | 3 metai |
| Atitikties sertifikatai | RoHS |
| **Kitos savybės** | |
| Kabelio ilgis | 0,2 m |
| **Matmenys ir svoris** | |
| Matmenys (I × P × A) | 3,00cm × 10,00cm × 20,00cm |

## Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

## Gamintojo ir saugos informacija

GAMINTOJAS

**RealQ, s.r.o.**
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

PLATINTOJAS

**MB KOMPIUTERIŲ GURU**
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.