Axagon EEM2-UB2 saugojimo diskų korpusas SSD korpusas Juoda M.2

Gamintojas: **AXAGON** · Modelis: **EEM2-UB2** · EAN: **8595247908506** · Prekės kodas: **554023**



21,90 €

Kaina su PVM

Be PVM: **18,10 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ SSD korpusas M.2, NVMe-oF M.2
- ✓ Palaikomų saugojimo tvarkyklių skaičius: 1
- ✓ NVMe
- ✓ USB jungtis
- ✓ S.M.A.R.T. palaikymas TRIM palaikymas UASP palaikymas
- ✓ 10 Gbit/s
- ✓ Maitinimo šaltinio tipas: USB
- ✓ Juoda
















Aprašymas

Fast external AXAGON EEM2-UB2 ARROW box with USB 10Gbps interface for M.2 NVMe SSDs. The double-sided USB-C connector on the box enables a reliable connection. In the package you will find an USB-C -> USB-C cable to connect the box to your computer.

The transmission rate is up to 10Gb/s thanks to the fast USB 3.2 Gen 2 interface. The external M.2 box also supports other modern features e.g. UASP, TRIM and enables reading S.M.A.R.T. disk status monitoring information. Standby support when idle.

The advantage is the attachment of three different lengths of SSD cards - 42, 60 and 80 mm. M.2 drives can be single-sided or double-sided. The box does not limit the capacity of inserted SSD.

Opening the box via only one screw makes it easy to mount and dismount the M.2 SSD. Disk replacement is quick and easy, thus expanding the possibilities of using the box, e.g. for data migration, testing, etc.

The outer metal housing is made in black colour with an elegant finish, that prevents unwanted fingerprints.

Aluminum box body and thermal conductive pad provides very good M.2 SSD disk cooling. This extends its service life and also prevents the disk from slowing down, so-called „Thermal Throttling“.

By inserting the M.2 SSD in the box, you will easily create fast compact and universal external disk. The box can be used with computers and notebooks, as well as with mobile phones and tablets.

Input:
• USB 10Gbps (USB 3.2 Gen 2), connector USB-C female.
• Compatible with USB 3.2 Gen 1, USB4 and Thunderbolt 3/4.

Device support:
• NMVe M.2 SSD disks,
• designed for M key or B+M key card formats,
• NGFF 75-pin M key slot for M.2 drives.

Other features:
• Supports transmission rates 10.000 / 5000 / 480 Mbit/s.
• Support of M key or B+M key NVMe (PCI-Express) M.2 SSD disks without a maximum capacity limit.
• Support of M.2 drives with a size of 2242, 2260, 2280 mm.
• Support of both one-sided and double-sided M.2 SSDs.
• Compliant with PCI Express Base Specification Revision 3.1a specification.
• Compliant with NVM Express 1.3 specification.
• Compliant with USB Mass Storage Class specification.
• The total bandwidth / transmission rate of the adapter is determined by the USB interface used (theor. 10 Gbit/s).
• The real adapter bandwidth / transmission rate is about 1.000 MB/s (1 GB/s), it is given by the limits of the USB 3.2 Gen 2 interface.
• Supports BOT (Bulk-Only Transport).
• Supports UASP (USB Attached SCSI) for faster data transmission in Windows 8 and later.
• Supports TRIM functionality to limit gradual degradation of the SSD performance over time.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

• Supports S.M.A.R.T. (Self-Monitoring, Analysis, and Reporting Technology) system monitoring disk condition.
• SSD boot support in external box.
• Possibility to connect your device while running thanks to the Hot Plug support.
• Full Plug and Play support.
• Standby support - drive asleep after 5 minutes of inactivity.
• Power supply via USB 3.0 bus up to 900mA from one USB port is sufficient in all cases.
• A decent blue LED indicating the connection to the computer's USB port (permanent light) and data transmission (blinking).
• Heavy-duty aluminium body and thermal conductive pad helps to better cooling the M.2 SSD disk.
• Higher box surface temperature is not a defect - thanks to the aluminum body, the heat generated by the disk operation is better drained and transferred to the environment.
• Connection via USB 3.2 Gen 2 type C female connector.
• USB type C male / USB type C male cable length 20 cm in the package.

Other data:
• Box dimensions 115 x 39 x 11 mm.
• Box weight 43 g (without cable and M.2 SSD disk).

Supported operating systems:
• Windows 7 / 8.1 / 10 / 11 and later, macOS, iPadOS, iOS, Linux, Chrome OS and Android.
• Compatibility depends on the operating system and device manufacturer support.
• Note: when Windows 7 used it is necessary to check OS support and driver availability with the M.2 SSD manufacturer.

Package contains:
• USB-C 10Gbps external box for M.2 SSD,
• USB-C - USB-C cable 20 cm long,
• 3 thermal conductive pads,
• mounting material and a screwdriver,
• multilingual manual CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / SK / SWE / TR / UA / BG / CN / ARA,
• packed in a cardboard box with a hanging hole.

Techninė specifikacija

Laikmenos	
Saugojimo kaupiklio dydis	M.2
Palaikomi saugojimo kaupiklių sąsajos	M.2, NVMe-oF
Palaikomų saugojimo tvarkyklių skaičius	1
Palaikomi kaupiklio ilgiai	42,60,80 mm
NVMe	Taip
Ryšys	
USB jungtis	Taip
USB versija	3.2 Gen 2 (3.1 Gen 2)
USB jungtis	C tipo USB
USB jungties lytis	Lizdinis
USB prievadų skaičius	1
Konstrukcija	

Gaminio tipas	SSD korpusas
Produkto spalva	Juoda
Medžiaga	Aliuminis
LED indikatoriai	Taip
Sertifikavimas	CE, RoHS
Veikimo charakteristikos	
Duomenų perdavimo sparta	10 Gbit/s
UASP palaikymas	Taip
TRIM palaikymas	Taip
S.M.A.R.T. palaikymas	Taip
„Plug and Play“ funkcija	Taip
Energijos valdymas	
Maitinimo šaltinio tipas	USB
Išorinio maitinimo adapteris	Ne
Sistemos reikalavimai	
Palaikomos mobiliosios operacinės sistemos	Taip
Palaikomos „Windows“ operacinės sistemos	Windows 10, Windows 11, Windows 7, Windows 8, Windows 8.1
Palaikoma operacinė sistema „Linux“	Taip
Palaikomos MAC operacinės sistemos	Taip
Svoris ir matmenys	
Plotis	39 mm
Ilgis	115 mm
Aukštis	11 mm
Svoris	43 g
Kabelio ilgis	0,2 m
Pakuotės plotis	83 mm
Pakuotės gylis	175 mm
Pakuotės aukštis	28 mm
Paketo svoris	102 g
Pakuotės turinys	
Pakuotės tipas	„Box“
Pridėti kabeliai	Iš C tipo USB į C tipo USB
Pridėti sraigtai	Taip
Pridėtas atsuktuvas	Taip

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Instrukcija	Taip
Techninė informacija	
Garantinis laikotarpis	3 metai
Atitikties sertifikatai	RoHS
Matmenys ir svoris	
Matmenys (I × P × A)	3,00cm × 9,00cm × 18,00cm

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.