

# TP-Link 5-Port 10/100/1000Mbps Desktop Network Switch

 Gamintojas: **TP-LINK** · Modelis: **LS105G** · EAN: **6935364085445** · Prekės kodas: **554266**


## 17,90 €

Kaina su PVM

 Be PVM: **14,79 €**

Sandėlyje


**Prekė internetu**

 Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ 10/100/1000Mbps Auto-Negotiation RJ45 port supporting Auto-MDI/MDIX
- ✓ Green Ethernet technology saves power
- ✓ IEEE 802.3X flow control provides reliable data transfer
- ✓ Steel housing, desktop or wall-mounting design
- ✓ Support 802.1p/DSCP QoS function
- ✓ Plug and play, no configuration needed



## Aprašymas

### Increase Your Network Speed and Save Energy

#### Let LiteWave Bring You Lighter Network Life

The TP-Link LiteWave Series Unmanaged Switches provide easy and affordable way to expand your wired network. They are easy to use and reliable. With these plug-and-play switches, you can expand your network connections to multiple devices instantly. With all ports support Auto-MDI/MDIX, there's no need to worry about the type of cable to use.

#### Go Green with Your Ethernet

The LiteWave Series also supports energy-efficient technology, helping you save power and money. Power consumption automatically adjusts according to link status and cable length, allowing you to expand your network while minimizing your carbon footprint. Save the planet and lower your energy bills — it's a win-win!

### Durable Metal Casing

The interior components of LS105G are protected by high-quality metal casing to ensure a long product life. Having passed an array of stringent reliability tests, LS105G delivers switching performance you can depend on. Its compact size makes it ideal for deployment on desktops or work benches.

### Use Where You Need, However You Need

The LS105G is fully compatible with networked devices such as computers, printers, webcams, IPTVs. It has a wide range of application scenarios and is suitable for networking in school dormitories, surveillance, homes, and small businesses.

## Techninė specifikacija

| Specifications                                |                                                                  |
|-----------------------------------------------|------------------------------------------------------------------|
| Sandėlio grupė                                | Switches [+133][-162]                                            |
| Management features                           |                                                                  |
| Switch type                                   | Unmanaged                                                        |
| Quality of Service (QoS) support              | Yes                                                              |
| Ports & interfaces                            |                                                                  |
| Basic switching RJ-45 Ethernet ports quantity | 5                                                                |
| Basic switching RJ-45 Ethernet ports type     | Gigabit Ethernet (10/100/1000)                                   |
| Installed SFP modules quantity                | 0                                                                |
| Installed SFP+ modules quantity               | 0                                                                |
| Gigabit Ethernet (copper) ports quantity      | 5                                                                |
| Power connector                               | DC-in jack                                                       |
| Network                                       |                                                                  |
| Networking standards                          | IEEE 802.1p, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x |
| 10G support                                   | No                                                               |
| Auto MDI/MDI-X                                | Yes                                                              |
| Auto-negotiation                              | Yes                                                              |
| Data transmission                             |                                                                  |
| MAC address table                             | 2000 entries                                                     |
| Switching capacity                            | 10 Gbit/s                                                        |
| Forwarding rate                               | 7.4 Mpps                                                         |
| Jumbo frames support                          | Yes                                                              |
| Jumbo frames                                  | 16000                                                            |
| Packet buffer memory                          | 1 MB                                                             |
| Design                                        |                                                                  |
| Rack mounting                                 | No                                                               |

|                                   |                      |
|-----------------------------------|----------------------|
| Product colour                    | Blue                 |
| Housing material                  | Metal                |
| LED indicators                    | Activity, LAN, Power |
| Wall mountable                    | Yes                  |
| Power                             |                      |
| Power source                      | DC                   |
| Power supply included             | Yes                  |
| Input current                     | 0.6 A                |
| Input voltage                     | 5 V                  |
| Power consumption (max)           | 2.776 W              |
| Power over Ethernet (PoE)         |                      |
| Power over Ethernet (PoE)         | No                   |
| Operational conditions            |                      |
| Operating temperature (T-T)       | 0 - 40 °C            |
| Storage temperature (T-T)         | -40 - 70 °C          |
| Operating relative humidity (H-H) | 10 - 90%             |
| Storage relative humidity (H-H)   | 5 - 90%              |
| Heat dissipation                  | 9.466 BTU/h          |
| Weight & dimensions               |                      |
| Width                             | 99.8 mm              |
| Depth                             | 98 mm                |
| Height                            | 25 mm                |
| Packaging content                 |                      |
| Quick start guide                 | Yes                  |
| Packaging data                    |                      |
| Package width                     | 125 mm               |
| Package depth                     | 128 mm               |
| Package height                    | 92 mm                |
| Package weight                    | 290 g                |
| Certificates                      |                      |
| Certification                     | CE, FCC, RoHS        |
| Logistics data                    |                      |
| Harmonized System (HS) code       | 85176990             |
| Matmenys ir svoris                |                      |

Matmenys (I × P × A)

13,00cm × 13,00cm × 9,00cm