Axagon ACU-PQ20W mobiliojo įrenginio kroviklis Universalus Balta AC Spartusis įkrovimas Vidaus

Gamintojas: **AXAGON** · Modelis: **ACU-PQ20W** · EAN: **8595247907899** · Prekės kodas: **554295**



14,90 €

Kaina su PVM

Be PVM: **12,31 €**


Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Įkroviklio suderinamumas: Universalus
- ✓ Įkroviklio tipas: Vidaus
- ✓ Maitinimo šaltinio tipas: AC
- ✓ Balta
- ✓ Kontaktas
- ✓ Spartusis įkrovimas Apsauga nuo per didelės įtampos, Apsauga nuo perkaitimo, Apsauga nuo perkrovos, Trumpasis jungimas
- ✓ 100 - 240 V 50 - 60 Hz 20 W Išvesties įtampa (maks.): 20 V



















Aprašymas

The compact AXAGON ACU-PQ20W enables fast charging of up to two mobile devices at the same time. With 20W of total power, the charger charges phones, tablets and other mobile devices at the highest possible speed. The adapter offers a standard USB-A connector, but also double-sided USB-C connector.

The charger is equipped with Power Delivery 3.0 / Quick Charge 4+ USB Type-C outputs and Quick Charge 3.0 USB Type-A outputs, enabling fast charging of not only smartphones and tablets with a power of up to 20W.

The charger supports 20W PD charging for iPhone 12, 13, 14 and 15 and their Pro and Pro Max models. The adapter is also compatible with other fast phone charging standards such as Apple iPhone, iPad, Samsung, Huawei, Honor, Xiaomi.

The advanced protection system at the charging adapter output protects the device being charged from damage. The charger function also detects the device being charged and selects the optimal charging speed and progress.

The body of the power adapter has a pleasant shape and compact size. The combination of small dimensions and a wide range of input voltages, makes the charger an ideal travel helper.

Input:
• input voltage AC 100V-240V / 1A / 50-60 Hz (WIV function) supports multiple national power standards
• two-pin euro plug - integrated in the body of the charger

Outputs:
• USB-A port QC (phones) max. 18W: 5V/3A, 9V/2A, 12V/1.5A
• Charging technology: QC 3.0, QC 2.0, AFC, SCP, FCP, PE+, SMART, Apple 2.4A

• USB-C port PD (tablets, phones) max. 20W: 5V/3A, 9V/2.22A, 12V/1.67A, PPS: 3.3-11V/2A
• Charging technology: PD 3.0, PD 2.0, PPS, QC4+, QC 3.0, QC 2.0, PE+, SMART, Apple PD

Maximum performance using multiple ports:
• maximum power QC + PD 15W, SMART mode charging is used (max. 5V/3A)
• total maximum power 20W
• total maximum current 3A

Supported charging technologies:
• Standard charging of all devices that support 5V and Apple iPhone 5, 6, SE, 7 charging.
• SMART - charging max. 5V/3A, Quick Charge 1.0, USB Battery Charging 1.2 (DCP 1.5A) a Apple 2.4A (iPad).
• PE+ - quick charging using MediaTek Pump Express+ and Pump Express+ 2.0 protocol
• FCP - quick charging using Huawei Fast Charge Protocol.
• SCP - quick charging (up to 20W) using Huawei SuperCharge Protocol.
• AFC - quick charging using Samsung Adaptive Fast Charging protocol.
• QC - quick charging using Qualcomm Quick Charge 2.0, Quick Charge 3.0 and Quick Charge 4+ protocol.
• PPS - quick charging using Programmable Power Supply protocol (part of USB PD 3.0 and QC4+).
• PD - quick charging using USB Power Delivery 2.0 and Power Delivery 3.0 protocol.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Examples of supported phones and tablets:
• PD - quick charging of Apple iPhone 8, 8 Plus, X, XS, XS Max, XR, 11, 11 Pro, 11 Pro Max phone.
• PD - quick charging (up to 20W) Apple iPhone 12, 12 Mini, 12 Pro, 12 Pro Max, 12, 12 Mini, 12 Pro, 12 Pro Max, 13, 13 Mini, 13 Pro, 13 Pro Max, 14, 14 Plus, 14 Pro, 14 Pro Max, 15, 15 Plus, 15 Pro, 15 Pro Max phones.
• PD - quick charging (up to 20W) iPad mini, iPad Air, iPad Pro and other tablets.

The charger supports WIV, AIC and CC functions:
• Wide Input Voltage - function of a wide range of input voltage; it protects the adapter against undervoltage and overvoltage at the input and allows the use of more “national power standards”.
• Automatic Intelligent Communication - function of automatic recognition of the connected device to select optimal charging parameters.
• Constant output Current - the current hold function prevents the output power fluctuations; this function ensures steady course of charging.

Complex output protection: OCP, OVP, OTP, OSP:
• Over Current Protection. Protection of output against current overload.
• Over Voltage Protection. Protection against overvoltage at the output.
• Over Temperature Protection. Protection against overheating of the adapter.
• Output Short Circuit protection. Short circuit protection at the output.

Other features:
• dimensions of the charger body 84 x 36 x 32 mm including a plug,
• weight: 55 g,
• material: non-flammable plastic.

Package contains:
• white wall charger,
• multilingual guide CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / TR / BG / CN / ARA,
• packed in a cardboard box with a hanging hole.

Techninė specifikacija

Veikimo charakteristikos	
Įkroviklio tipas	Vidaus
Įkroviklio suderinamumas	Universalus
Maitinimo šaltinio tipas	AC
Vienalaikiškai sujungtų prietaisų skaičius (maks.)	2
USB 2.0 portų kiekis	1
USB tipo C prievadų kiekis	1
Belaidis įkrovimas	Ne
Spartusis įkrovimas	Taip
Sparčiojo įkrovimo technologija	Power Delivery 3.0, Quick Charge 3.0, Quick Charge 4, Quick Charge 4+
„USB Power Delivery“	Taip
Darbinis principas	Kontaktas
USB maitinimo šaltinio peržiūra	3.0
USB maitinimo tiekimas iki	20 W

Maitinimo apsaugos ypatybės	Apsauga nuo per didelės įtampos, Apsauga nuo perkaitimo, Apsauga nuo perkrovos, Trumpasis jungimas
Specialios funkcijos	Smart IC
Suderinamas su „MagSafe“	Ne
Aušinimo ventiliatorius	Ne

Konstrukcija

Produkto spalva	Balta

Energijos valdymas

Įėjimo įtampa	100 - 240 V
Įėjimo dažnis	50 - 60 Hz
Maksimali galia	20 W
Išvesties įtampa (maks.)	20 V
Išvesties įtampa (min.)	4,5 V
1 jungties atiduodamoji galia	18 W
2 jungties atiduodamoji galia	20 W
Suderinamų energijos šaltinio kištukinių lizdų tipai	EU

Svoris ir matmenys

Plotis	36 mm
Ilgis	32 mm
Aukštis	84 mm
Svoris	55 g

Pakuotės duomenys

Pakuotės plotis	113 mm
Pakuotės gylis	103 mm
Pakuotės aukštis	32 mm
Paketo svoris	94 g
Pakuotės tipas	Įpakavimas

Pakuotės turinys

Kiekis pakuotėje	1 vnt
Instrukcija	Taip

Sertifikatai

Atitikties sertifikatai	RoHS, CE
Sertifikavimas	CE, RoHS

Logistikos duomenys

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Kilmės šalis	Kinija
Garantinis laikotarpis	3 metai
Matmenys ir svoris	
Matmenys (I × P × A)	4,00cm × 11,00cm × 10,00cm

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt