

Lindy 47245 networking cable Grey 3 m Cat6 F/UTP (FTP)

 Gamintojas: **LINDY** · Modelis: **47245** · EAN: **4002888472456** · Prekės kodas: **554732**


6,90 €

Kaina su PVM

 Be PVM: **5,70 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Twisted Pair Patch Cable with RJ45 connectors
- ✓ Cat.6 F/UTP, CCA
- ✓ Integrated snagless connector for latch protection
- ✓ Gold plated pins for better conductivity and elimination of signal loss



Aprašymas

Cat.6 F/UTP CCA network cable with support for bandwidth up to 250MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.6 cable for operating frequencies up to 250Mhz in a shielded version with foil shielding (F/UTP). Cat.6 cables are widespread throughout the professional sector. They are ideal for Gigabit Ethernet or AV extension applications. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

The high frequencies used in network technology cause a high current load in the outer layers of the conductors due to the skin effect , while the conductor cores are only subjected to very low electrical loads. This allows the use of copper clad aluminium (CCA) conductor material, making this cable more cost-effective than pure copper cables.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m.

Techninė specifikacija

Specifications	
Sandėlio grupė	Network Cables [+116][-204]
Features	
Cable length	3 m
Cable standard	Cat6
Cable shielding	F/UTP (FTP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Grey
Connector 1 gender	Male
Connector 2 gender	Male
Connector contacts plating	Nickel/Gold
Connector shielding	Yes
Connector shield material	Aluminium
Jacket material	Polyvinyl chloride (PVC)
Conductor material	Copper-Clad Aluminium (CCA)
Cabling technology	10/100/1000Base-T(X)
AWG wire size	26
Frequency	250 MHz
Bend radius (min)	7.2 cm
Operational conditions	
Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-20 - 75 °C
Certificates	
Certification	RoHS, REACH, California Proposition 65
Weight & dimensions	
Outer diameter	6 mm
Connector 1 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Connector 2 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package type	Polybag

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------

Matmenys ir svoris

Matmenys (l × p × A)	25,00cm × 23,00cm × 2,00cm
----------------------	----------------------------