



CHARGER USB UNIVERSAL WHITE/2P TA- UC-2AC12-01 GEMBIRD



Modelis: TA-UC-2AC12-01

Gamintojas: GEMBIRD

EAN: 8716309129558

Prekės kodas: 554829

4.99€

Universal 2-port USB charging adapter, 5 V / 2.4 A

Supports both charging via standard USB port and via Type-C port.

Just plug it into the wall socket to charge your USB-rechargeable device

Supports all smartphones, tablets and other USB devices

- PURE POWER
- 2-ports: charge two devices at once, including Type-C devices
- Perfect for charging your portables
- Suitable for use with your smartphone, tablet or any other USB device

Summary: Gembird TA-UC-2AC12-01. Charger type: Indoor, Power source type: AC, Charger compatibility: Smartphone, Smartwatch, Tablet. Input voltage: 100 - 240 V, Maximum output

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

voltage: 5 V, AC adapter output current: 2.4 A. USB 2.0 ports quantity: 1, USB Type-C ports quantity: 1, Power protection features: Overload, Short circuit. Product colour: White | Vendor Homepage: <https://gembird.nl/item.aspx?id=12955> | Charger compatibility: Smartphone/Smartwatch/Tablet | Charger type: Indoor | Number of outputs: 2 | Number of simultaneously connected devices (max): 2 | Operating principle: Contact | Power protection features: Overload/Short circuit | Power source type: AC | USB 2.0 ports quantity: 1 | USB Power Delivery (USB PD): Yes | USB Power Delivery up to: 12 | USB Type-C ports quantity: 1 | Product colour: White | AC adapter output current: 2.4 | AC adapter power: 24 | Input current: 0.3 | Input frequency: 50/60 | Input voltage: 100 - 240 | Maximum output voltage: 5 | Maximum power: 24 | Output current (5V): 2.4 | Output power: 12 | Port 1 output current: 2.4 | Port 1 output power: 12 | Port 2 output current: 2.4 | Port 2 output power: 12 | Weight: 129 | Package depth: 45 | Package height: 120 | Package type: Hanging box | Package weight: 167 | Package width: 80 | Operating temperature (T-T): 0 - 40 | Compliance certificates: CE/RoHS | Country of origin: China | Model: TA-UC-2AC12-01 | Units per Pallet: 0 | Units per Shipping Box: 48 | Unit Calculated Volume: 0.0007866 | Unit Calculated Weight: 0.1