



WRL ACCESS POINT/DAP140 TELTONIKA



Modelis: DAP140

Gamintojas: TELTONIKA

EAN: 4779051843251

Prekės kodas: 556116

72.00€

The DAP140 is a Teltonika industrial wireless access point with passive PoE-in, designed to enhance Wi-Fi coverage and performance in industrial environments. Featuring Wi-Fi 4 with Wi-Fi mesh and Fast Roaming, as well as dual RJ45 ports and support of up to 50 simultaneous connections, this wireless access point is integral in maintaining reliable connectivity. An integrated DIN rail bracket, 3-pin power connector, and industrial-grade aluminium housing make the DAP140 the ideal access point for industrial applications.

- Seamless Wi-Fi 4 with Wi-Fi mesh & Fast Roaming
- 2 x 10/100 RJ45
- 1 x 3-pin power connector tailored for industrial use
- Easy mounting for plug-and-play deployment

Summary: Teltonika DAP140. 2.4 GHz, Maximum data transfer rate: 300 Mbit/s. Security algorithms: OWE, WPA-EAP, WPA-PSK, WPA2-EAP, WPA2-PSK, WPA3-EAP, WPA3-SAE. Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: Black | Vendor Homepage:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

<https://teltonika-networks.com/products/access-points/DAP140/> | 2.4 GHz: Yes | 5 GHz: No | 6 GHz: No | Cabling technology: 10/100Base-T(X) | Ethernet LAN data rates: 10/100/1000 | Fast roaming: Yes | Maximum data transfer rate: 300 | Maximum data transfer rate (2.4 GHz): 300 | Networking standards: IEEE 802.11b/IEEE 802.11e/IEEE 802.11g/IEEE 802.11k/IEEE 802.11n/IEEE 802.11r/IEEE 802.11s/IEEE 802.11v/IEEE 802.3/IEEE 802.3az/IEEE 802.3u | Wireless meshing: Yes | MAC address filtering: Yes | Security algorithms: OWE/WPA2-EAP/WPA2-PSK/WPA3-EAP/WPA3-SAE/WPA-EAP/WPA-PSK | VPN support: OpenVPN, IPsec, GRE, PPTP, L2TP, Stunnel, DMVPN, SSTP, ZeroTier, WireGuard, Tinc, Tailscale | DHCP client: Yes | DHCP server: Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Supported network protocols: TCP, UDP, IPv4, IPv6, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSL/TLS, ARP, VRRP, PPP, PPPoE, UPNP, SSH, DHCP, Telnet, SNMP, MQTT, Wake On Lan (WOL) | Universal Plug and Play (UPnP): Yes | Command-line interface (CLI): Yes | Web-based management: Yes | Ethernet LAN (RJ-45) ports: 2 | RS-232 interface: No | WAN connection: Ethernet (RJ-45) | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Housing material: Aluminium | International Protection (IP) code: IP30 | LED indicators: Power | Placement: Shelf,Wall | Product colour: Black | Reset button: Yes | Antenna connector type: RP-SMA | Antenna type: External | Built-in processor: Yes | Flash memory: 128 | Internal memory: 16 | Operating system installed: RutOS | Processor frequency: 580 | Depth: 68.6 | Height: 25 | Weight: 150 | Width: 113.1 | Quantity per pack: 1 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Storage relative humidity (H-H): -50 - 75 | Storage temperature (T-T): 10 - 90 | Model name: DAP140000000 | Units per Shipping Box: 20 | Unit Calculated Volume: 0.0011794 | Unit Calculated Weight: 0.259

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903