GIGABYTE UD1000GM PG5 V2 ICE Power Supply Unit- PCIe Gen 5.1, 80 PLUS Gold, Fully Modular Design, 120mm Fan, ATX 3.1 compatible, EU Plug

Gamintojas: **GIGABYTE** · Modelis: **GP-UD1000GM PG5 ICE** · EAN: **4719331556594** · Prekės kodas: **558018**

124,90 €

Kaina su PVM

Be PVM: **103,22 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Intel ATX 3.1 and PCIe Gen 5.1 ready
- ✓ 80 PLUS Gold certified
- ✓ Fully modular design
- ✓ Powerful single +12V rail
- ✓ Compact size
- ✓ 100% Japanese capacitors
- ✓ 120mm smart hydraulic bearing (HYB) fan
- ✓ Optimized thermal solution
- ✓ OVP/OPP/SCP/UVP/OCP/OTP protection

Aprašymas

Ensure reliable and efficient power delivery with GIGABYTE power supplies. Designed for peak performance and durability, our PSUs offer stable and consistent energy to power your high-performance systems. With advanced protections and high-quality components, GIGABYTE power supplies provide the confidence you need for seamless, uninterrupted computing experiences.

Techninė specifikacija

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Specifications	
Sandėlio grupė	PSU [+93][-103]
Power	
Total power	1000 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	15 - 6.5 A
Power factor	0.9
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	125 W
Combined power (+12V)	1000 W
Combined power (+5V)	125 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	15 W
Max output current (+3.3V)	25 A
Max output current (+12V)	83.3 A
Max output current (+5V)	25 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	3 A
Hold time	16 ms
Efficiency	90%
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage
Ports & interfaces	
Motherboard power connector	20+4 pin ATX
Peripheral (Molex) power connectors (4-pin)	3
Motherboard power cable length	61 cm
Number of SATA power connectors	8
PCI Express power connectors (6+2 pin)	4
PCI Express power connectors (12+4 pin)	1
PCI Express power connectors (12+4 pin) cable length	700 mm
PCI Express power cable length	60 cm
CPU power connector (4+4 pin)	Yes
CPU power cable length	65 cm
Floppy drive power connector	1
PCI Express connector	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Number of EPS connectors	2
Cabling type	Fully-Modular
Performance	
Purpose	PC
Power supply unit (PSU) form factor	ATX
80 PLUS certification	80 PLUS Gold
ATX version	3.1
Bearing technology	HYB
Mean time between failures (MTBF)	100000 h
Design	
Product colour	White
Cooling type	Active
Fan diameter	12 cm
Number of fans	1 fan(s)
On/off switch	Yes
Weight & dimensions	
Width	150 mm
Depth	140 mm
Height	86 mm
Weight	2.48 kg
Packaging data	
Package width	618 mm
Package depth	269 mm
Package height	211 mm
Package weight	2.64 kg
Package type	Box
Logistics data	
Warranty period	10 year(s)
Matmenys ir svoris	
Matmenys (I × P × A)	12,00cm × 26,00cm × 22,00cm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.
www.shopro.lt · info@shopro.lt · +370 693 39903