

DELL Pro P P2726HE computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD LCD Grey

Gamintojas: **DELL** · Modelis: **210-BVKQ** · EAN: **5397321029519** · Prekės kodas: **559006**



254,90 € ~~281,91 €~~

Kaina su PVM

Be PVM: **210,66 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 27" LCD IPS
- ✓ Full HD, 16:9, 1920 x 1080
- ✓ 120Hz, 5ms
- ✓ USB Hub, USB PD (96W)



Aprašymas

Equipped for seamless productivity, this 27-inch FHD hub monitor offers extensive connectivity, up to 100W of power delivery, and TÜV-certified 4-star eye comfort.

Techninė specifikacija

Specifications

Sandėlio grupė Monitors [+296][-472]

Display

Display diagonal 68.6 cm (27")

Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LCD
Touchscreen	No
HD type	Full HD
Panel type	IPS
Response time	8 ms
Screen shape	Flat
Contrast ratio (typical)	1500:1
Maximum refresh rate	120 Hz
Display number of colours	16.7 million colours
LED backlight	Yes
Backlight type	Edge LED
Display brightness (peak)	300 cd/m²
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1600 x 900, 1920 x 1080 (HD 1080)
Supported video modes	1080p, 720p, 576p, 480p
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Response time (fast)	5 ms
Pixel pitch	0.3114 x 0.3114 mm
Pixel density	82 ppi
Viewable size, horizontal	59.8 cm
Viewable size, vertical	33.6 cm
Viewable size diagonal	68.6 cm
Digital horizontal frequency	30 - 135 kHz
Digital vertical frequency	48 - 120 Hz
Surface hardness	3H
sRGB coverage (typical)	99%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes

Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	No
Built-in camera	No
Design	
Market positioning	Consumer
Product colour	Grey
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	No
USB upstream port type	USB Type-C
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	2
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	96 W
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort out quantity	1
DisplayPort out version	1.4
HDCP	Yes
HDCP version	1.4
Network	
Ethernet LAN	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Cable management	Yes
Cable lock slot type	Kensington

Adjustable height (max)	15 cm
Pivot	Yes
Pivot angle	-90 - 90°
Swivelling	Yes
Swivel angle range	-45 - 45°
Tilt adjustment	Yes
Tilt angle range	-5 - 21°
On Screen Display (OSD)	Yes
Power	
Energy efficiency class (SDR)	D
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	15 kWh
Power consumption (typical)	14.9 W
Power consumption (standby)	0.5 W
Power consumption (max)	205 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	2.5 A
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%
Operating altitude	0 - 5000 m
Non-operating altitude	5000 - 12192 m
Weight & dimensions	
Width (with stand)	610.7 mm
Depth (with stand)	192.3 mm
Height (with stand)	534.6 mm
Weight (with stand)	6.14 kg
Width (without stand)	610.7 mm
Depth (without stand)	50 mm

Height (without stand)	354.7 mm
Weight (without stand)	4.5 kg
Bezel width (side)	6.4 mm
Bezel width (top)	6.4 mm
Bezel width (bottom)	1.2 cm
Packaging data	
Package weight	8.92 kg
Packaging content	
Stand included	Yes
Cables included	Power, USB Type-C to USB Type-C
Sustainability	
Sustainability certificates	ENERGY STAR, TCO, TCO10, EPEAT, EPEAT Gold, EPEAT Climate +
Doesn't contain	PVC/BFR, Arsenic, Mercury
Carbon footprint	
Total carbon footprint (kg of CO2e)	186
Carbon emissions, manufacturing (kg of CO2e)	90.95
Carbon emissions, logistics (kg of CO2e)	17.86
Carbon emissions, energy usage (kg of CO2e)	62.87
Carbon emissions, end-of-life (kg of CO2e)	14.51
PAIA version	GaBi version 2, 2026
Other features	
Compliance certificates	RoHS
Matmenys ir svoris	
Matmenys (l × p × A)	82,00cm × 15,00cm × 46,00cm