



Minix P165 GaN Wall Charger with 3x USB-C and 1x USB-A Ports



Modelis: NEO-P165

Gamintojas: MINIX

EAN: 4897016411823

Prekės kodas: 560851

64.99€

Minix P165 GaN Wall Charger (3x USB-C, 1x USB-A)

The Minix P165 is a high-performance wall charger with a maximum power output of 165 W, featuring 4 ports—3x USB-C and 1x USB-A—that allow for simultaneous charging of multiple devices. Thanks to GaN (gallium nitride) technology, it delivers high power while maintaining compact dimensions of 68 × 76 × 33 mm. Support for the PD 3.1 standard and dynamic power management ensure that charging is fast, stable, and tailored to the connected devices.

Modern GaN technology - more power in a smaller form factor

The use of GaN technology allows for high performance while reducing the device's size. The charger maintains a compact form factor while delivering up to 165 W of power, which means you can power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

demanding devices without needing multiple power adapters.

Four ports - convenient charging of multiple devices simultaneously

The P165 model offers three USB-C ports and one USB-A port, providing great flexibility for everyday use. USB-C1 supports up to 140 W, USB-C2 up to 100 W, USB-C3 up to 30 W, and USB-A up to 22.5 W, allowing you to charge a laptop, smartphone, tablet, or headphones simultaneously. Dynamic power distribution automatically adjusts settings to the connected devices. The charger also supports popular protocols, including PD 3.1/3.0/2.0, PPS, QC 5, and DCP, ensuring compatibility with a wide range of devices. Support for Apple 2.4A, AFC, and FCP further enhances versatility, enabling efficient charging of devices from various manufacturers.

Safety and Smart Power Management

The built-in safety system protects devices from short circuits, overvoltage, overcurrent, and overheating. This allows you to use the charger without worrying about the safety of your connected devices. Smart power distribution ensures stable charging even when multiple devices are connected simultaneously. The charger is equipped with interchangeable Type A (US), Type C (EU), and Type G (UK) plugs, allowing you to use it in various regions around the world. The wide AC input voltage range of 100–240 V makes it suitable for use at home, in the office, and while traveling.

Included:

- Charger with Type A (US) plug
- Type C (EU) plug
- Type G (UK) plug

Manufacturer	Minix
Model	NEO-P165
Maximum power	165 W
Number of ports	4

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.
www.shopro.lt | info@shopro.lt | +370 693 39903

Ports	3x USB-C, 1x USB-A
USB-C1 power	Up to 140 W
USB-C2 power	Up to 100 W
USB-C3 power	Up to 30 W
USB-A power	Up to 22.5 W
Supported protocols	PD 3.1/3.0/2.0, PPS, QC 5, DCP, AFC, FCP, Apple 2.4A
Input power	AC 100–240 V ~ 50/60 Hz, 2 A
Dimensions	68 × 76 × 33 mm
Protections	Short-circuit, overvoltage, overcurrent, thermal
Technology	GaN

GPSR Link: https://psr-assets.innpro.pl/gsm_accessories/sg_gsm_accessories_chargers.pdf, Gross weight: 370, Net weight: 300, Box length: 15,00, Box width: 12,50, Box height: 4,50, PPWR: <https://ppwr.innpro.pl/minix>