



Review monitor 7 F700



Modelis: B0DF5FWYJS

Gamintojas: NEEWER

EAN: 6976831832469

Prekės kodas: 560895

339.99€

F700 7" Overview Monitor

The F700 Overview Monitor is a 7" Full HD touchscreen display that is ideal for professional video applications. With an impressive resolution, brightness of up to 2,000 nits and a wide 160° viewing angle, the image remains clear and readable even in bright sunlight, without the need for a sun visor. The monitor supports automatic and manual backlight adjustment, which ensures comfort regardless of the working conditions. The F700 is a reliable tool for any filmmaker, which significantly improves the efficiency of work and the quality of shots - both in the studio and in the field.

Comprehensive monitoring functions

The F700 is equipped with a range of professional tools to support exposure, focus and frame composition, such as False Color, histogram, vectorscope, Focus Peak, safety markers and audio bar. You also gain the ability to upload up to 60 of your own 3D LUT files (and use 15 uploaded ones) for quick color correction in the field. REC-709-compliant calibration guarantees accurate color

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

reproduction and high detail. With a resolution of 1920 x 1080 and a brightness of 2,000 nits, the displayed image is always clear and legible.

4K signal support and user-friendly interface

An advanced interface and support for HDMI Loop In & Out (up to 4K) ensure smooth operation in a variety of shooting scenarios. The monitor supports a wide range of video signal resolutions and offers a 3.5mm headphone output for simultaneous audio monitoring (headphones not included). What's more, shortcut buttons (F1, F2, F3) allow quick access to the most important functions.

Flexible power supply and mobility

The monitor can be powered in several ways - with an NP-F battery (F550, F750, F970), a 12V/3A power adapter or via a USB-C port. Two NP-F750 rechargeable batteries with 4400 mAh capacity are included, providing a total of up to 4.8 hours of operation. In addition, the F700 can act as a battery to power the camera (DC 8V/1.5A), making it ideal for outdoor shooting.

Freedom of mounting and active cooling

Thanks to the 1/4" mounting threads on the bottom and side and the included cold-shoe mount, the monitor can be easily adapted to various configurations. The mount allows 180° adjustment, and a fan cooling system with four modes (auto, low, medium, high) ensures stable operation even during long shooting sessions.

Included

- monitor
- monitor mount
- USB to Type-C charging cable
- HDMI to HDMI cable
- HDMI to Micro HDMI cable
- HDMI to Mini HDMI cable
- user manual

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Manufacturer	Neewer
Model	F700
Resolution	1920x1080
Dot spacing	0.0804 (H) x 0.0804 (W) (mm)
Aspect ratio	16:9
Brightness	2000nit ±10%
Contrast ratio	1000:1
Viewing angle	>160°H/160°V; 80°/80°(L/R) 80°/80°(U/D)
Input	HDMI
Output	HDMI, 3.5mm headphone jack
Power input/output	DC 5.5mm input interface: DC 12-26V (cannot be used as a replacement battery when output voltage is low); DC 2.5mm output interface: DC 8.4V (you can connect the power cable to the camera via the DC power output interface, which greatly extends the battery life of the camera); Type-C input interface: Supports fast chargers 5V/3A and higher or portable chargers (3A output)
Support for HDMI input formats	480i, 576i, 480p, 576p, 720p (60/59.94/50/30/29.97/25/24/23.98), 1080i (60/59.94/50), 1080p (60/59.94/50/30/29.97/25/24/24SF/23.98/23.98sF), 3840x2160 (30/25/24Hz), 4096x2160 (25/24Hz).
Total power consumption	≤22W (without DC 8.4V output)
Operating temperature	-20°C-55°C
Storage temperature	-30°C-65°C
Dimensions	175 x 107 x 25 mm

GPSR Link: [https://psr-](https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photo_accessories.pdf)

[assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photo_accessories.pdf](https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photo_accessories.pdf), Gross weight: 1250, Net weight: 709, Box length: 20,00, Box width: 12,50, Box height: 8,00

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903