



Neewer Q4 Flash with Battery

Modelis: 10105783

Gamintojas: NEEWER

EAN: 6976831830335

Prekės kodas: 560926

366.99€

Neewer Q4 Flash with Battery

The NEEWER Q4 400Ws is a portable flash designed for both studio and outdoor photography. It offers 400Ws of power and a high guide number of GN72, making it well-suited for everything from portraits to more demanding product and fashion shoots. The compact housing, weighing approximately 2.24 kg, makes it easy to transport, and the convenient handle allows for comfortable work outside the studio. HSS synchronization up to 1/8000s and a very short flash duration of up to 1/10989s help freeze motion and capture images even in intense daylight.

High-capacity battery and fast continuous shooting

The flash is equipped with a 21.6V lithium battery with a capacity of 2800mAh, which provides approximately 400 full-power flashes. A short recycling time of 0.01 to 1.2 seconds allows for smooth operation during dynamic photo shoots. The ability to shoot in burst mode at up to 20 frames per second makes this model well-suited for sports, event, and reportage photography. An additional

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

advantage is the option to power the flash from the mains using the included adapter.

Precise light control and advanced flash modes

The NEEWER Q4 supports TTL, Manual, and Multi modes, allowing you to easily adapt your workflow to the type of photography. Power adjustment from 1/1 to 1/256 in 0.1-stop increments enables precise flash intensity control. Stroboscopic mode allows for up to 100 flashes at a frequency of up to 199Hz, offering greater possibilities for creative motion shots. The flash also supports first- and second-curtain sync as well as S1 and S2 modes, which facilitate coordination with other light sources.

LED modeling light with natural color rendering

The built-in 30W LED modeling light with a color temperature of 5600K helps you assess the lighting setup before taking the photo. The high CRI of 95+ translates to more natural color rendering, which is important for product and portrait photography. Thanks to the preview of shadows and light direction, it's easier to set up the scene and reduce the number of test flashes.

Wireless Communication and Wide Compatibility

The model uses the NEEWER 2.4G Q wireless system with a range of up to 100 meters. Support for 32 channels and 5 groups allows for convenient control of a larger lighting setup. The flash can also work with the Godox 2.4G X system in RX COMPAT mode and is compatible with the Sekonic L-858D light meter with the RT-GX module. Compatibility with Canon, Nikon, and Sony cameras facilitates integration with popular photography systems.

Bowens mount and convenient operation

The use of a standard Bowens mount allows you to use popular light modifiers, such as softboxes, reflectors, or beauty dishes, without additional adapters. A built-in fan aids cooling during intensive use, and a dot-matrix display improves the ease of adjusting settings. The manufacturer has also equipped the flash with a USB-C port for software updates, an automatic power-saving feature, and an audible signal indicating readiness for the next flash.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Included

- 1 x Q4 Flash
- 1 x Standard Reflector
- 1 x Lithium Battery
- 1 x Handle
- 1 x AC Adapter
- 1 x Power Cord
- 1 x Carrying Case

Manufacturer	NEEWER
Model	Q4
Power	400Ws
Flash duration	1/209s to 1/10989s
Recycle time	approx. 0.01-1.2s
Power adjustment	9 levels (1/256-1/1)
Flash modes	M/Multi (radio off), TTL/M/Multi (radio receiver mode)
Photocell	S1/S2
Flash delay	0.01-30s
Stroboscopic flash	Yes (up to 100 times, 199Hz)
Synchronization	HSS (up to 1/8000 s), first or second curtain
Capacity	400 full-power flashes
Modeling light (LED)	30 W / 5600 K / CRI 95+
Color temperature	5600 ± 200 K
Flash Exposure Compensation (FEC)	Manual; FEB: +/-3 stops in 1/3-stop increments
2.4G Q Radio System	32 channels, 5 groups
Transmission range	100m
Power supply	Lithium battery / DC power adapter (included)
Power Saving	Auto-off after 30-120 min of inactivity

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Triggering Methods	2.4G Radio, S1/S2, 3.5mm sync cable, Test button
Battery Specifications	21.6V / 56Wh / 2800mAh
Additional features	Masking function, built-in silent fan, buzzer, flash duration display, battery level indicator
Display	Dot matrix screen
Net weight with battery (without flash head and reflector)	1.98 kg

GPSR Link: <https://psr->

assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photo_accessories.pdf, Gross weight: 4870, Net weight: 3574, Box length: 36,50, Box width: 23,50, Box height: 31,50