



Neewer Z2-S TTL Speedlite Flash for Sony Cameras

Modelis: 10104959

Gamintojas: NEEWER

EAN: 6921268814472

Prekės kodas: 560935

179.00€

Neewer Z2-S TTL Speedlite Flash for Sony Cameras

The Neewer Z2-S is designed to work with Sony cameras, offering automatic TTL metering, manual mode, and stroboscopic flash. With HSS synchronization up to 1/8000s, you can comfortably shoot in full sunlight without having to sacrifice fast lenses and shallow depth of field. The TCM function allows you to quickly switch from TTL to manual mode while retaining the previously selected flash power.

Even light and a swivel head

The round head design generates softer and more natural light than standard reporter lights. The 76Ws power output works well for both portrait and reportage photography. The head rotates 330° and tilts from -7° to 120°, making it easy to bounce light and create more natural scene lighting.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

LED Modeling Light

Two 2W dimmable LEDs help you assess the lighting setup before taking the shot. The 10-step adjustment allows you to tailor the light intensity to your shooting conditions, making it easier to focus and plan shadows and highlights.

Fast operation and efficient battery

The built-in lithium battery provides up to 600 full-power flashes and a fast recycle time of approximately 1.5 seconds. These specifications are ideal for dynamic sessions and event photography, where quick equipment response times are crucial.

2.4G wireless communication

The flash supports the Neewer 2.4G system with a range of up to 100 meters. The ability to operate as a Master or Slave, along with support for multiple groups and channels, allows for convenient control of an extensive flash setup. Compatibility with the Godox X system further enhances integration capabilities with other photography equipment.

Compatibility with Sony cameras

This model is compatible with many Sony cameras, including the A9 II, A7R V, A7 IV, A7R III, A7S III, A7 III, A1, A6700, A6400, and ZV-E10. The flash is designed to work with both full-frame mirrorless cameras and Sony models featuring an APS-C sensor.

Included

- 1 × flash
- 1 × lithium battery
- 1 × USB-C cable
- 1 × stand (mini tripod)
- 1 × protective case
- 1 × user manual

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Manufacturer	NEEWER
Model	Z2-S
Product type	TTL flash
Compatibility	Sony cameras (including A1, A9 II, A9, A7R V, A7R IV, A7R III, A7R II, A7 IV, A7 III, A7 II, A7, A7S III, A7S II, A7S, A7C II, A7C, A6700, A6600, A6500, A6400, A6100, A6000, A99, A350, ZV-E10)
Flash power	76Ws
Zoom range	28-105 mm (automatic or manual)
HSS sync	up to 1/8000 s
Recycle time	approx. 1.5 s
Flash duration	1/180 s - 1/20000 s
Operating modes	TTL / Manual / Stroboscopic
Power adjustment range	1/1 - 1/256
Exposure compensation	yes
Photoelectric sensor modes	S1 / S2
Wireless system	2.4G Q System / compatible with Godox 2.4G X System
Transmission range	up to 100 m (in open space)
Channels	32
ID	1-99
Master groups	A / B / C / D
Slave groups	A / B / C / D / E
LED modeling light	yes
LED brightness levels	10

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

LED color temperature	3300K ±200K
Power supply	7.4V / 2600 mAh lithium battery
Battery capacity	approx. 480 - 600 flashes at full power
Head movement range	rotation 0°-330°, tilt -7° to 120°
Material	plastic
Dimensions	206 × 76 × 76 mm
Weight	580 g (with battery)

Set: Yes, Adjustable intensity: Yes, GPSR Link: https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf, Gross weight: 930, Net weight: 499, Box length: 24,50, Box width: 13,50, Box height: 10,00