



Wireless Router TP-LINK

**Wireless Router
733 Mbps IEEE
802.11a IEEE
802.11 b/g IEEE
802.11n IEEE
802.11ac USB
2.0 1x10/100M
TL-WR902AC**

Modelis: TL-WR902AC

Gamintojas: TP-LINK

EAN: 6935364095666

Prekės kodas: 565948

33.99€

Portable and compact

The incredibly compact TL-WR902AC is the world's first AC750 travel router. Take it with you to create a personal Wi-Fi spot anywhere internet is available. It fits easily in your pocket, purse or bag

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

and is perfect for use while traveling. Watch movies over private dual-band Wi-Fi at a hotel.

Dual-Band AC for Fast Wi-Fi Speeds

The travel router creates fast AC750 Wi-Fi over dual 2.4 GHz (300 Mbps) and 5 GHz (433 Mbps) bands. Dual bands allow for more devices to be connected to your personal network and provide reliable Wi-Fi access so you can enjoy what you love without interruptions.

Multiple Wi-Fi Modes for Any Situation

Whether you need a private Wi-Fi network while away or something to boost your Wi-Fi at home, the TL-WR902AC has a mode for you.

Multifunctional USB Port for File Sharing and Charging

A The travel router comes with a built-in USB 2.0 sharing port. Connect a USB storage drive to share access to files, download movies and back up recent photos. Connect your smartphone cable and the router doubles as a 5V/1A charging station for one device.

- Transforms any internet connection into a private AC750 dual-band Wi-Fi network*
- Incredibly compact router fits easily in your pocket, purse or bag, perfect for traveling
- Works with 2.4 GHz and 5 GHz devices, including Chromecast and Amazon Fire TV Stick
- USB port lets you share files or conveniently charge any device with up to 5V/1A of power
- Flexible powering options let you connect to an external adapter or USB port

Summary: TP-Link TL-WR902AC. WAN connection type: RJ-45. Wi-Fi band: Dual-band (2.4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 433 Mbit/s. Ethernet LAN interface type: Fast Ethernet, Ethernet LAN data rates: 10,100 Mbit/s, Cabling technology: 10/100Base-T(X). Mobile network generation: 4G. Security algorithms: WEP, WPA, WPA2, Firewall security: SPI | Vendor Homepage: <https://www.tp-link.com/us/home-networking/wifi-router/tl-wr902ac/> | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Wi-Fi standards: 802.11a/802.11b/802.11g/Wi-Fi 5 (802.11ac) | WLAN data transfer rate (first band): 300 | WLAN data transfer rate (max): 433 | WLAN data transfer rate (second band): 433 | 3G/4G USB modem compatibility: Yes | DSL WAN: No | Ethernet WAN: Yes | SIM card slot: No | WAN connection type: RJ-45 | Built-in FTP server: Yes | Cabling technology: 10/100Base-T(X) | Dynamic DNS (DDNS): Yes | Ethernet LAN: Yes | Ethernet LAN data rates: 10/100 | Ethernet LAN interface type: Fast Ethernet | Media server: Yes | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11b/IEEE

802.11g/IEEE 802.11n/IEEE 802.3/IEEE 802.3u | Number of guest networks (2.4 GHz): 1 | Number of guest networks (5 GHz): 1 | Port forwarding: Yes | Port triggering: Yes | Receiver sensitivity: 11a 54M: -76dBm; 11ac VHT20 MCS8: -70dBm; 11ac VHT40 MCS9: -65.5dBm; 11ac VHT80 MCS9: -61.5dBm 2.4GHz: 11g 54M: -76dBm11n; HT20 MCS7: -74dBm; 11n HT40 MCS7: -71dBm | VPN Passthrough: Yes | VPN support: PPTP, L2TP, IPSec | Mobile network generation: 4G | Ethernet LAN (RJ-45) ports: 1 | USB 2.0 ports quantity: 1 | USB port: Yes | Quality of Service (QoS) support: Yes | Reset button: Yes | WPS push button: Yes | DMZ support: Yes | DoS attack prevention: Yes | Filtering: Yes | Firewall: Yes | Firewall security: SPI | Guest access: Yes | IP address filtering: Yes | Security algorithms: WEP/WPA/WPA2 | Stateful Packet Inspection (SPI): Yes | URL filtering: Yes | DHCP client: Yes | DHCP server: Yes | Supported network protocols: IPv4, IPv6 | Universal Plug and Play (UPnP): Yes | Product colour: White | Product type: Portable router | AC adapter included: Yes | Cables included: LAN (RJ-45) | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Quick start guide: Yes | Sustainability compliance: Yes | Antenna design: Internal | Antennas quantity: 2 | Receive power: 11a 54M: -76dBm; 11ac VHT20 MCS8: -70dBm; 11ac VHT40 MCS9: -65.5dBm; 11ac VHT80 MCS9: -61.5dBm, 2.4GHz: 11g 54M: -76dBm11n; HT20 MCS7: -74dBm; 11n HT40 MCS7: -71dBm | Transmit power: CE:20dBm(2.4GHz), 23dBm(5GHz) | Built-in processor: Yes | Processor cores: 1 | Output current: 2 | Output voltage: 5 | Power source type: USB | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Linux operating systems supported: Yes | Mac compatibility: Yes | Mac operating systems supported: Yes | Windows operating systems supported: Yes | Depth: 67 | Height: 22 | Weight: 56.7 | Width: 74 | Package depth: 109 | Package height: 81.5 | Package weight: 299 | Package width: 110 | Harmonized System (HS) code: 85176990 | Product Net Weight: 0.25 | Shipping Box Height: 11 | Unit Calculated Volume: 0.0009922 | Unit Calculated Weight: 0.294 | Units per Shipping Box: 1 | Model name: TL-WR902AC