

Dahua Technology PFS3008-8GT-96 network switch Unmanaged L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: **DAHUA** · Modelis: **CS4006-4ET2GT-36** · EAN: **6939554912986** · Prekės kodas: **566023**



38,90 €

Kaina su PVM

Be PVM: **32,15 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Layer two commercial switch
- ✓ Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards
- ✓ MAC auto learning, aging, MAC address capacity is 8K
- ✓ Supports MDI/MDIX self-adaptation
- ✓ RJ45 port supports 10/100/1000 Mbps self-adaptation
- ✓ Supports IEEE802.3af and IEEE802.3at power supply standards
- ✓ Adopts metal enclosure
- ✓ Supports Hi-PoE 60W
- ✓ Supports DC 48-57V power supply



Aprašymas

- 4 × RJ45 10/100 Mbps PoE ports, 2 × RJ45 Gigabit ports
- 36 W total PoE budget, 802.3af/at on all PoE ports
- DIP switch to fast turn on/off working mode of Cloud-Managed, PoE Watchdog, Long Distance PoE
- Wide operating temperature ranging from -10 °C to 55 °C
- Supports VLAN and loop protection
- WEB-managed and centralized cloud management through the DoLink App and performs real-time monitoring of the network

- Easy config to auto detect and set up network and systems

Summary: Dahua Technology PoE CS4006-4ET2GT-36. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 6. MAC address table: 2000 entries, Switching capacity: 4.8 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3, IEEE 802.3x, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3az, IEEE.... DC input voltage: 53 V. Power connector: DC-in jack. Power over Ethernet (PoE). Form factor: Desktop/Wall-Mounting | Vendor Homepage: <https://transmission.dahuasecurity.com/en/product-list/Business/CloudManagementSolution/NetworkSwitch/CS4006-4ET2GT-36> | Switch type: Managed | Switch layer: L2 | Cloud-managed: Yes | Web-based management: Yes | System event log: Yes | Basic switching RJ-45 Ethernet ports quantity: 6 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Fast Ethernet (copper) ports quantity: 4 | Gigabit Ethernet (copper) ports quantity: 2 | Power connector: DC-in jack | Networking standards: IEEE 802.1Q/IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3az/IEEE 802.3u/IEEE 802.3x | 10G support: No | Port mirroring: Yes | Broadcast storm control: Yes | Flow control support: Yes | VLAN support: Yes | Number of VLANs: 32 | Switching capacity: 4.8 | Forwarding rate: 3.57 | MAC address table: 2000 | Jumbo frames support: Yes | Jumbo frames: 9216 | Packet buffer memory: 4 | DHCP features: DHCP client | Rack mounting: No | Form factor: Desktop/Wall-Mounting | Product colour: Blue | Housing material: Metal | Reset button: Yes | LED indicators: Yes | Mean time between failures (MTBF): 2039146.92 | Power source: DC/PoE | Power supply included: Yes | DC input voltage: 53 | Input current: 0.8 | Power consumption (max): 42.4 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 4 | Total Power over Ethernet (PoE) budget: 36 | Operating temperature (T-T): -10 - 55 | Storage temperature (T-T): -40 - 70 | Operating relative humidity (H-H): 10 - 90 | Storage relative humidity (H-H): 5 - 95 | Width: 84 | Depth: 115 | Height: 27 | Weight: 200 | Cables included: AC | Package width: 114 | Package depth: 195 | Package height: 83 | Package weight: 720 | Compliance certificates: CE | Unit Calculated Weight: 0.746 | Product Net Weight: 0.2 | Unit Calculated Volume: 0.002621 | Units per Shipping Box: 12 | Unit Width: 11.5 | Units per Pallet: 0 | Shipping Box Height: 29.5 | Unit Depth: 20 | Unit Height: 8.5 | Name: NET SWITCH 5PORT 4POE 100M/CS4006-4ET2GT-36 DAHUA | Model name: CS4006-4ET2GT-36

Techninė specifikacija

Specifications	
Sandėlio grupė	Switches [+131][-164]
Management features	
Switch type	Unmanaged
Switch layer	L2
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	8
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Flow control support	Yes
Auto MDI/MDI-X	Yes
MAC address auto-learning supported	Yes

MAC address auto-aging supported	Yes
----------------------------------	-----

Data transmission

MAC address table	8000 entries
-------------------	--------------

Switching capacity	20 Gbit/s
--------------------	-----------

Forwarding rate	11.9 Mpps
-----------------	-----------

Design

Product colour	Black
----------------	-------

Housing material	Metal
------------------	-------

LED indicators	Yes
----------------	-----

Power

DC input voltage	48 - 57 V
------------------	-----------

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
---------------------------	-----

Operational conditions

Operating temperature (T-T)	-10 - 55 °C
-----------------------------	-------------

Operating relative humidity (H-H)	10 - 90%
-----------------------------------	----------

Weight & dimensions

Width	190 mm
-------	--------

Depth	100 mm
-------	--------

Height	30 mm
--------	-------

Weight	490 g
--------	-------

Matmenys ir svoris

Matmenys (I × P × A)	20,00cm × 12,00cm × 9,00cm
----------------------	----------------------------