



**Switch DAHUA
CS4006-4ET2GT-
36 Switch type
Managed Switch
layer L2 Form
factor
Desktop/Wall-
Mounting 6xRJ-
45 ports RJ-45
Ports Type
Gigabit Ethernet
(10/100/1000)
4xFast Ethernet
(copper) ports
quantity
2xGigabit
Ethernet
(copper) ports
quantity Power
over Ethernet**

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(PoE) Yes 4xPower over Ethernet (PoE) ports quantity Total Power over Ethernet (PoE) budget 36 W CS4006- 4ET2GT-36



Modelis: CS4006-4ET2GT-36

Gamintojas: DAHUA

EAN: 6939554912986

Prekės kodas: 566023

38.99€

- 4 × RJ45 10/100 Mbps PoE ports, 2 × RJ45 Gigabit ports
- 36 W total PoE budget, 802.3af/at on all PoE ports
- DIP switch to fast turn on/off working mode of Cloud-Managed, PoE Watchdog, Long Distance PoE
- Wide operating temperature ranging from -10 °C to 55 °C
- Supports VLAN and loop protection
- WEB-managed and centralized cloud management through the DoLynk App and performs real-time monitoring of the network

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Easy config to auto detect and set up network and systems

Summary: Dahua Technology PoE CS4006-4ET2GT-36. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 6. MAC address table: 2000 entries, Switching capacity: 4.8 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3, IEEE 802.3x, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3az, IEEE.... DC input voltage: 53 V. Power connector: DC-in jack. Power over Ethernet (PoE). Form factor: Desktop/Wall-Mounting | Vendor Homepage: <https://transmission.dahuasecurity.com/en/product-list/Business/CloudManagementSolution/NetworkSwitch/CS4006-4ET2GT-36> | Cloud-managed: Yes | Switch layer: L2 | Switch type: Managed | System event log: Yes | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 6 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Fast Ethernet (copper) ports quantity: 4 | Gigabit Ethernet (copper) ports quantity: 2 | Power connector: DC-in jack | 10G support: No | Broadcast storm control: Yes | Flow control support: Yes | Networking standards: IEEE 802.1Q/IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3az/IEEE 802.3u/IEEE 802.3x | Number of VLANs: 32 | Port mirroring: Yes | VLAN support: Yes | Forwarding rate: 3.57 | Jumbo frames: 9216 | Jumbo frames support: Yes | MAC address table: 2000 | Packet buffer memory: 4 | Switching capacity: 4.8 | DHCP features: DHCP client | Form factor: Desktop/Wall-Mounting | Housing material: Metal | LED indicators: Yes | Product colour: Blue | Rack mounting: No | Reset button: Yes | Mean time between failures (MTBF): 2039146.92 | DC input voltage: 53 | Input current: 0.8 | Power consumption (max): 42.4 | Power source: DC/PoE | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 4 | Total Power over Ethernet (PoE) budget: 36 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -10 - 55 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 115 | Height: 27 | Weight: 200 | Width: 84 | Cables included: AC | Package depth: 195 | Package height: 83 | Package weight: 720 | Package width: 114 | Compliance certificates: CE | Model name: CS4006-4ET2GT-36 | Units per Pallet: 0 | Units per Shipping Box: 12 | Unit Calculated Volume: 0.002621 | Unit Calculated Weight: 0.746