

FSP HEXA 85+ PRO 450W Power supply unit ATX ATX2.5 Black

 Gamintojas: **FSP** · Modelis: **HEXA 85+ PRO 450** · EAN: **4713224522703** · Prekės kodas: **566408**


60,90 €

Kaina su PVM

 Be PVM: **50,33 €**

Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Complies with ATX12 v2.5 & EPS12 v2.92
- ✓ Efficiency $\geq 85\%$ at typical load
- ✓ Active PFC ≥ 0.9
- ✓ Hold up time > 17ms at 80% load
- ✓ +12V single-rail design
- ✓ Japanese electrolytic capacitors
- ✓ +5V&3.3V DC to DC module design
- ✓ 120mm silent and long life fan
- ✓ Flat black ribbon cables
- ✓ Complete protection: OCP/OVP/OPP/SCP



Aprašymas

80 Plus® Bronze Certification

HEXA 85+ Pro Series, 80 PLUS ® bronze certified, saves energy through its high efficiency up to 85%.

All Black Round Cables

It gives your system a superior look than any other entry level power supplies.

Stable DC to DC Output Quality

HEXA85+ PRO series applies DC to DC modules to improve the reliability for greater compatibility as well as low ripple noise to reduce interference of system components for a prolonged system lifetime.

+12V Single Rail Design

Designed for power-intensive VGA cards, no problems to any overloading condition.

Optimal Cooling

HEXA 85+ PRO series comes with a 120mm quiet fan and a highly efficient ventilation fan guard to guarantee low noise operations without compromising its cooling efficiency.

Japanese Electrolytic Capacitors

Japanese electrolytic capacitors ensures safety on spare parts for prolonged lifespan and reliability.

Energy Related ErP/Eup 2013

Green Power! The total AC power consumption less than 5Vsb rail to meet the new EU Regulation ErP 2013 for modern systems.

Techninė specifikacija

Specifications	
Sandėlio grupė	PSU [+92][[-104]
Power	
Total power	450 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	6-2.5 A
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	85 W
Combined power (+12V)	450 W
Combined power (+5V)	85 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	12.5 W
Max output current (+3.3V)	16 A
Max output current (+12V)	37.5 A
Max output current (+5V)	16 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	2.5 A
Hold time	17 ms
Efficiency	85%
Power protection features	Over current, Over power, Over voltage, Short circuit
Ports & interfaces	
Motherboard power connector	24-pin ATX
Peripheral (Molex) power connectors (4-pin)	2

Number of SATA power connectors	5
PCI Express power connectors (6+2 pin)	2
CPU power connector (4+4 pin)	Yes
ATX Power connector (24-pin)	Yes
Floppy drive power connector	1
Floppy disk drive connector	Yes
PCI Express connector	Yes
Cabling type	Non-Modular
Performance	
Purpose	PC/Server
Power supply unit (PSU) form factor	ATX
80 PLUS certification	80 PLUS Bronze
ATX version	2.5
EPS version	2.92
Bearing technology	Sleeve
Design	
Product colour	Black
Cooling type	Active
Fan diameter	12 cm
Number of fans	1 fan(s)
Fan location	Top
On/off switch	Yes
Packaging content	
Cables included	CPU, PCIe, Peripheral (Molex), SATA
Weight & dimensions	
Width	140 mm
Depth	150 mm
Height	86 mm
Weight	1.25 kg
Logistics data	
Warranty period	5 year(s)
Harmonized System (HS) code	84733020
Matmenys ir svoris	
Svoris	1,72kg