

APC Smart-UPS nepertraukiamo maitinimo resursai (UPS) „Line-Interactive“ 3 kVA 2700 W 9 AC išvestis(ys / čių)

Gamintojas: **APC** · Modelis: **SMX3000RMHV2UNC** · EAN: **731304272694** · Prekės kodas: **566737**



3 989,90 €

Kaina su PVM

Be PVM: **3 297,44 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ „Line-Interactive“
- ✓ 3 kVA 2700 W
- ✓ Signalų forma: Sinusas
- ✓ 9 AC išvestis(ys / čių)
- ✓ Rūgštinis akumulatorius (VRLA)
- ✓ Stelažas / bokštas Juoda



Peace of mind at home or office with PowerChute™ Serial Shutdown Software. UPS management, greater protection, and energy management software for:



AVR - Automatic Voltage Regulation

Voltage fluctuations can cause damage to data, AVH reliably controls voltage to protect equipment, ensuring stable and consistent power to your connected devices.



Aprašymas

Stay always online and prevent data loss

As soon as the power fails, an APC Smart-UPS immediately supplies emergency power to all connected equipment. Because an APC UPS does this automatically, you prevent unwanted failure of, for example, a PC, server or switch. With the APC PowerChute Network shutdown software, you can even have critical IT hardware shut down automatically and in a controlled manner when the UPS battery is almost empty. This prevents data loss, downtime and physical damage to hardware.

Extend the runtime

You can easily increase the number of minutes that the APC SMX UPS can independently supply emergency power by connecting external battery packs (SMX120RMBP2U). A runtime of several hours is even possible.

Safety

In addition, a Smart-UPS protects connected devices against peak voltage caused by lightning, among other things. This APC emergency power supply is ideally suited for (small) business use.

Manage your Smart-UPS

Thanks to the pre-installed network card (ap9641), you can easily connect the APC UPS to the network. This allows you to monitor and manage the UPS remotely (SNMP) and the UPS can send a shutdown signal to multiple physical and/or virtual servers using PowerChute Network Shutdown software.

PowerChute Network Shutdown

PowerChute Network Shutdown is UPS management software that works with the UPS Network Management Card to protect Windows, Linux and Host ESXi, but also hyperconverged and virtual infrastructure*. In the event of a power failure, PowerChute can shut down your virtual machines correctly and the pre-configured boot sequence ensures that they are turned back on.

*For HCI and virtual machine support an additional license is required:

1 year: SWPCNS**1**Y-DIGI

Up to (Replace bold number in article number with desired variant)

6 years: SWPCNS**6**Y-DIGI

Remote management and monitoring of your network

The network card can be managed externally via the user-friendly web browser interface, remote management software EcoStruxure™ IT (SFTWES1-DIGI) or another SNMP-compatible system. Tip EcoStruxure™ IT also includes the functionalities of the support contract below.

Support contract

The optional network card support contract license* ensures that you are always up-to-date and secure and includes additional benefits such as frequent updates with:

- New and improved functions
- Security updates
- Advanced support

(The functionality of the support contract is included free of charge in the first year of the UPS)

*The above license and available in the variants:

1 year: SWNMC3SU-**1**Y-DIGI

Up to (Replace the bold number in the article number with the desired variant)

6 years: SWNMC3SU-**6**Y-DIGI

Ease of use

The basic functionalities can be set and read using physical buttons and an LCD screen.

Rack/tower convertible

The APC Smart-UPS SMX is rack/tower convertible. Because both the feet and the 4 post rack mounting brackets are included, you can mount it in a rack (2U) or place it upright.

Extend the lifespan

The internal battery cartridge (APCRBC117) can be easily, safely and independently replaced by the user. This without having to switch off the APC SMX3000RMHV2UNC or connected equipment. This allows you to easily and cheaply extend the lifespan of the APC Smart-UPS and your equipment always remains online.

Warranty extension

The factory warranty of the SMX3000RMHV2UNC is 3 years, with the exception of the battery cartridge, which has a factory warranty of 2 years. Both are extended by 3 years to 6 and 5 years respectively with the APC service pack (WBEXTWAR3YR-SP-05).

Switched Outlet Groups: Remote reboot and phased start-up

Thanks to the Switched Outlet Groups, it is possible to configure a phased/delayed power-on per UPS outlet group. This reduces the peak load on the UPS and brings it closer to the constant load, which can limit oversizing of the UPS.

It is also possible to reset a group of multiple UPS outlets and the equipment connected to them. If a network card (ap9640) is used in combination with Ecostruxure IT Expert (SFTWES1-DIGI), this can even be done remotely.

You can also switch off non-critical loads; this extends the runtime for critical equipment.

Included in the box

1x SMX3000RMHV2UNC

1x USB cable

2x C13 to C14 powercord 2 Meter

1x Schuko to C19 input powercord 2 Meter

1x C19 to C20 powercord 2.5 Meter

1x Software CD with PowerChute Network Shutdown Edition

1x Documentation CD

1x British BS1363A to C19 input powercord

2x 4 post rack mounting brackets

1x Temperature sensor

Techninė specifikacija

Features	
UPS topology	Line-Interactive
Output power capacity	3 kVA
Output power	2700 W

Waveform	Sine
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency regulation	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Surge energy rating	645 J
Hold time (min)	2 ms
Hold time (max)	10 ms
Efficiency	98.5%
Emergency Power Off (EPO)	Yes
Noise level	55 dB
Surge protection	Yes
Audible alarm(s)	Yes
Auto-restart	Yes
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler
Power plug	C20 coupler
AC outlets quantity	9 AC outlet(s)
Number of output IEC jumpers	2
SmartSlot	Yes
SmartConnect port	No
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	738 VAh
Typical backup time at full load	6.25 min
Typical backup time at half load	18 min
Battery life (max)	5 year(s)
Battery recharge time	3 h
Hot-swap battery	Yes
Automatic battery test	Yes
Design	
Form factor	Rackmount/Tower
Product colour	Black
Rack capacity	2U

Cable length	2.44 m
LED indicators	Battery replacement
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Certificates	
Compliance certificates	RoHS
Certification	C-tick, CE, EN 50091-1, EN 50091-2, EN 55022 Class A, EN 60950, FCC Part 15 Class A, GOST, IRAM, UL 1778, VDE, REACH, PEP, EOL
Packaging content	
Rack mount kit	Yes
Cables included	RS-232
Management card included	Yes
Manual	Yes
Weight & dimensions	
Width	432 mm
Depth	667 mm
Height	85 mm
Weight	37.3 kg
Packaging data	
Temperature sensor	Yes
Software CD	Yes
Package width	596 mm
Package depth	869 mm
Package height	85 mm
Package weight	45.4 kg
Logistics data	
Products per pallet	8 pc(s)
Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	2723.74

Other features

Nominal output voltage	230 V
Nominal input voltage	230 V
Packaging content	Web/SNMP Management Card

Matmenys ir svoris

Matmenys (I × P × A)	88,00cm × 60,00cm × 26,00cm
----------------------	-----------------------------

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 RUEIL MALMAISON, FR

[se.com](https://www.se.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt