

CLUB3D USB4™ Gen3x2 Type-C, 6-in-1 Hub with HDMI™ 8K60Hz or 4K120Hz, 2xUSB Type-A(10G), Ethernet RJ45(2.5G) and 2xUSB Type-C, 1x Data(10G) and 1xPD3.0 charging 100 watt

Gamintojas: CLUB 3D · Modelis: CSV-1599 · EAN: 8719214472566 · Prekės kodas: 567392



153,90 €

Kaina su PVM

Be PVM: 127,19 €

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Designed for USB4™, Thunderbolt4, Thunderbolt3 and DP 1.4 Alt mode supported Type-C host (PC, laptop, etc)
- ✓ Downwards compatible - Specifications are limited to Source capability
- ✓ Support USB4™ Specification with max 40Gbps bandwidth
- ✓ Compliant USB4™ Gen3x2(40Gbps), USB4™ Gen2x2(20Gbps) and backwards compatible USB3.2&USB2.0
- ✓ Compliant DP1.4 alt mode with max 32.4Gbps
- ✓ HDMI™ supports max 8k60Hz or 4K120Hz video output and High Dynamic Range(HDR10+)
- ✓ USB Type-C data port and 2 USB Type-A support USB 3.2 Gen2 SuperSpeed 10Gbps
- ✓ One USB Type-A and USB Type-C data port support 5V/1.5A downstream charging
- ✓ Fast Ethernet RJ45 supports 10M/100M/1000M/2.5G bandwidth
- ✓ One USB Type-C PD Charging support PD3.0 with max 100W PD Charging, 15W is dedicated to the functioning of this product, the rest power (85W) will be passed to charge for the host



Aprašymas

The Club 3D CSV-1599 is a USB4™ Gen3x2 Type-C, 6-in-1 Hub with HDMI™ 8K60Hz or 4K120Hz, 2xUSB Type-A(10G), Ethernet RJ45(2.5G) and 2xUSB Type-C, 1x Data(10G) and 1xPD3.0 charging 100 watt, this adapter is offering an integrated solution for video, data, power and Ethernet. It has a HDMI™ (8K60Hz) for video transmission, 3 USB data ports (2 USB-A 10G, 1 Type-C 10G)for data transmission, a 2.5Gbps Ethernet port for surfing on line. Besides, this adapter is equipped with Type-C PD3.0 Charging port with max 100W power supply. It can work on USB4™, Thunderbolt4, Thunderbolt3 and DP Alt mode (15W is dedicated to the functioning of this product, the rest power(max 85W) will be passed to charge for the host. This 6-in-1 Hub will work on all DP Alt mode supported Type-C hosts

- Max 10Gbps data transmission
- Support 7.5W(5V@1.5A) downstream charging
- Support short-circuit, over-current, over-voltage protection
- 1x USB Type-C Female (for PD 3.0 Charging)
- Support PD3.0 with max 100W PD Charging
- 15W is dedicated to the functioning of this product, the rest power (85W) will be passed to charge for the host
- Support fast role swap of PD3.0, the connected device will not get disconnected while plugging out PD Adapter;
- 2x USB Type-A Female
- 1- USB Type-A port Data 10G, support max 7.5W(5V@1.5A) downstream charging(closest to RJ45)
- 2- USB Type-A port Data 10G, support max 4.5W(5V@900mA) downstream charging
- 3- Support short-circuit, over-current, over-voltage protection
- 4- USB Type-C and 2 USB Type-A ports share max 2.4A(24W) downstream charging
- 1x RJ45 (Gigabit Ethernet)
- Support 10M/100M/1000M/2.5G bandwidth
- Supports twisted pair crossover detection and auto-correction
- Support WOL(Wake-On-LAN), Full Duplex flow(10M/100M/1G/2.5G Rate), Auto-Negotiation
- Light indicator indicates the state, no light when no Internet connected, orange light turns on when network connection is established, green light flashes when transmitting data.

Techninė specifikacija

Specifications	
Sandėlio grupė	Notebook > Dockingstations/Hubs [+935][-452]
Ports & interfaces	
Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
HDMI ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	2
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
USB Power Delivery up to	100 W
DC-in jack	No
HDCP	Yes
HDCP version	1.4/2.3
Network	
Ethernet LAN (RJ-45) ports	1

Ethernet LAN data rates	10,100,1000 Mbit/s
Performance	
Product colour	Black
Card reader integrated	No
Maximum refresh rate	120 Hz
Hub interfaces	HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C
LED indicators	Yes
Power	
Power supply type	USB
Wireless charging	No
Weight & dimensions	
Width	147 mm
Depth	31 mm
Height	18 mm
Weight	92 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	60 mm
Package depth	240 mm
Package height	35 mm
Package weight	136 g
Packaging composition	
Plastic packaging weight	0 g
Paper/cardboard packaging weight	44 g
Total plastic packaging weight	0 g
Total paper/cardboard packaging weight	0 g
Technical details	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Logistics data	
Harmonized System (HS) code	84733020
Other features	
Overload protection	Yes