Lindy DST-Mini USB-C Laptop Mini Docking Station with 4K Support and 100W Pass-Through Charging

Gamintojas: **LINDY** · Modelis: **43358** · EAN: **4002888433587** · Prekės kodas: **567957**



62.90€ ~~73.89€~~

Kaina su PVM

Be PVM: **51.98€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Adds two USB Type A ports, an HDMI port, Gigabit Ethernet and a Power Delivery port to your notebook
- ✓ Supports 4K 3840x2160 60Hz for an HDMI display
- ✓ Features DisplayPort Alternate Mode
- ✓ USB Power Delivery PD 3.0 capable up to 100W
- ✓ 2 year warranty







Aprašymas

The DST-Mini is a compact, multifunctional mini docking station. Part of Lindy's expert docking station range, this product is great for those who need a lightweight, portable solution but cannot compromise on functionality. With SuperSpeed USB, 4k capability and pass-through charging, this

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

docking station is a great solution for any hybrid worker.

Added Connectivity

The DST-Mini's USB Type A ports are multifunctional. This means that not only do they support SuperSpeed data transfer, but also USB Battery Charging Specification 1.2 for charging mobile devices and other smaller peripherals, quickly. Delivering two USB Type A ports, a PD 3.0 USB-C, 4k HDMI, (Micro-) SD card slots and Gigabit Ethernet, this docking station unlocks a world of connectivity for your device.

Plug-and-Play

The Lindy USB-C Laptop Mini Docking Station 4k HDMI, PD 3.0 100W does not require any driver installation. This allows for seamless large-scale implementation and a hassle-free experience.

Techninė specifikacija

Ports & interfaces	
Connectivity technology	Wired
Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 2.0 ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
HDMI ports quantity	1
Microphone in	No
Headphone outputs	0
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
USB Power Delivery up to	100 W
HDMI version	2
HDCP	Yes
HDCP version	1.4/2.3
Network	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,1000 Mbit/s
Performance	
Product colour	Black
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash), SD
Maximum digital resolution	3840 x 2160 pixels
Maximum analog resolution	3840 x 2160 pixels

Maximum refresh rate	60 Hz
Plug and Play	Yes
Charging function	Yes
Housing material	Aluminium
Certification	CE, FCC, REACH & RoHS, CP65
Operational conditions	
Operating temperature (T-T)	0 - 55 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	10 - 85%
Storage relative humidity (H-H)	10 - 85%
Weight & dimensions	
Width	115 mm
Depth	43 mm
Height	12 mm
Weight	74 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	174 mm
Package depth	194 mm
Package weight	100 g
Packaging content	
Manual	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	15.00cm × 7.00cm × 2.00cm

Dokumentai ir vaizdo įrašai

- User manual
- Product leaflet
- Declaration of conformity

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Gamintojo ir saugos informacija

MANUFACTURER

LINDY International Ltd.
Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB
lindy.com

EU RESPONSIBLE PERSON

LINDY-Elektronik GmbH
Markircher Str. 22, 68229 Mannheim, DE
lindy.com

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

› Declaration of conformity