

WRL ACCESS POINT/TAP100 TELTONIKA

Gamintojas: **TELTONIKA** · Modelis: **TAP100** · EAN: **4779051840182** · Prekės kodas: **568071****37,90 €** ~~39,91 €~~

Kaina su PVM

Be PVM: **31,32 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt

Aprašymas

TAP100 is the first-ever Teltonika Networks Access Point, perfect for strengthening Wi-Fi coverage in small enterprise and commercial spaces. This PoE-in access point can be powered by active PoE devices via its RJ45 port and was designed with simplicity and ease of installation in mind

- POE-IN - Can be powered by PoE devices via RJ45 port
- SLEEK DESIGN - UV-stabilized plastic housing that blends in with its environment
- EASY INSTALLATION - Integrated mounting bracket for easy ceiling setup
- RMS MANAGEMENT - Free access to RMS Management for 24 months

Summary: Teltonika · Accesspoint· TAP100· 2x1· Wi-Fi 4· 300Mbit· 1x 10/100· 15W PoE - Access Point - 0,1 Gbps. 2.4 GHz, Maximum data transfer rate: 300 Mbit/s. Security algorithms: AES-CCMP, TKIP, WPA-PSK, WPA2-EAP, WPA2-PSK, WPA3-EAP, WPA3-SAE. Ethernet LAN data rates: 10,100 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 2 W | Vendor Homepage: <https://teltonika-networks.com/products/access-points/tap100> | 2.4 GHz: Yes | 5 GHz: No | 6 GHz: No | Maximum data transfer rate: 300 | Ethernet LAN data rates: 10/100 | Networking standards: IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.11r/IEEE 802.3/IEEE 802.3az/IEEE 802.3u | Cabling technology: 10/100Base-T(X) | Wi-Fi roaming: Yes | VLAN support: Yes | Security algorithms: AES-CCMP/TKIP/WPA2-EAP/WPA2-PSK/WPA3-EAP/WPA3-SAE/WPA-PSK | MAC address filtering: Yes | Web-based management: Yes | Firmware upgradeable: Yes | Ethernet LAN (RJ-45) ports: 1 | WAN connection: Ethernet (RJ-45) | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Active PoE | DC voltage range: 44 - 57 | Power consumption (max): 2 | Placement: Ceiling,Wall | Product colour: White | Housing material: Plastic | International Protection (IP) code: IP30 | Reset button: Yes | LED indicators: Power | Antenna type: Internal | Built-in processor: Yes | Processor frequency: 580 | Flash memory: 16 | Internal memory: 64 | Certification: IEC 62368-1:2018 EN IEC 62368-1:2020+A11:2020 EN IEC 62311:2020 EN 300 328 V2.2.2 CE, UKCA, CB, FCC, IC, WEEE | Width: 158 | Depth: 30 | Height: 158 | Weight: 190 | Quantity per pack: 1 | Mounting kit: Yes | Operating relative humidity (H-H): 10 - 90 | Operating temperature

(T-T): -40 - 75 | Unit Calculated Weight: 0.243 | Product Net Weight: 0.19 | Unit Calculated Volume: 0.001357 | Units per Shipping Box: 18 | Units per Pallet: 0 | Shipping Box Height: 20 | Name: WRL ACCESS POINT/TAP100 TELTONIKA | Model: TAP100 | Model name: TAP100001000

Techninė specifikacija

Specifications	
Sandėlio grupė	Wireless Access Points [+40][-78]
Matmenys ir svoris	
Matmenys (l × p × A)	18,00cm × 17,00cm × 4,00cm