

CyberPower UT1200EG uninterruptible power supply (UPS) Line-Interactive 1.2 kVA 700 W 4 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **UT1200EG** · EAN: **4712856273427** · Prekės kodas: **568727**



181,90 €

Kaina su PVM

Be PVM: **150,33 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Energy Saving Technology
- ✓ Generator Compatible
- ✓ Overload Protection
- ✓ Phone/Fax/Modem/DSL/Network Protection
- ✓ USB Connectivity Port
- ✓ EMI and RFI Filtration
- ✓ Automatic Voltage Regulation (AVR)
- ✓ LED Status Indicator
- ✓ Surge and Spike Protection
- ✓ High-speed Ethernet Data Transmission



Aprašymas

UT1200EG

CyberPower UT1200EG guarantees power protection for computers, networking equipment, and storage devices. The product adopts line-interactive topology with Automatic Voltage Regulation (AVR) function to offer stabilized AC power output. The patented GreenPower UPS Bypass design achieves ultra-low power consumption to reduce energy costs, and allows a lower operation temperature which extends battery lifespan. The LED indicator shows the utility, battery and operating status of the UPS. It is also compatible with generators to extend power continuity. Other features include overload protection, EMI filter and configurable alarm to safeguard your devices. Its tower design allows users to place it easily on desks or other tight spaces.

Techninė specifikacija

Specifications	
Sandėlio grupė	Stromversorgung > USV [+449][-331]
Features	
UPS topology	Line-Interactive
Output power capacity	1.2 kVA
Output power	700 W
Waveform	Sine
Input operation voltage (min)	165 V
Input operation voltage (max)	290 V
Input frequency	50/60 Hz
Output operation voltage (max)	230 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Maximum current	5.21 A
Surge energy rating	150 J
Response time	4 ms
Heat dissipation	27 BTU/h
Number of input phases	1
Number of output phases	1
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Over voltage, Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm
Ports & interfaces	
AC outlet types	Type F
AC outlets quantity	4 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Ethernet LAN (RJ-45) ports	2
Cabling technology	10/100/1000Base-T(X)
Battery	

Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	6 min
Typical backup time at half load	48 min
Battery recharge time	6 h
Design	
Form factor	Tower
Product colour	Black
Housing material	Plastic
Cable length	1.2 m
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 90%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 3000 m
Certificates	
Compliance certificates	CE, RoHS
Certification	CE, EAC
Packaging content	
Cables included	USB cable
Quick installation guide	Yes
Weight & dimensions	
Width	95 mm
Depth	307 mm
Height	220 mm
Weight	7.6 kg
Packaging data	
Package width	119 mm
Package depth	347 mm
Package height	291 mm
Package weight	7.87 kg
Logistics data	

Harmonized System (HS) code	8504408590
Country of origin	China
Sustainability	
Sustainability compliance	Yes