



**UPS EATON 900
Watts 1600 VA
Wave form type
Pure sinewave
LineInteractive
Phase 1phase
Desktop/pedestal
5E1600UD**

Modelis: 5E1600UD

Gamintojas: EATON

EAN: 3553340704345

Prekės kodas: 568968

224.00€

Eaton 5E Gen2 delivers efficient, affordable power protection for critical applications in both residential and professional settings.

Power protection

Eaton 5E Gen2 UPS protects application and data against power loss.

Double-boost Automatic Voltage Regulation (AVR) technology regulates grid fluctuations (under and overvoltage) to save battery power in the event of power outage.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

A wide product range covers the power requirements of many IT devices.

Auto-restart function enables the UPS to restart automatically when mains power recovers after a total battery discharge.

Easy integration

Eaton 5E Gen2 implements national outlet formats (FR, DIN/IT, BS and IEC) to make application connection and protection easy.

Fanless design up to 1200VA ensures silent operation in residential settings.

Compact housing makes it easy to integrate in home or office.

Easily manage your UPS from your PC (on USB models):

Integrates automatically with Windows / MacOS / Linux power management for safe system shutdown.

Analyse energy usage and manage UPS parameters with Eaton UPS Companion software.

Peace of mind

A leading manufacturer you can trust with decades of experience and high quality standards: CE-certified by an external agency (TUV) according to latest international safety standards.

Know you can depend on batteries round the clock:

5E Gen2 batteries are permanently recharged (even when off).

UPS can start without mains (cold start).

Automatic battery test and battery replacement alarm.

Ensure peace of mind thanks to a two-year warranty.

Summary: Eaton 5E Gen2 1600 USB. UPS topology: Line-Interactive, Output power capacity: 1.6 kVA, Output power: 900 W. AC outlet types: Type F, AC outlets quantity: 4 AC outlet(s). Form factor: Tower, Product colour: Black, Control type: Buttons. Compliance certificates: Low Voltage Directive (LVD), RoHS, WEEE, Certification: EN IEC 62040-1:2019; EN 62040-2:2006; IEC 62040-2: 2016, IEC 62040-3: 2021; CE; EAC; UKCA; Cm; Ukr. Width: 133 mm, Depth: 180 mm, Height: 330 mm | Vendor Homepage: https://www.eaton.com/content/dam/eaton/products/backup-power-ups-surge-it-power-distribution/backup-power-ups/eaton_5e_ups/eaton-5e-ups---emea/eaton-dpq-5egen2-ups-datasheet-en-gb.pdf | Audible alarm modes: Battery replacement | Audible alarm(s): Yes | Auto-restart: Yes | Input frequency: 50/60 | Input operation voltage (max): 240 | Input operation voltage (min): 220 | Noise level: 25 | Output operation voltage (max): 240 | Output operation voltage (min): 220 | Output power: 900 | Output power capacity: 1.6 | Power protection features: Over voltage/Under voltage |

Power source type: AC | UPS topology: Line-Interactive | AC outlet types: Type F | AC outlets quantity: 4 | USB 2.0 ports quantity: 1 | USB port: Yes | Automatic battery test: Yes | Cold start: Yes | Control type: Buttons | Form factor: Tower | Product colour: Black | Operating temperature (T-T): 0 - 40 | Certification: EN IEC 62040-1:2019; EN 62040-2:2006; IEC 62040-2: 2016, IEC 62040-3: 2021; CE; EAC; UKCA; Cm; Ukr | Compliance certificates: Low Voltage Directive (LVD)/RoHS/WEEE | Sustainability compliance: Yes | Depth: 180 | Height: 330 | Weight: 9300 | Width: 133 | Model: 5E1600UD | Units per Shipping Box: 1 | Unit Calculated Volume: 0.036225 | Unit Calculated Weight: 10.5