



Switch TP-LINK ES216G Type L4 ES216G



Modelis: ES216G

Gamintojas: TP-LINK

EAN: 1210002600682

Prekės kodas: 569295

86.99€

Omada Cloud Essentials — A Free and Easy Cloud-Based Network Management

Omada Cloud Essentials is a free, easy-to-use version of the Omada Cloud-based Controller. It provides cloud-based centralized management and monitoring for the Omada networking system, covering access points, switches, and gateways, ideal for surveillance networks and small businesses.

- 16× 10/100/1000Mbps RJ45 ports
- Easy to Use: Supports plug-and-play for instant connectivity and simple configuration for additional features
- Centralized Cloud Management via the web or the Omada app†
- VLAN, Port Isolation, Cable Test△, QoS△ for reliable surveillance networking
- Automatic Loop Prevention and IGMP Snooping
- Fanless design for silent operation

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsilyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Durable metal casing and desktop/rack mounting design

Summary: TP-Link Omada ES216G. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. MAC address table: 8000 entries, Switching capacity: 32 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3i, IEEE 802.3x. Power connector: AC-in jack. Rack mounting | Vendor Homepage: <https://www.omadanetworks.com/my/business-networking/omada-switch-easy-managed/es216g/> | Cloud-managed: Yes | Quality of Service (QoS) support: Yes | Switch layer: L2 | Switch type: Managed | Unified static configuration: Yes | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 16 | Power connector: AC-in jack | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Fast leave: Yes | Flow control support: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1ab/IEEE 802.1p/IEEE 802.1Q/IEEE 802.3ab/IEEE 802.3at/IEEE 802.3i/IEEE 802.3x | Number of VLANs: 32 | Port mirroring: Yes | Virtual LAN features: MTU VLAN/Port-based VLAN/Tagged VLAN | VLAN support: Yes | Zero Touch Provisioning (ZTP): Yes | Forwarding rate: 23.8 | Jumbo frames: 15000 | Jumbo frames support: Yes | MAC address table: 8000 | Packet buffer memory: 4 | Store-and-forward: Yes | Switching capacity: 32 | DHCP features: DHCP client | IGMP snooping: Yes | Loop protection: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | LED indicators: Yes | Product colour: Black | Rack mounting: Yes | Fanless: Yes | Firmware upgradeable: Yes | Flash memory: 64 | Mean time between failures (MTBF): 2131140 | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Power consumption (max): 8.4 | Power source: AC | Power supply included: Yes | Surge protection: Yes | Surge protection voltage: 6 | Power over Ethernet (PoE): No | Heat dissipation: 28.52 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -5 - 50 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 140 | Height: 44 | Width: 294 | Cables included: AC | Rack mount kit: Yes | User guide: Yes | Package type: Box | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Product Net Weight: 0.93 | Shipping Box Height: 36 | Unit Calculated Volume: 0.008379 | Unit Calculated Weight: 2 | Units per Pallet: 0 | Units per Shipping Box: 8 | Model: TP-LINK OMADA ES216G | Model name: ES216G