

Sharp PN-UN553V LCD Indoor

Gamintojas: **SHARP** · Modelis: **PNUN553V** · EAN: **4550556178075** · Prekės kodas: **569790**



3 268,90 €

Kaina su PVM

Be PVM: **2 701,57 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Easy installation – effortless set up with Auto TileMatrix and out-of-the-box calibration. Ready-to-use image presets save time for predefined application scenarios.
- ✓ Enhanced imaging performance – advanced settings of all relevant visual parameters allow full control of brightness, colour, gamma and uniformity via the SpectraView Engine for precise, natural images.
- ✓ Lifelike and consistent colour – experience true to life colour reproduction with IPS panel technology. Uniform visibility is maintained in both landscape and portrait orientation, as well as at wide viewing angles as viewers pass by.
- ✓ Secure reliability and longevity – The metal chassis aids natural heat dissipation while the unique heat management system allows users to monitor and control internal temperatures, safeguarding components against heat build-up.
- ✓ Cost Saving Device Management – save effort whilst managing all connected Sharp and legacy devices from a centralised location by using the NaViSet Administrator 2 software tool.



Aprašymas

Seamless video walls to amplify your brand

Scale up your visual impact with the modular Sharp MultiSync® UN Series, purpose-designed with ultra-narrow bezels to create high-resolution video walls with minimal image interruption.

Advanced intelligent features and imaging performance powered by SpectraView™ ensure precise and consistent visualisation across the entire wall, creating the impression of a single, continuous surface for clear and engaging content presentation.

Engineered for 24/7 operation in public spaces, the series combines robust metal construction with advanced thermal management to deliver reliable, long-lasting performance.

The 55-inch Sharp MultiSync® UN553V draws on its heritage of engineering excellence to deliver a premium experience yet at remarkable value. Positioned to fulfil the requirements of demanding signage applications, it is suited for retail environments, digital-out-of-home media, leisure and museum venues, as well as rental and staging scenarios.

Techninė specifikacija

Specifications	
Sandėlio grupė	Displays > Lcd Monitor [+326][-426]
Display	
Display technology	LCD
Display brightness	500 cd/m²
Display diagonal	139.7 cm (55")
Display resolution	1920 x 1080 pixels
HD type	Full HD
Panel type	IPS
LED backlight	Yes
LED backlighting type	Direct-LED
Native aspect ratio	16:9
Contrast ratio (typical)	3500:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Horizontal scan range	26 - 134 kHz
Vertical scan range	23 - 86 Hz
Haze rate	25%
Colour gamut	72%
Display diagonal (metric)	138.8 cm
Design	
Placement supported	Indoor
Orientation	Horizontal/Vertical
Wall mountable	Yes
VESA mounting	Yes
Panel mounting interface	400 x 400 mm

Ports & interfaces

HDMI ports quantity	3
HDMI input ports quantity	2
HDMI output ports quantity	1
VGA (D-Sub) input ports	1
DisplayPorts quantity	3
DisplayPorts in	2
DisplayPorts out	1
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	2
RS-232 input ports	1
HDCP	Yes
Audio input	Yes
Audio output	Yes

Power

Power consumption (typical)	140 W
Power consumption (standby)	2 W
Energy efficiency scale	A to G
Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	122 kWh

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	1212.7 mm
Depth	106.4 mm
Height	683.5 mm
Weight	28.6 kg

Matmenys ir svoris

Matmenys (I × P × A)	145,00cm × 89,00cm × 32,00cm
Svoris	40,50kg