

CyberPower OLS1000ERT2UA uninterruptible power supply (UPS) Double-conversion (Online) 1 kVA 900 W 8 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **OLS1000ERT2UA** · EAN: **4712856273809** · Prekės kodas: **569863**



565,90 €

Kaina su PVM

Be PVM: **467,69 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Online (Double Conversion) UPS Topology
- ✓ Generator Compatible
- ✓ Zero Transfer Time
- ✓ Extended Battery Module Auto-detection
- ✓ Critical/Non-critical Load Outlets
- ✓ Phone/Fax/Modem/DSL/Network Protection
- ✓ Variable Speed Fans
- ✓ PowerPanel® Management Software
- ✓ Rack/Tower Convertible Configurations



Aprašymas

CyberPower OLS1000ERT2UA is a high-performance UPS featuring online double-conversion topology, which provides seamless Pure Sine Wave power for mission-critical devices such as NAS and servers, DVRs/surveillance systems, transportation and infrastructure, and emergency systems. It's typically integrated in the back office, server room, and data center environment.

The UPS features color LCD panel for users to monitor power system and configure settings easily, and relay-type dry contact to perform local management. This model is designed with extended battery module auto-detection, which can automatically detect the quantity of connected Extended Battery Modules (EBM) to estimate UPS's runtime. The variable speed fans provide automatic thermal management based on power load to reduce noise and provide greater comfort for users.

Techninė specifikacija

Specifications	
Sandėlio grupė	Stromversorgung > USV [+431][-341]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	1 kVA
Output power	900 W
Waveform	Pure sine
Input operation voltage (min)	160 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Maximum current	4.5 A
Surge energy rating	363 J
Response time	0 ms
Efficiency (ECO mode)	95%
Power factor	0.9
Input power factor	0.99
Crest factor	3:1
ECO mode	Yes
Input current Total Harmonic Distortion (THD)	3%
EMI/RFI noise filtering	Yes
Surge protection	Yes
Surge protection features	Modem, Network, Telephone
Power protection features	Surge protection
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler
AC outlets quantity	8 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1

Modem (RJ-11) ports	1
---------------------	---

Ethernet LAN (RJ-45) ports	1
----------------------------	---

Battery

Battery technology	Sealed Lead Acid (VRLA)
--------------------	-------------------------

Battery capacity	9 Ah
------------------	------

Battery voltage	12 V
-----------------	------

Number of batteries supported	2
-------------------------------	---

Typical backup time at full load	4.6 min
----------------------------------	---------

Typical backup time at half load	13.9 min
----------------------------------	----------

Charging current	1.5 A
------------------	-------

Hot-swap battery	Yes
------------------	-----

Replacement battery cartridge	RBP0156
-------------------------------	---------

Design

Form factor	Rackmount/Tower
-------------	-----------------

Product colour	Black
----------------	-------

Housing material	Metal
------------------	-------

Rack capacity	2U
---------------	----

Cable length	1.5 m
--------------	-------

Display type	LCD
--------------	-----

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Storage temperature (T-T)	-20 - 50 °C
---------------------------	-------------

Operating relative humidity (H-H)	20 - 90%
-----------------------------------	----------

Storage relative humidity (H-H)	10 - 90%
---------------------------------	----------

Operating altitude	0 - 1500 m
--------------------	------------

Non-operating altitude	0 - 1500 m
------------------------	------------

Certificates

Certification	CE, EAC, RoHS
---------------	---------------

Packaging content

Cables included	USB cable
-----------------	-----------

Weight & dimensions

Width	438 mm
-------	--------

Depth	430 mm
-------	--------

Height	88 mm
--------	-------

Weight	10.4 kg
Packaging data	
Package width	540 mm
Package depth	550 mm
Package height	230 mm
Package weight	16.2 kg
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China