# APC Smart-UPS nepertraukiamo maitinimo resursai (UPS) „Line-Interactive“ 1 kVA 800 W 8 AC išvestis(ys / čių)

Gamintojas: **APC** · Modelis: **SMX1000I** · EAN: **731304268635** · Prekės kodas: **570361**



**1 140,90 €**

Kaina su PVM

Be PVM: **942,89 €**

**Sandėlyje**

**Prekė internetu**

Nuskenuokite kodą arba apsilankykite www.shopro.lt

## Pagrindinės savybės

- ✓ „Line-Interactive“
- ✓ 1 kVA 800 W
- ✓ Signalų forma: Sinusas
- ✓ 8 AC išvestis(ys / čių)
- ✓ Rūgštinis akumuliatorius (VRLA)
- ✓ Stelažas / bokštas Juoda













## Aprašymas

### Stay always online and prevent data loss

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

As soon as the power fails, an APC Smart-UPS immediately supplies emergency power to all connected equipment. Because an APC UPS does this automatically, you prevent unwanted failure of, for example, a PC, server or switch. With the free APC PowerChute software, you can even have critical IT hardware shut down automatically and in a controlled manner when the UPS battery is almost empty. This prevents data loss, downtime and physical damage to hardware.

## Extend the runtime

You can easily increase the number of minutes that the APC SMX UPS can independently supply emergency power by connecting external battery packs (SMX48RMBP2U).
A runtime of several hours is even possible.

## Safety

In addition, a Smart-UPS protects connected devices against peak voltage caused by lightning, among other things. This APC emergency power supply is ideally suited for (small) business use.

## Network Management Card

If you connect the UPS directly to your network via the optional APC Network Management Card (AP9640/AP9641), it can be easily managed remotely via SNMP or our remote management software Ecostruxure IT Expert (SFTWES1-DIGI). You can also automatically send a shutdown signal via the network to multiple physical and/or virtual servers. By means of the APC PowerChute Network Shutdown Software belonging to the network card, it is even possible to differentiate between the shutdown moment and the order in which this happens.

## Easy to use

This APC Smart-UPS SMX is easy to operate thanks to the LCD screen.

## Rack/tower convertible

The APC Smart-UPS SMX is rack/tower convertible. Because both the feet and the front post rack brackets are included, you can mount it in a rack (2U) or place it upright. If you prefer to mount it on all four rack uprights, order the optional SU032A.

## Extend the lifespan

The internal battery cartridge (APCRBC116) can be replaced easily, safely and independently by the user. This without having to switch off the APC SMX1000I or connected equipment. This allows you to easily and cheaply extend the lifespan of the APC Smart-UPS and your equipment will always remain online.

## Warranty extension

The factory warranty of the SMX1000I is 3 years, with the exception of the battery cartridge, which has a factory warranty of 2 years. Both are extended by 3 years to 6 and 5 years respectively with the APC service pack (WBEXTWAR3YR-SP-02).

## Switched Outlet Groups: Remote reboot and phased start-up

Thanks to the Switched Outlet Groups, it is possible to configure a phased/delayed power-on per UPS outlet group. This reduces the peak load on the UPS and brings it closer to the constant load, which can limit oversizing of the UPS.

It is also possible to reset a group of multiple UPS outlets and the equipment connected to them. If a network card (ap9640) is used in combination with Ecostruxure IT Expert (SFTWES1-DIGI), this can even be done remotely.

You can also switch off non-critical loads; this extends the runtime for critical equipment.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

This APC Smart-UPS is designed for IT managers or network administrators to maintain business uptime, data transfer and continuity during prolonged power outages. The 1000VA line interactive 2U rack/tower UPS provides pure sine wave power to support critical electronics during power disruptions. The SMX comes with IEC 320 C14 input, 8x IEC 320 C13 outlets, and 2x IEC jumper cables. The UPS has a SmartSlot for optional Network Management Card that enables graceful shutdown of physical servers, virtual machines & HCI Clusters via PowerChute Network Shutdown. It comes with IEC 320 C14 input, 8x IEC 320 C13 outlets, and 2x IEC jumper cables. The UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty. This uninterrupted power supply can connect to EcoStruxure IT or third-party centralized management platforms. The SMX UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty. This is compatible with dedicated user-replaceable battery, and the APC replacement battery cartridge helps restore UPS performance to the original specifications. The Smart-UPS comes with a pair of tower-mounting stabilizing feet and rack-mounting brackets. The 2 switchable outlet groups allow more granular management of the power supplied to your devices. The Emergency Power Off feature enables the UPS to remotely shutdown during emergencies.

## Techninė specifikacija

| | |
|---|---|
| **Features** | |
| UPS topology | Line-Interactive |
| Output power capacity | 1 kVA |
| Output power | 800 W |
| Waveform | Sine |
| Input operation voltage (min) | 151 V |
| Input operation voltage (max) | 302 V |
| Input frequency | 50/60 Hz |
| Output frequency regulation | 50/60 Hz |
| Automatic Voltage Regulation (AVR) | Yes |
| Surge energy rating | 600 J |
| Efficiency | 98.2% |
| Emergency Power Off (EPO) | Yes |
| Noise level | 40 dB |
| Surge protection | Yes |
| Audible alarm(s) | Yes |
| Audible alarm modes | Low battery alarm, Overload alarm |
| Auto-restart | Yes |
| **Ports & interfaces** | |
| AC outlet types | C13 coupler |
| Power plug | C14 coupler |
| AC outlets quantity | 8 AC outlet(s) |
| Number of output IEC jumpers | 2 |
| USB port | Yes |
| SmartSlot | Yes |

| | |
|---|---|
| SmartConnect port | No |

## Battery

| | |
|---|---|
| Battery technology | Sealed Lead Acid (VRLA) |
| Battery capacity | 299 VAh |
| Typical backup time at full load | 8.1 min |
| Typical backup time at half load | 24.2 min |
| Battery life (max) | 5 year(s) |
| Battery recharge time | 3 h |
| Hot-swap battery | No |
| Automatic battery test | Yes |
| Cold start | Yes |

## Design

| | |
|---|---|
| Form factor | Rackmount/Tower |
| Product colour | Black |
| Rack capacity | 2U |
| Cable length | 1.83 m |
| LED indicators | Yes |

## Operational conditions

| | |
|---|---|
| Operating temperature (T-T) | 0 - 40 °C |
| Storage temperature (T-T) | -15 - 45 °C |
| Operating relative humidity (H-H) | 0 - 95% |
| Storage relative humidity (H-H) | 0 - 95% |
| Operating altitude | 0 - 3000 m |
| Non-operating altitude | 0 - 15000 m |

## Certificates

| | |
|---|---|
| Compliance certificates | RoHS |
| Certification | CE, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH, PEP, EOLI |

## Packaging content

| | |
|---|---|
| Rack mount kit | Yes |
| Cables included | RS-232, USB cable |
| Management card included | No |
| Quick installation guide | Yes |

## Weight & dimensions

| | |
|---|---|
| Width | 432 mm |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

| | |
|---|---|
| Depth | 490 mm |
| Height | 89 mm |
| Weight | 22.9 kg |
| **Packaging data** | |
| Software CD | Yes |
| Package width | 589 mm |
| Package depth | 620 mm |
| Package height | 246 mm |
| Package weight | 27.3 kg |
| **Logistics data** | |
| Products per pallet | 8 pc(s) |
| Harmonized System (HS) code | 85078000 |
| Total carbon footprint (kg of CO2e) | 1153.31 |
| **Other features** | |
| Nominal output voltage | 230 V |
| Nominal input voltage | 230 V |
| Packaging content | Removable support feet |
| **Matmenys ir svoris** | |
| Matmenys (I × P × A) | 63,00cm × 35,00cm × 24,00cm |

## Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

## Gamintojo ir saugos informacija

GAMINTOJAS

**Schneider Electric SE**
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

**MB KOMPIUTERIŲ GURU**
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.