



Access Point TP-LINK 11000



Mbps IEEE

802.11a/b/g IEEE

802.11n IEEE

802.11ac IEEE

802.11ax

1x2.5GbE

EAP772

Modelis: EAP772

Gamintojas: TP-LINK

EAN: 8885020623055

Prekės kodas: 570395

217.99€

Ultra-Thin Enterprise WiFi 7 Access Point

- Next-Gen WiFi 7
- Wi-Fi Speeds up to 9214 Mbps
- Multi-Link Operation (MLO)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- 1× 2.5G RJ45 Port
- PoE Power
- Ultra-Thin Design
- Centralized Cloud Management
- Omada Mesh Technology

Ultra-Thin Design for Flexible Deployment

The overall design of EAP772 utilizes a thinner circular arc with a groove around the top cover, fitting closer to various installation surfaces such as ceilings. The compact internal hardware layout and heat-dissipating design ensure high performance with a sharp aesthetic.

Boosted Network Security

- Secure Guest Network with up to 24 SSIDs
- Boost Your Business with SMS Login
- WPA3 for Worry-Free Open Public Networks
- Rogue AP Detection

- BE9300 Tri-Band Wi-Fi 7 (5760 Mbps on 6 GHz + 2880 Mbps on 5 GHz + 574 Mbps on 2.4 GHz)
- A clear 6 GHz band brings cleaner and wider band resources
- 1× 2.5G Port unlocks the full potential of Wi-Fi 7
- 320 MHz bandwidth enables many more simultaneous transmissions
- Multi-Link Operation and Multi-RUs ensure the high performance of your network
- Advanced Functions: Centralized management, mesh, and AI roaming

Summary: TP-Link Omada BE9300 Ceiling Mount Tri-Band Wi-Fi 7 Access Point. 2.4 GHz, 5 GHz, 6 GHz, Maximum data transfer rate: 9300 Mbit/s. Security algorithms: SNMP, SNMPv2, SNMPv3, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal,.... Ethernet LAN data rates: 2500 Mbit/s. Product colour: White | Vendor Homepage: <https://www.tp-link.com/nl/business-networking/omada-wifi-wifi7/eap772/> | 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: Yes | Airtime Fairness (ATF): Yes | BeamForming: Yes | Bluetooth: Yes | Bluetooth version: 5.2 | Ethernet LAN data rates: 2500 | Maximum data transfer rate: 9300 | Maximum data transfer rate (2.4 GHz): 574 | Maximum data transfer rate (5 GHz): 2880 | Maximum data transfer rate (6 GHz): 5760 | MIMO: Yes | MIMO type: Multi User MIMO | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11ax/IEEE

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

802.11b/IEEE 802.11be/IEEE 802.11g/IEEE 802.11n | Number of users: 380 | Quality of Service (QoS) support: Yes | VLAN support: Yes | Access Control List (ACL): Yes | MAC address filtering: Yes | Number of SSID supported: 24 | Remote Authentication Dial-In User Service (RADIUS): Yes | Security algorithms: SNMP/SNMPv2/SNMPv3/WPA2-Enterprise/WPA2-Personal/WPA3-Enterprise/WPA3-Personal/WPA-Enterprise/WPA-Personal | Service Set Identifier (SSID) features: Multiple SSIDs | Web-based management: Yes | Ethernet LAN (RJ-45) ports: 1 | LED indicators: Yes | Placement: Ceiling,Wall | Product colour: White | Antenna type: Internal | Certification: CE, FCC, RoHS, IC | Depth: 220 | Height: 32.5 | Width: 220 | AC adapter included: No | Mounting kit: Yes | Quantity per pack: 1 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Model name: EAP772 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.006817 | Unit Calculated Weight: 1.41