

CyberPower PR2200ELCDSXL uninterruptible power supply (UPS) Line-Interactive 2.2 kVA 1980 W 9 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **PR2200ELCDSXL** · EAN: **4712856275599** · Prekės kodas: **572310**



1 002,90 €

Kaina su PVM

Be PVM: **828,84 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive UPS Topology
- ✓ Energy Saving Technology
- ✓ Active PFC Compatible
- ✓ Pure Sine Wave Output
- ✓ Automatic Voltage Regulation (AVR)
- ✓ Overload Protection
- ✓ Hot-swappable Batteries
- ✓ Surge and Spike Protection
- ✓ EMI and RFI Filtration
- ✓ LCD Status Display



Aprašymas

CyberPower PR2200ELCDSXL Line-Interactive UPS, with seamless Pure Sine Wave, provides the best power protection available for office system devices including PCs, workstations, networking devices, and peripherals. It's typically integrated in the back office, server room, and data center environment.

The UPS can be locally managed via USB or serial ports, or remotely managed via an SNMP Card (an optional Remote Management Card), allowing administrators and users unsurpassed flexibility to remotely access each UPS through the network to perform real-time monitoring, UPS configurations, and scheduled system shutdowns by using PowerPanel Management software. The product is also certified to be interoperable and compatible with Cisco, which helps to achieve the best energy performance possible.

Techninė specifikacija

Specifications	
Sandėlio grupė	Stromversorgung > USV [+434][-323]
Features	
UPS topology	Line-Interactive
Output power capacity	2.2 kVA
Output power	1980 W
Waveform	Pure sine
Input operation voltage (min)	151 V
Input operation voltage (max)	301 V
Input frequency	50/60 Hz
Output operation voltage (min)	230 V
Output operation voltage (max)	230 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Maximum current	16 A
Surge energy rating	405 J
Response time	4 ms
Number of input phases	1
Number of output phases	1
Output power factor	0.9
Power Factor Correction (PFC) type	Active
Emergency Power Off (EPO)	Yes
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler
Power plug	C20 coupler
AC outlets quantity	9 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1

USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	1
RS-232 ports	1
Emergency Power Off (EPO) connector	Yes
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	1
Typical backup time at full load	2.5 min
Typical backup time at half load	9.5 min
Battery recharge time	8 h
Hot-swap battery	Yes
Design	
Form factor	Tower
Product colour	Black
Cable length	3.05 m
Control type	Buttons
Display type	LCD
LED indicators	Power
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Certificates	
Compliance certificates	CE, RoHS
Packaging content	
Cables included	Power load cable, Serial, USB cable
Manual	Yes
Weight & dimensions	
Width	170 mm

Depth	432 mm
Height	221 mm
Weight	25.5 kg
Packaging data	
Package width	316 mm
Package depth	579 mm
Package height	360 mm
Package weight	27 kg
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Other features	
Battery type	RBP0116
Sustainability	
Sustainability compliance	Yes