



TACENS MARS MCPU-X3 90 PWM 190W CPU cooler

Modelis: TACMARS-MCPUX3

Gamintojas: TACENS

EAN: 8435693113355

Prekės kodas: 572714

15.98€

Type: Air cooler | Anti-vibration system: Yes | Fan current: 0.2 A | Suitable location: Processor | Product colour: Black | Weight: 248 g | Radiator material: Aluminum | LED voltage: 5 V | Thermal grease: Yes | Base plate material: Copper | Fan power consumption: 2.4 W | Fan speed (min): 800 RPM | Fan's mean time to failure (MTTF): 60000 h | Fan speed (max): 2600 RPM | Fan voltage: 12 V | Supported processor sockets: LGA 1151 (Socket H4) | Fan noise level (min): 9 dB | Supported processor sockets: LGA 1150 (Socket H3) | Package type: Box | Supported processor sockets: LGA 775 (Socket T) | Manual: Yes | Package depth: 105 mm | Width: 93 mm | Package width: 145 mm | Pulse-width modulation (PWM) support: Yes | Fan noise level (max): 28 dB | Maximum air pressure: 1.25 mmH2O | Height: 132 mm | Thermal Design Power (TDP): 150 W | Fan dimensions (W x D x H): 90 x 25 x 90 mm | Depth: 64 mm | Bearing type: Hydraulic | Maximum airflow: 67 cfm | Fan connector: 4-pin | Fan diameter: 9 cm | Fins material: Aluminium | Number of fans: 1 fan(s) | Supported processor sockets: Socket AM4 | Supported processor sockets: Intel LGA1851 | Quantity per pack: 1 pc(s) | Minimum air pressure: 0.8 mmH2O | Number of heat pipes: 3 | Illumination LED: Yes | Illumination colour: Multi | Supported processor sockets: LGA 1366 (Socket B) | Supported

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

processor sockets: Socket AM5 | Package height: 117 mm | Supported processor sockets: LGA 1200 (Socket H5) | Supported processor sockets: LGA 1156 (Socket H) | Supported processor sockets: LGA 1700 | Supported processor sockets: LGA 1155 (Socket H2) | Supported processor sockets: LGA 1851