



IP camera Hikvision DS- 2CD1343G2- LIU(2.8mm)

Modelis: DS-2CD1343G2-LIU

Gamintojas: HIKVISION

EAN: 6942160472737

Prekės kodas: 572720

92.99€

Certification: FCC: 47 CFR Part 15, Subpart B, EN 55032: 2015, EN 61000-3-2:2019, EN 61000-3-3: 2013+A1:2019, EN 50130-4: 2011 +A1: 2014, RCM: AS/NZS CISPR 32: 2015, IC: ICES-003: Issue 7, UL 62368-1, IEC 62368-1: 2014+A11, CE-LVD: EN 62368-1: 2014/A11: 2017, IS 13252 (Part 1): 2010/IEC 60950-1: 2005, CE-RoHS: 2011/65/EU, WEEE: 2012/19/EU, Reach: Regulation (EC) No 1907/2006 | Number of lenses: 1 | Networking standards: IEEE 802.3af | Type: IP security camera | Package height: 141 mm | Web-based management: Yes | Password protection: Yes | DC output voltage: 12 | Operating temperature (T-T): -30 - 60 °C | Noise reduction: Yes | Mounting type: Ceiling/wall | LED type: IR | Built-in HDD: No | Camera shutter speed: 1/3 - 1/100000 s | Region of Interest (ROI) encoding: Yes | Product colour: White | Ethernet LAN: Yes | Angle of rotation: 360° | Viewing angle, vertical: 54° | Camera tilt control: Yes | Number of users: 32 user(s) | Power source type: DC, PoE | Power consumption (max): 5 W | Image quality adjustment: White balance | Camera pan control: Yes | Image quality adjustment: Sharpness | Weight: 340 g | Infrared (IR) cut-off filter: Yes | Connectivity technology: Wired | Heartbeat: Yes | Housing material: Plastic | Progressive scan: Yes | Supported graphics resolutions: 640 x 480 (VGA) | Bit rate: 32 Kbps - 8 Mbps | Video motion

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

detection: Yes | Privacy masking: Yes | Storage relative humidity (H-H): 0 - 95% | Total megapixels: 4 MP | Pan range: 0 - 360° | Supported graphics resolutions: 2560 x 1440 | Gain control type: Auto | Package weight: 560 g | Height: 89.2 mm | Operating relative humidity (H-H): 0 - 95% | Ethernet LAN (RJ-45) ports: 1 | Optical sensor size: 25.4 / 3 mm (1 / 3") | Viewing angle, horizontal: 98° | Wide Dynamic Range (WDR): Yes | Night vision distance: 30 m | Tilt angle range: 0 - 75° | Number of sensors: 1 | Supported graphics resolutions: 640 x 360 | Video streaming: Yes | Storage temperature (T-T): -30 - 60 °C | Form factor: Turret | Infra-red wavelength: 850 nm | Package width: 150 mm | Bluetooth: No | Video compression formats: H.264 | Maximum resolution: 2560 x 1440 pixels | Video compression formats: H.264+ | Wi-Fi: No | Sensor type: CMOS | Video compression formats: H.265 | Supported graphics resolutions: 1280 x 720 (HD 720) | DC output current: 0.4 A | Housing material: Metal | Maximum aperture number: 1.6 | Number of cameras: 1 | Day/night mode: Yes | International Protection (IP) code: IP67 | Mirror: Yes | Image quality adjustment: Saturation | Video compression formats: H.265+ | Dedicated application: Hik-Connect (Android, iOS) | Image quality adjustment: Brightness | Viewing angle, diagonal: 114° | Quality of Service (QoS) support: Yes | Package depth: 150 mm | Power consumption (Power over Ethernet (PoE)): 6.5 W | Built-in microphone: Yes | Night vision: Yes | Placement supported: Outdoor | Noise reduction technology: 3D noise reduction | Video compression formats: M-JPEG | Diameter: 11 cm | Digital watermark: Yes | Frame rate: 20 fps | Image quality adjustment: Contrast | Fixed focal length: 2.8 mm | Supported graphics resolutions: 1920 x 1080 (HD 1080)