



**Hikvision Pro
Series with
AcuSense DS-
2CD2046G2H-
IU(2.8mm)(eF)
Bullet IP
security camera
Outdoor 2688 x
1520 pixels
Ceiling/wall**

Modelis: DS-2CD2046G2H-IU(2.8mm)(eF)

Gamintojas: HIKVISION

EAN: 6942160420707

Prekės kodas: 572721

149.99€

Password reset via email: Yes | Number of simultaneous live view channels: 6 channels | User access level: Administrator, Operator, User | Pixel counter: Yes | Audit log: Yes | Compliance certificates: UL | Network access storage (NAS): Yes | Compliance certificates: Low Voltage Directive (LVD) |

Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: CB | Flash log:

Yes | Automatic Network Replenishment (ANR): Yes | Number of Privacy masking areas: 4 | Maximum

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be

išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

resolution: 2688 x 1520 pixels | Product colour: Black | Reset button: Yes | Product colour: White | Power source type: DC, PoE | Weight: 525 g | Connectivity technology: Wired | Built-in microphone: Yes | Supported graphics resolutions: 1280 x 720 (HD 720) | Bluetooth: No | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 640 x 360 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Tilt angle range: 0 - 90° | Security algorithms: TLS | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.1x | Web-based management: Yes | Security algorithms: HTTPS | Mirror: Yes | Heartbeat: Yes | Active tampering alarm: Yes | Privacy protection: Yes | Number of sensors: 1 | Power consumption (Power over Ethernet (PoE)): 7 W | Number of languages: 33 | Behavior analysis: Intrusion detection, Line crossing detection | Infrared (IR) cut-off filter: Yes | Number of lenses: 1 | Live view: Yes | Languages support: Multi | Dynamic range: 120 dB | Infra-red wavelength: 850 nm | Digest authentication: Yes | Video compression formats: H.265 | Video motion detection: Yes | Mounting type: Ceiling/wall | Day/night mode: Yes | Video compression formats: H.264+ | Noise reduction: Yes | DC output voltage: 12 | Built-in HDD: No | Maximum aperture number: 1 | Video compression formats: H.265+ | Video compression formats: H.264 | Number of users: 32 user(s) | Video compression formats: M-JPEG | Protection features: Water resistant | Recognize distance: 12 m | Ethernet interface type: Fast Ethernet | DC output current: 0.45 A | Operating temperature (T-T): -30 - 60 °C | Operating relative humidity (H-H): 0 - 95% | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | Progressive scan: Yes | Package width: 234 mm | Night vision distance: 40 m | Package weight: 750 g | Image quality adjustment: Sharpness | Video streaming: Yes | Optical sensor size: 25.4 / 3 mm (1 / 3") | Image quality adjustment: Saturation | Storage temperature (T-T): -30 - 60 °C | Package depth: 120 mm | Lens viewing angle, diagonal: 119.7° | Intelligent Video Surveillance (IVS) system features: Face detection | Compatible memory cards: MicroSDXC | Smart IR: Yes | Compatible memory cards: MicroSD (TransFlash) | Total megapixels: 4 MP | Region of Interest (ROI) encoding: Yes | Image quality adjustment: Contrast | Compatible memory cards: MicroSDHC | Form factor: Bullet | Wi-Fi: No | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Fixed focal length: 2.8 mm | Card reader integrated: Yes | Lens mount interface: M12 | Client interoperability: iVMS-4200, Hik-Connect, Hik-Central | Detect distance: 63 m | Night vision: Yes | Placement supported: Outdoor | Length: 179.2 mm | Number of cameras: 1 | Lens viewing angle, vertical: 54.7° | Minimum illumination: 0 lx | Diameter: 7.44 cm | Observe distance: 25 m | Lens viewing angle, horizontal: 100.2° | Signal-to-Noise Ratio (SNR): 52 dB | Human and vehicle targets classification: Yes | Sensor type: CMOS | Power consumption (max): 5.5 W | Ethernet LAN: Yes | Angle of rotation: 360° | Noise reduction technology: 3D noise reduction | Wide Dynamic Range (WDR): Yes | Maximum memory card size: 512 GB | Package height: 117 mm | HTTPS encryption: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

| IP address filtering: Yes | International Protection (IP) code: IP67 | Image quality adjustment: Brightness | LED type: IR | Privacy masking: Yes | Password protection: Yes | Bit rate range: 8 - 320 Kbit/s | Type: IP security camera | Storage relative humidity (H-H): 0 - 95% | Identify distance: 6 m | Sample rates: 8 - 48 kHz | Housing material: Metal | Bit rate: 32 Kbps - 8192 Kbps | Quality of Service (QoS) support: Yes | Highlight Compensation (HLC): Yes | Pan range: 0 - 360° | Audio formats supported: MP2L2 | Frame rate: 30 fps | Audio formats supported: PCM | Camera shutter speed: 1/3 - 1/100000 s | Audio formats supported: AAC-LC | Audio formats supported: G.711 μ -law | Audio formats supported: G.711 A-law | Audio formats supported: G.726 | Audio formats supported: G.722.1 | Audio formats supported: MP3 | Browser supported: IE 10, IE 11, Chrome 57.0+, Firefox 52.0+