

Hikvision Value Series DS-2CD1163G2-LIU(2.8MM) Dome IP security camera Indoor & outdoor 3200 x 1800 pixels Ceiling

Gamintojas: **HIKVISION** · Modelis: **DS-2CD1163G2-LIU 2.8mm PL** · EAN: **6942160472881** · Prekės kodas: **572722**



108,90 €

Kaina su PVM

Be PVM: **90,00 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Live view: Yes | Operating temperature (T-T): -30 - 60 °C | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | Manual: Yes | Night vision distance: 30 m | Bluetooth: No | Number of sensors: 1 | International Protection (IP) code: IP67 | Minimum illumination: 0 lx | Number of cameras: 1 | Number of simultaneous live view channels: 6 channels | Mounting type: Ceiling | Infrared (IR) cut-off filter: Yes | Supported graphics resolutions: 2560 x 1440 | Lens viewing angle, horizontal: 105° | Storage temperature (T-T): -30 - 60 °C | Number of languages: 1 | Wide Dynamic Range (WDR): Yes | Power consumption (Power over Ethernet (PoE)): 7.5 W | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 640 x 480 (VGA) | Lens viewing angle, diagonal: 127° | Package width: 150 mm | Housing material: Plastic | Languages support: Polish | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Number of Privacy masking areas: 4 | Image quality adjustment: Sharpness | Image quality adjustment: Saturation | Height: 97.6 mm | Storage relative humidity (H-H): 0 - 95% | IK code: IK08 | Image quality adjustment: Contrast | Package weight: 800 g | Tilt angle range: 0 - 75° | Dynamic range: 120 dB | Housing material: Metal | Type: IP security camera | Supported graphics resolutions: 640 x 360 | Ethernet LAN: Yes | Video recording: Yes | Heartbeat: Yes | DC output current: 0.5 A | Operating relative humidity (H-H): 0 - 95% | Supported network protocols: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP | Infra-red wavelength: 850 nm | Networking standards: IEEE 802.3af | Ethernet interface type: Fast Ethernet | Supported graphics resolutions: 3200 x 1800 | Maximum resolution: 3200 x 1800 pixels | Mirror: Yes | Compliance certificates: CB | Product colour: White | Wi-Fi: No | Package depth: 150 mm | Identify distance: 7 m | Image quality adjustment: Brightness | Built-in light: Yes | Form factor: Dome | Package height: 141 mm | Video motion detection: Yes | Privacy masking: Yes | Compliance certificates: WEEE | Compliance certificates: BIS | Connectivity technology: Wired | Number of lenses: 1 | DC output voltage: 12 | LED type: IR/White | Compliance certificates: REACH | Compliance certificates: UL | Built-in microphone: Yes | Night vision: Yes | Power source type: DC, PoE | Power consumption (max): 6 W | Number of users: 32 user(s) | Weight: 550 g | Compliance certificates: RoHS | Compliance certificates: CE | Password protection: Yes | Mounting kit: Yes | Placement supported: Indoor & outdoor | Bit rate range: 16 - 160 Kbit/s |

Sample rates: 8 - 16 kHz | Lens viewing angle, vertical: 55° | Video formats supported: H.265+ | Video formats supported: H.264+ | Video formats supported: H.265 | Pan range: 0 - 355° | Diameter: 12.1 cm | Sustainability compliance: Yes | Highlight Compensation (HLC): Yes | Total megapixels: 6 MP | Video formats supported: H.264 | Digital Wide Dynamic Range (DWDR): Yes | Fixed focal length: 2.8 mm | Frame rate: 20 fps | Signal-to-Noise Ratio (SNR): 52 dB | Recognize distance: 15 m | HTTPS encryption: Yes | Angle of rotation: 355° | User access level: Administrator, Operator, User | Progressive scan: Yes | Video compression formats: H.264+ | Video compression formats: H.265 | Day/night mode: Yes | Video compression formats: H.265+ | Video compression formats: H.264 | Supported video modes: 360p | Noise reduction: Yes | Supported video modes: 480p | Supported video modes: 1080p | Supported video modes: 720p | Supported video modes: 1440p | Maximum aperture number: 1.6 | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Noise reduction technology: 3D noise reduction | Camera shutter speed: 1/100000 - 1/3 s | Audio formats supported: PCM | Audio formats supported: MP2L2 | Observe distance: 30 m | Detect distance: 76 m | Audio formats supported: AAC-LC | Audio formats supported: G.711 µ-law | Audio formats supported: G.722.1 | Sensor type: CMOS | Audio formats supported: G.711 A-law | Built-in HDD: No | Password reset via email: Yes

Techninė specifikacija

Specifications	
Sandėlio grupė	Video cameras [+0][-0]
Matmenys ir svoris	
Matmenys (I × P × A)	14,00cm × 15,00cm × 15,00cm
Svoris	0,65kg